



Toll Free: 87 PERMATEX
(877-376-2839)

10 Columbus Blvd., Hartford,
Connecticut 06106

6875 Parkland Boulevard, Solon
Ohio 44139

Technical Data Sheet

Permatex® Anti-Seize Lubricant

AAM Revised 10/17

PRODUCT DESCRIPTION

Permatex® Anti-Seize Lubricant is a heavy duty, high temperature lubricant that prevents galling, seizing and corrosion during assembly and assures easier disassembly. Also reduces wear in heavy pressure applications. The product contains a refined blend of aluminum, copper and graphite lubricants that can be used on slow moving parts. Meets or exceeds the requirements of Military Specification Mil-A-907E.

PRODUCT BENEFITS

- Effectively lubricates assemblies exposed to high temperatures and heavy contact pressures
- Suitable for service up to 870°C (1,600°F)
- Reduce corrosion and seizing due to weathering or chemicals
- Permits easy disassembly of parts exposed to heat or corrosive environments
- Brush-top aerosol available

TYPICAL APPLICATIONS

- Spark plug threads
- Exhaust manifold and engine bolts
- Anchor pins on brake assemblies
- U-bolts and spring bolts
- Lubricates and permits easy disassembly of assemblies exposed to high temperatures and heavy contact pressures, such as boiler and oven parts, jet engines, and industrial turbines.
- Hinges, gears, chain, sprockets and rollers

DIRECTIONS FOR USE

1. Clean mating surfaces before application
2. For best results, apply to clean, dry surfaces.
3. Clean surfaces with Permatex® Brake & Parts Cleaner.
4. Wire brush any loose surface rust.
5. Apply Anti Seize to the parts that require protection.
6. Reassemble parts using normal torque values.
7. Wipe off excess material.
8. Clean brush on aerosol product to make future applications easier.

For Cleanup

1. Clean parts of excess material with disposable towel.
2. Clean hands with Permatex® brand hand cleaners.

PROPERTIES OF MATERIAL

	Typical Value
Chemical Type	Grease
Appearance	Silver metallic paste
Odor	Light petroleum
Specific Gravity	1.13
Temperature Range, °C (°F)	-60(-51) to 870 (1,600)
Viscosity, poise	1000 - 2000
Flash Point	>350°F

GENERAL INFORMATION

WARNING: Not for use on wheel lug nut or stud applications.

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected for use with chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

Ordering Information

Part Number	Container Size
09975	4 gm pouch
80071	4 oz. bottle
80078(133K)	8 oz. brush-top bottle
80206	1 gallon pail
80208(767)	16 oz. brush-top bottle
80210	20 gram stick
81343(133AR)	1 oz. tube

Storage

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8° and 28°C (46° and 82°F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range.

Note

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.

NOT FOR PRODUCT SPECIFICATIONS.
THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.
PLEASE CONTACT PERMATEX, INC., TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.
PERMATEX, INC., HARTFORD SQUARE NORTH, 10 COLUMBUS BOULEVARD, HARTFORD, CT 06106 PHONE - (1-87PERMATEX)