



ALLPRO® Corporation  
Brandon, FL 33511

## Technical Bulletin

### PRO PATCH™ Vinyl Spackling

AP13116  
July 2012

#### Description

**PRO PATCH™** Vinyl Spackling Compound is formulated to fill cracks and holes in plaster, wallboard, wood and many other types of interior / exterior construction surfaces. **PRO PATCH™** requires no mixing and is very easy to use. **PRO PATCH™** is bright white, sands smooth, won't crack and cleans up with water.

#### Prominent Features

- Interior / Exterior
- Ready to Use
- Easy to Apply

Repair Cracks, Dents and Wall Defects on:

- Wood
- Plaster
- Sheetrock
- Stucco
- Masonry

#### Uses

Exterior applications must be top-coated with good quality exterior paint. Not to be used on structural cracks. Do not use as a joint sealant where expansion and contraction might occur. Do not use as a skim coat for smoothing rough surfaces. Do not apply to surfaces where water ponding may occur. Keep from freezing.

#### Surface Preparation

Surface must be dry and free of dirt, dust, oil, mildew, loose paint, old caulk or other contaminates.

#### Application

Apply only when sealant surface and air temperature are above 50°F and rising. Do not apply on surfaces above 120° F or when rain is expected. Apply with a clean putty knife. Press compound as far into hole as possible. For repairs deeper than  $\frac{1}{4}$  " apply two or more layers, as needed, allowing time to dry between applications. Backer material may be required. Sand may be added for modelling textured plaster. Allow to dry 4 to 8 hours before sanding or painting with oil-based products.

#### Clean-Up

Clean all equipment immediately after use with warm, soapy water.

#### Disposal

Unused paste can contain trace quantities of vinyl acetate monomers which may cause adverse effects to the environment if disposed of improperly. Contact your local sanitation department or household hazardous waste coordinator for information concerning the correct procedure for disposal of containers which still contain unused material. All material must be disposed in accordance with Federal, State, and Local Regulations.

#### Limited Warranty

Manufacturer warrants that this product when properly stored and applied, will perform as intended. If product does not, return proof of purchase to Manufacturer for replacement of product. Manufacturer shall not be held liable for damages in excess of the purchase price of the product. This is the sole and exclusive remedy and liability for defects or failure of this product. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, WRITTEN OR ORAL, STATUTORY, EXPRESSED OR IMPLIED; INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS.

<u>Caution</u>	<u>Technical Information</u>										
<p><b>Do not take internally</b></p> <p><b>WARNING!</b> May cause eye, skin &amp; respiratory irritation, or allergic skin reaction. Harmful if swallowed or absorbed through skin. Overexposure may cause adverse kidney, cardiovascular &amp; liver effects. Use only with adequate fresh air ventilation. Avoid contact with eyes, skin &amp; clothing. Wear gloves &amp; safety glasses. See MSDS for additional safety information. For an MSDS, contact your supplier, visit <a href="http://www.allprocorp.com/technical.cfm">www.allprocorp.com/technical.cfm</a> or call 518-237-3330.</p> <p><b>NOTICE:</b> For emergency information call ChemTrec at 800-424-9300. For additional safety information, refer to the Material Safety Data Sheet for this product. Obtain professional advice before using. Close container after each use.</p> <p><b>WARNING:</b> This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.</p> <p><b>Material Safety Data Sheets (MSDS) available upon request.</b> Similar information for solvents and other chemicals used with ALLPRO products should be obtained from your supplier(s). When solvents are used, proper safety precautions must be observed.</p> <p><b>FIRST AID:</b> In case of skin contact, wash off quickly with plenty of soap and water, remove contaminated clothing. For eye contact flush eyes immediately with large quantities of water, for at least 15 minutes. Obtain emergency medical treatment. If swallowed, obtain medical treatment immediately. <b>DO NOT INDUCE VOMITING.</b> If inhalation causes physical discomfort, remove to fresh air. If discomfort persists or any breathing difficulty occurs, get medical help.</p> <p><b>Warning:</b> When scraping, sanding, or removing old paint, you may release lead dust. <b>LEAD IS TOXIC.</b> Exposure to lead dust can cause serious illness. This can include brain damage, especially in children. Pregnant women are also particularly at risk, and should avoid exposure. Always use a NIOSH approved respirator to control lead exposure. Clean up area with a HEPA vacuum and a wet mop. Before starting any project that may expose individuals to paint dust, find out how to protect yourself, your co-workers, and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD.</p> <p>Manufactured For: ALLPRO® Corporation Brandon, FL, 33511</p> <p>Note: The information, ratings and opinions stated above pertain to the material currently offered and represent the results of tests and calculations believed to be reliable.</p>	<p><b>Packaging:</b> Standard packaging: 4 gallons per case 6 quarts per case 24 1/2 pints per case</p> <p><b>Color:</b> White</p> <p><b>Physical &amp; Chemical Characteristics</b></p> <p><b>Weight per Gallon:</b> 12.9 to 13.9 lbs.</p> <p><b>Total Non-Volatiles:</b> 76 to 80 % <b>Vertical Slump:</b> less than 1/4 inch <b>Clean up: (before cure):</b> water <b>Freeze/Thaw Stability:</b> Passes 5 freeze/thaw cycles <b>Shelf Life:</b> 12 to 18 month sun opened at room temperature</p> <p><b>Drying Time:</b> Typically 4-8 hours, before sanding. Complete through drying in 24 to 36 hours, depending on size of patch, temperature and humidity.</p> <p><b>Odor:</b> Mild latex</p> <p><b>Analysis:</b></p> <table> <tbody> <tr> <td>Aqueous Polymer Solution</td> <td>Nonhazardous</td> </tr> <tr> <td>Calcium Carbonate</td> <td>1317-65-3 75</td> </tr> <tr> <td>Water</td> <td>7732-18-5</td> </tr> <tr> <td>Silica, crystalline</td> <td>14808-60-7</td> </tr> <tr> <td>Ethoxylated Nonylphenol</td> <td>[mixture]</td> </tr> </tbody> </table> <p>Contents Partially Unknown</p>	Aqueous Polymer Solution	Nonhazardous	Calcium Carbonate	1317-65-3 75	Water	7732-18-5	Silica, crystalline	14808-60-7	Ethoxylated Nonylphenol	[mixture]
Aqueous Polymer Solution	Nonhazardous										
Calcium Carbonate	1317-65-3 75										
Water	7732-18-5										
Silica, crystalline	14808-60-7										
Ethoxylated Nonylphenol	[mixture]										

