

# PATH-PRO<sup>®</sup>

## SERIES



**90 DAY**  
LTD. COMMERCIAL  
WARRANTY

**3 YEAR**  
LTD. RESIDENTIAL  
WARRANTY

### MANEUVERABILITY AND DURABILITY COMBINED.

While lightweight and easy to move, the Path-Pro<sup>®</sup> is no pushover. A single stage that performs like a two stage, Path-Pro<sup>®</sup> features a tireless Ariens<sup>®</sup> AX engine, a 12.2-inch housing height and 8.375-inch paddles capable of clearing up to 9 inches of snow straight down to the pavement.

#### HOUSING & PADDLE

Steel-walled housing shreds through snow, while the reinforced rubber paddles and adjustable scraper bar provide a clean to the pavement finish.

#### EASY STORAGE

Our folding handlebars allow this unit to be stored in tight places.

#### QUICK-ACCESS COVER

With an easy-access maintenance hatch, we make it easy to keep your Ariens<sup>®</sup> Sno-Thro<sup>®</sup> running like an Ariens.

#### WHEELS

Enjoy the mobility and agility of semi-pneumatic wheels.

#### AVAILABLE REMOTE CHUTE

Remote chute rotation gives you the power to let snow fly in any direction you please. Available on specific models.

#### ELECTRIC START

Go ahead. Hit snooze. We promise your Path-Pro will be up and at 'em as soon as you start.

## PRODUCT SPECIFICATIONS

DESIGNATION	PATH-PRO® 208E	PATH-PRO® 208EC
MODEL #	938032	938033
STAGE TYPE	SINGLE STAGE	SINGLE STAGE
ENGINE POWER	208CC (9.5 FT/LBS)	208CC (9.5 FT/LBS)
ENGINE BRAND	ARIENS® AX	ARIENS® AX
STARTING SYSTEM	120V/RECOIL	120V/RECOIL
CLEARING WIDTH	21 IN (53.3 CM)	21 IN (53.3 CM)
HOUSING HEIGHT	12.2 IN (31 CM)	12.2 IN (31 CM)
THROWING DISTANCE	3 - 35 FT (.9 - 10.7 M)	3 - 35 FT (.9 - 10.7 M)
CHUTE TURNING RADIUS	210°	210°
CHUTE ROTATION	MANUAL	REMOTE
DEFLECTOR CONTROL	MANUAL	MANUAL
TIRE SIZE	7.5 X 1.75 IN (19.1 X 4.4 CM)	7.5 X 1.75 IN (19.1 X 4.4 CM)
TIRE TYPE	N/A	N/A
STEERING	SOLID UNLOCKED	SOLID UNLOCKED
DRIVE TYPE	AUGER PROPELLED	AUGER PROPELLED
SPEEDS	1 FORWARD	1 FORWARD
GEAR CASE	N/A	N/A
GEAR CASE WARRANTY	N/A	N/A
IMPELLER PROFILE	STEEL 3 BLADE	STEEL 3 BLADE
IMPELLER DIAMETER	N/A	N/A
AUGER DIAMETER	8.375 IN (21.3 CM)	8.375 IN (21.3 CM)
AUGER TYPE	REINFORCED RUBBER	REINFORCED RUBBER
SKID SHOES	N/A	N/A
SCRAPER BAR	POLYMER ADJUSTABLE	POLYMER ADJUSTABLE
PRODUCT WARRANTY	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM
LENGTH	54.3 IN (137.9 CM)	54.3 IN (137.9 CM)
WIDTH	21.6 IN (54.9 CM)	21.6 IN (54.9 CM)
HEIGHT	40.9 IN (103.9 CM)	40.9 IN (103.9 CM)
WEIGHT	95 LBS (43.1 KG)	97 LBS (43.9 KG)
ACCESSORIES AT A GLANCE	FLOOR MAT, REMOTE CHUTE ROTATION KIT, SNO-THRO COVER, HIGH WEAR PADDLES	FLOOR MAT, REMOTE CHUTE ROTATION KIT, SNO-THRO COVER, HIGH WEAR PADDLES



Registered trademark and ™ trademark of AriensCo. Kawasaki®, Kohler® and Hydro-Gear® are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit Ariens.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary. © Copyright 2020 AriensCo. All rights reserved. 0720

VISIT [ARIENS.COM](https://www.ariens.com) FOR DETAILS

AN **ARIENS|CO** BRAND