





250 CFM/5.0 Sones (Horizontal) @ 0.10" SP. 220 CFM/5.5 Sones (Vertical) @ 0.10" S.P. 230 CFM/5.5 Sones (Round) @ 0.10" S.P.

Dimensions

Overall bottom projection - 22" Overall top projection -12" Height - 6" Available widths: 30" & 36"

Hood Body

23 gauge cold rolled steel, laser welded, coated with a baked enamel finish or stainless steel.

Motor

High efficency PSC 4 pole motor. Two speed, thermally protected, permanently lubricated. Rated 115/120 Volts, 60 hz.

Lighting

Two - GU10 base, MR16, 50 watt Halogen lights with 2 brightness settings

<u>Ducting Options</u>


Horizontal ducting: $3\frac{1}{4}$ "x10" (duct adapter and damper included). Vertical ducting: $3\frac{1}{4}$ "x10" (duct adapter and damper included). Vertical ducting: 7" round (duct adapter and damper included). Ductless: removable damper, top vent (charcoal filter not included).


Blade

Polymeric axial fan blade 10-3/8" diameter with 5 paddles.

Electrical connection

Hood top - 7/8" knockout hole for use with 1/2" cable clamp Hood back - 7/8" knockout hole for use with 1/2" cable clamp





Filters

UL rated, class 2 filter. Grease Filter (30" models): GF-09S (included). Grease Filter (36" models): GF-10S (included). Charcoal Filter (30" models): CF-09S (not included). Charcoal Filter (36" models): CF-10S (not included).

Available Finishes

Stainless Steel (AB30SS, AB36SS), White (AB30WH, AB36WH) Black (AB30BL, AB36BL)

EXPANDED PERFORMANCE										
		Static Pressure (inches of w.g.)						Fan Speed	Power	
Air Flow - CFM	0	0.1	0.125	0.15	0.2	0.25	@ .1 SP	RPM	Watts	Amps
Horz Ducting	300	250	236	221	191	161	5.0	1670	67.0	1.6
Vert Ducting	279	220	205	190	158	127	5.5	1680	65.4	1.6
Round Ducting	302	230	207	183	137	96	5.5	1680	65.0	1.6

PROJECT							ARCHITECT			
LOCATION							ENGINEER			
CONTRACTOR							SUBMITTED BY DATE			
FAN NUMBER	MODEL Number	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS	



Air King: 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 • 877-304-3785 Fax: (610) 696-8048 Canada: Brampton, Ontario Tel: 905-456-2033 Fax: (905) 456-1015

Specifications subject to change without notice. Updated 2-18