



ALLPRO® Corporation
Tampa, FL 33619

Technical Bulletin

Paint Thinner-Mineral Spirits

AP5920-22000PS
AP5920-22001PS
AP5920-22002PS
AP5920-22003PS
May, 2019

Description

Quality Thinner for Oil-Based Paints, Varnishes & Enamels
Improves Brushing Quality. Effective Cleaner & Degreaser for Painting Tools

Prominent Features

- » 100% Mineral Spirits
- » Quality Thinner For Oil-Based Paints, Varnishes & Enamels
- » Improves Brushing Quality
- » Effective Cleaner & Degreaser for Painting Tools

Uses

Thins and Cleans.

Limitations

Application

Carefully read all cautions and instructions before use. Protect hands with solvent-resistant gloves, and eyes with safety glasses. Open can slowly to relieve pressure

Disposal

Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Place empty containers in normal refuse for disposal. Contact your local sanitation department or household hazardous waste coordinator for information concerning possible reuse or disposal of unused solvent-containing products.

| <u>Caution</u> | <u>Technical Information</u> |
|--|--|
| <p>WARNING! DANGER! EXTREMELY FLAMMABLE. KEEP AWAY FROM HEAT, SPARKS, FLAME AND ALL OTHER SOURCES OF IGNITION. VAPORS MAY CAUSE FLASH FIRE OR IGNITE EXPLOSIVELY. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone. Beware of static electricity that may be generated by synthetic clothing and other sources. Whenever possible, use outdoors in open air area. Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms or small enclosed areas. USE ONLY WITH ADEQUATE VENTILATION TO PREVENT BUILDUP OF VAPORS. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering - STOP - ventilation is inadequate. Leave area immediately. DANGER! May be harmful or fatal if swallowed. Vapor harmful. Skin and eye irritant. Contains Petroleum Distillates. Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Intentional misuse of this product by deliberately concentrating and inhaling can be harmful or fatal. For further information, refer to the Material Safety Data Sheet. This product should not be used frequently or on a regular basis without properly engineered air control systems designed to prevent exceeding appropriate TLV. It is intended for occasional use only. Do not take internally. Avoid prolonged or repeated breathing of vapors or mist and contact with skin and eyes. Close container after each use. Do not reuse this container. For OSHA controlled work place and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors. FIRST AID - IF SWALLOWED, do not induce vomiting. Call your poison control center, hospital emergency room or physician immediately for instructions. IN CASE OF EYE CONTACT, immediately flush with water for at least 15 minutes. Get medical attention. FOR SKIN CONTACT, wash with soap and water. If irritation persists, get medical attention. KEEP OUT OF REACH OF CHILDREN.</p> <p>Manufactured For: ALLPRO® Corporation Tampa, FL 33619</p> <p>Note: The information, ratings and opinions stated above pertain to the material currently offered and represent the results of tests and calculations believed to be reliable.</p> | <p>Packaging: 'F' style metal container 1 (5g) per case 2 (2.5g) per case 6 gallons per case 12 quarts per case</p> <p>Weight Per Gallon: 7.48 lbs./gal. excluding container Boiling Range: 316° - 399°F Vapor Density: 4.9 % Solids By Weight: 0% % Solids By Volume: 0% Photochemical Reaction: Non-Photochemically reactive Flash Point: 109° F (T.C.C.) CPSC Flamm. Class.: II Storage: Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Store locked up. Keep out of the reach of children. Store away from other materials. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations</p> <p>MAX Vapor Pressure: 0 mm Hg at 20° C Air Quality Data: MAX VOC 98.0 VOL 768.3 g/l</p> <p><u>Analysis CAS</u> Mineral Spirits (64742-88-7) Stoddard Solvent (8052-41-3) 1,2,4-Trimethylbenzene (95-63-6) Nonane (111-84-2) Toluene (108-88-3) Naphthalene (91-20-3) Ethylbenzene (100-41-4)</p> |
| | |
| | |