

Builder's Best, Inc. 201 Broiles Drive Jacksonville, TX 75766 888-368-7233 fax: 800-259-8368 www.BuildersBest.com

## **V830 BUILDER'S BEST® PIPE**




## **DESCRIPTION**

SAF-T-DUCT® Dryer Venting is the trusted solution for professional installers nationwide. These parts are available in several retail programs. It meets all clothes dryer manufacturer specifications. Heavy duty aluminum, Snap-Lock™ fittings, unique elbows and periscopes round out this line.

# PRODUCT SPECIFICATIONS • 5', 6', 8', and 12' lengths

- 4" diameter
- 8' length compressed to 24"
- Snap-Lock™ Fittings: One collar crimped (male), one collar slotted (female)
- Available with and without clamps









## PART NUMBERS

| Diameter                     | Length | Part # | Qty | Package      |
|------------------------------|--------|--------|-----|--------------|
| 4"                           | 6'     | 110129 | 12  | Display Bag  |
|                              | 6'     | 010016 | 12  | Display Tray |
|                              | 5'     | 110138 | 15  | Bulk         |
|                              | 6'     | 110107 | 12  | Bulk         |
|                              | 8'     | 110120 | 20  | Bulk         |
|                              | 12'    | 110079 | 20  | Bulk         |
| With two steel screw clamps: |        |        |     |              |
| 4"                           | 6'     | 110092 | 12  | Bulk         |

Builder's Best® Flexible pipe is designed to Snap-Lock™ to elbows (like the Close Elbow™pictured) or to other pieces of V830 for longer runs



### **AIRFIOW**



## PERFORMANCE DATA

• Recommended Operating Pressure: Positive: 6" WC max Negative: 6" WC max

Maximum velocity: 5,000 FPM Operating Temp. Range:-100°F to +430°F

 Flame Speed Smoke Developed INSTALLATION: Air duct connections and joins shall be made per installation instructions outlined by Builder's Best.(Installation instructions are included inside each carton.)

### WARRANTY

Manufacturer assumes no responsibility for failure due to improper installation. All specifications and designs are subject to change without notice and without incurring liability.

WARRANTY EXCLUSION AND DISCLAIMER Seller specifically excludes, and hereby disclaims any express representation or express warranty of any kind with respect to the goods ordered hereunder. All implied warranties, including without limitation merchantability or fitness for a particular purpose or arising from a course of dealing or usage or trade shall expire and cease 45 days after date of delivery. Seller shall not be liable to buyer or any third party for any special, secondary, incidental, or consequential damages however arising. Nothing in this provision shall invalidate or restrict any right or remedy otherwise available under state or federal law. Materials and specifications subject to change without notice.

