

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U. S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (As Used on Label and List) HI-SPEED READY-STRIP	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
--	---

Section I

Manufacturer's Name Sunnyside Corporation	Manufacturers Code: 656	Emergency Telephone Number Chem Trec (800) 424-9300
Address (Number, Street, City, and ZIP Code) 225 Carpenter Avenue Wheeling, IL 60090		Telephone Number for Information (847) 541-5700
		Date Prepared 6/22/09
		Signature of Preparer (optional)

Section II-Hazardous Ingredients/Identity Information

Hazardous Components Common Name	CAS#	OSHA PEL	ACGIH TLV	%
Benzyl Alcohol	100-51-6	NE	NE	25-35 %
Dimethyl Glutarate	1119-40-0	NE	NE	6-10 %
Dimethy Adipate	627-93-0	NE	NE	2-6 %
Dimethyl Succinate	106-65-0	NE	NE	1-5%
Propylene Glycol	57-55-6	NE	NE	1-2%
Formic Acid	64-18-6	5 ppm	5 ppm	1-3 %
NE = Not Established				

Section III- Physical/Chemical Characteristics

Boiling Point	205° F	Specific Gravity (H₂O=1)	1.02
Vapor Pressure (mm Hg.) at 25° C	0.15 mm Hg.	Melting Point	Not applicable
Vapor Density (AIR =1)	> 1.0	Evaporation Rate (Butyl Acetate=1)	<1
Solubility in Water	Partial		
Appearance and Odor	Creamy Gel with mild odor		

Section IV- Fire and Explosion Hazard Data

Flash Point (Method Used)	Over 200°F	Flammable Limits	LEL 1.3% Vol	UEL 13% Vol
Extinguishing Media	Use water, foam or dry chemical to extinguish			
Special Fire Fighting Procedures	Wear self contained positive pressure breathing apparatus. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.			
Unusual Fire and Explosion Hazards	Vapor is explosive at air temperatures higher than the flash point.			
Health	1	Flammability	1	Reactivity 0

Section V-Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	
Incompatibility (<i>Materials to Avoid</i>) Strong oxidizers, acid and alkalis			
Hazardous Decomposition or Byproducts			
Hazardous Polymerization	May Occur		Conditions to Avoid Keep away from heat, sparks and open flame.
	Will Not Occur	X	

Section VI-Health Hazard Data

Route(s) of Entry:			
Inhalation : At very high concentrations inhalation causes headaches, dizziness, drowsiness, and nausea, and may lead to unconsciousness. Slightly irritating to the respiratory system (redness).			
Ingestion: Extreme levels can cause nausea, headache and vomiting, or higher levels may cause unconsciousness.			
Skin/Eye Contact: May cause eye or skin irritation (redness)			
Health Hazards (<i>Acute and Chronic</i>) Direct contact or exposure to mists and vapor may cause slight to moderate eye irritation. Prolonged or repeated exposure to product, vapors or mists may cause slight skin irritation. Ingestion may cause moderate to severe irritation of the respiratory tract.			
Carcinogenicity:	NTP? No	IARC monographs? No	OSHA Regulated? No
Signs and Symptoms of Exposure: Very low evaporation unlikely to reach exposure limits.			
Medical Conditions Generally Aggravated by Exposure None established			
Emergency and First Aid Procedures General: Protection of first-aider: Put on appropriate personal protective equipment. Move exposed person to fresh air. Remove contaminated clothing and shoes. Inhalation: If inhaled, remove to fresh air. Prevent cooling of the person. Keep victim at rest in half upright position. If not breathing, give artificial respiration. Obtain medical attention. Ingestion: If swallowed, rinse mouth with water (only if person is conscious). Seek medical attention. Skin Contact: Wash with soap and water. Remove contaminated clothing and shoes. Obtain medical attention if symptoms occur. Eye Contact: Rinse with plenty of running water. Obtain medical attention if symptoms occur.			

Section VII-Precautions for Safe Handling and Uses

Steps to Be Taken in Case Material is Released or Spilled	Soak up with suitable, non -reactive absorbant material, collect in suitable containers for disposal.
Waste Disposal Method	Dispose of in accordance with all local, state and federal regulations.
Precautions to Be Taken in Handling and Storing	Store at temperatures between 40 ⁰ F-95 ⁰ F

Section VIII-Control Measures

Respiratory Protection (<i>Specify Type</i>) Wear filter mask, filter type A (full face recommended) when spraying material..			
Ventilation	Local Exhaust	Use with adequate ventilation	Special N/A
	Mechanical (General)	Exhaust preferred and recommended	Other N/A
Protective Gloves	Neoprene gloves	Eye Protection	Safety glasses with side shield
Other Protective Clothing or Equipment. Filter mask, filter type A			

N/A = Not applicable.

Section IX-Additional Information

This product does not contain any chemicals that are reportable under Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

TRANSPORTATION: Not regulated.