



BRUSHING REDUCER V701

Features

- For use with all alkyd and oil-modified polyurethane coatings
- Effectively cleans tools and equipment
- May be used to reduce and thin coatings up to the legal limits allowed by district

General Description

Brushing Reducer is a blend of High Flash Naphtha and Mineral Spirits. Use this solvent to improve the brushing characteristics of single-component, solvent-based coatings.

Recommended For

For use with all alkyd and oil modified polyurethane coatings. For effective cleaning of tools and equipment. May be used to reduce and thin coatings up to the legal limits allowed by district

Limitations

- Do not use for thinning 2 component urethanes.
- For Industrial Use Only

Product Information

Product Information																																																			
<p>Colors — Standard: N/A</p> <p>— Tint Bases: N/A</p> <p>— Special Colors: N/A</p>	<table border="1"> <thead> <tr> <th>Technical Data^Δ</th> <th>Brushing Reducer</th> </tr> </thead> <tbody> <tr> <td>Vehicle Type</td> <td>N/A</td> </tr> <tr> <td>Pigment Type</td> <td>N/A</td> </tr> <tr> <td>Volume Solids</td> <td>N/A</td> </tr> <tr> <td>Coverage per Gallon at Recommended Film Thickness</td> <td>N/A</td> </tr> <tr> <td>Recommended Film Thickness</td> <td> <table border="0"> <tr> <td>– Wet</td> <td>N/A</td> </tr> <tr> <td>– Dry</td> <td>N/A</td> </tr> </table> </td> </tr> <tr> <td>Dry Time @ 77°F (25°C) @ 50% RH</td> <td> <table border="0"> <tr> <td>– Tack Free</td> <td>N/A</td> </tr> <tr> <td>– To Recoat</td> <td>N/A</td> </tr> </table> </td> </tr> <tr> <td>Dries By</td> <td>N/A</td> </tr> <tr> <td>Dry Heat Resistance</td> <td>N/A</td> </tr> <tr> <td>Viscosity</td> <td>N/A</td> </tr> <tr> <td>Flash Point</td> <td>104°F (TT-P-141, Method 4293)</td> </tr> <tr> <td>Gloss / Sheen</td> <td>N/A</td> </tr> <tr> <td>Surface Temperature at Application</td> <td> <table border="0"> <tr> <td>– Min.</td> <td>N/A</td> </tr> <tr> <td>– Max</td> <td>N/A</td> </tr> </table> </td> </tr> <tr> <td>Thin With</td> <td>N/A</td> </tr> <tr> <td>Clean Up Thinner</td> <td>N/A</td> </tr> <tr> <td>Weight Per Gallon</td> <td>3 kg (6.57 lbs.)</td> </tr> <tr> <td>Storage Temperature</td> <td> <table border="0"> <tr> <td>– Min.</td> <td>40°F (4.4°C)</td> </tr> <tr> <td>– Max</td> <td>95°F (35°C)</td> </tr> </table> </td> </tr> </tbody> </table>	Technical Data ^Δ	Brushing Reducer	Vehicle Type	N/A	Pigment Type	N/A	Volume Solids	N/A	Coverage per Gallon at Recommended Film Thickness	N/A	Recommended Film Thickness	<table border="0"> <tr> <td>– Wet</td> <td>N/A</td> </tr> <tr> <td>– Dry</td> <td>N/A</td> </tr> </table>	– Wet	N/A	– Dry	N/A	Dry Time @ 77°F (25°C) @ 50% RH	<table border="0"> <tr> <td>– Tack Free</td> <td>N/A</td> </tr> <tr> <td>– To Recoat</td> <td>N/A</td> </tr> </table>	– Tack Free	N/A	– To Recoat	N/A	Dries By	N/A	Dry Heat Resistance	N/A	Viscosity	N/A	Flash Point	104°F (TT-P-141, Method 4293)	Gloss / Sheen	N/A	Surface Temperature at Application	<table border="0"> <tr> <td>– Min.</td> <td>N/A</td> </tr> <tr> <td>– Max</td> <td>N/A</td> </tr> </table>	– Min.	N/A	– Max	N/A	Thin With	N/A	Clean Up Thinner	N/A	Weight Per Gallon	3 kg (6.57 lbs.)	Storage Temperature	<table border="0"> <tr> <td>– Min.</td> <td>40°F (4.4°C)</td> </tr> <tr> <td>– Max</td> <td>95°F (35°C)</td> </tr> </table>	– Min.	40°F (4.4°C)	– Max	95°F (35°C)
Technical Data ^Δ	Brushing Reducer																																																		
Vehicle Type	N/A																																																		
Pigment Type	N/A																																																		
Volume Solids	N/A																																																		
Coverage per Gallon at Recommended Film Thickness	N/A																																																		
Recommended Film Thickness	<table border="0"> <tr> <td>– Wet</td> <td>N/A</td> </tr> <tr> <td>– Dry</td> <td>N/A</td> </tr> </table>	– Wet	N/A	– Dry	N/A																																														
– Wet	N/A																																																		
– Dry	N/A																																																		
Dry Time @ 77°F (25°C) @ 50% RH	<table border="0"> <tr> <td>– Tack Free</td> <td>N/A</td> </tr> <tr> <td>– To Recoat</td> <td>N/A</td> </tr> </table>	– Tack Free	N/A	– To Recoat	N/A																																														
– Tack Free	N/A																																																		
– To Recoat	N/A																																																		
Dries By	N/A																																																		
Dry Heat Resistance	N/A																																																		
Viscosity	N/A																																																		
Flash Point	104°F (TT-P-141, Method 4293)																																																		
Gloss / Sheen	N/A																																																		
Surface Temperature at Application	<table border="0"> <tr> <td>– Min.</td> <td>N/A</td> </tr> <tr> <td>– Max</td> <td>N/A</td> </tr> </table>	– Min.	N/A	– Max	N/A																																														
– Min.	N/A																																																		
– Max	N/A																																																		
Thin With	N/A																																																		
Clean Up Thinner	N/A																																																		
Weight Per Gallon	3 kg (6.57 lbs.)																																																		
Storage Temperature	<table border="0"> <tr> <td>– Min.</td> <td>40°F (4.4°C)</td> </tr> <tr> <td>– Max</td> <td>95°F (35°C)</td> </tr> </table>	– Min.	40°F (4.4°C)	– Max	95°F (35°C)																																														
– Min.	40°F (4.4°C)																																																		
– Max	95°F (35°C)																																																		
<p>Certification:</p> <p>The product supported by this data sheet is regulated by consumer product VOC rules, in some areas, as a paint thinner, multi-purpose solvent.</p> <p>This product is exempt under the Ozone Transport Commission regulations.</p> <p>It also does not apply to LEED (Leadership in Energy and Environmental Design) standards.</p> <p>Suitable for Use in USDA Inspected Facilities</p>	<p>Volatile Organic Compounds (VOC)</p> <p>787 g/L 6.57 Lbs./Gallon</p>																																																		
<p>Technical Assistance:</p> <p>Available through your local authorized independent Benjamin Moore® retailer. For the location of the retailer nearest you, call 1-866-708-9180, or visit www.benjaminmoore.com</p>																																																			

Brushing Reducer V701

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application

Corotech® Brushing Reducer is a blend of Mineral Spirits and High Flash Naphtha. Use this solvent to improve the brushing characteristics of solvent based coatings.

Environmental Health & Safety Information

DANGER!

Causes skin irritation

Causes serious eye irritation

Suspected of causing cancer

May cause respiratory irritation. May cause drowsiness or dizziness

Causes damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Flammable liquid and vapor

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash face, hands and any exposed skin thoroughly after handling. Wear eye/face protection. Do not breathe dust/fume/mist/vapors/spray. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces, no smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep cool.

Response: If exposed or concerned, get medical attention. If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists get medical attention. If skin irritation occurs get medical attention. If on skin (or hair) take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. If inhaled remove victim to fresh air and keep at rest in a position comfortable for breathing. If swallowed immediately call a POISON CENTER or physician. Do NOT induce vomiting. In case of fire use CO₂, dry chemical, or foam for extinction.

Storage: Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Disposal: Dispose of contents /container to an approved waste disposal plant.

WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

**KEEP OUT OF REACH OF CHILDREN
FOR INDUSTRIAL USE ONLY**

**Refer to Safety Data Sheet for
additional health and safety information**