



SAFETY DATA SHEET

Revision Date: 16-Sep-2016

Revision Number: 3

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name UNIVERSAL METAL PRIMER RED
Product Code V131-20
Alternate Product Code V13120
Product Class SOLVENT THINNED PAINT
Color Red
Recommended use Primers
Restrictions on use No information available

Manufacturer
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
Phone: 800-225-5554
corotechcoatings.com

Emergency Telephone Number(s)
CHEMTREC (US): 800-424-9300
CHEMTREC (outside US): (703)-527-3887

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable liquids	Category 3

Label elements

Danger

Hazard statements

May cause an allergic skin reaction
May cause cancer
Causes damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways
Flammable liquid and vapor



Appearance liquid

Odor solvent

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves
Do not breathe dust/fume/mist/vapors/spray
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Keep away from heat/sparks/open flames/hot surfaces, no smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting/equipment
Use only non-sparking tools
Take precautionary measures against static discharge

Precautionary Statements - Response

If exposed or concerned get medical attention

Skin

If skin irritation or rash occurs get medical attention
Wash contaminated clothing before reuse
If on skin (or hair) take off immediately all contaminated clothing. Rinse skin with water

Ingestion

If swallowed immediately call a POISON CENTER or physician
Do NOT induce vomiting

Fire

In case of fire use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded

Other information

No information available

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical Name	CAS-No	Weight % (max)
Limestone	1317-65-3	30
Talc	14807-96-6	25
Xylene	1330-20-7	10
Iron oxide	1309-37-1	10
Stoddard solvent	8052-41-3	5
Zinc phosphate	7779-90-0	5
Ethyl benzene	100-41-4	5
Silica, crystalline	14808-60-7	1
Methyl ethyl ketoxime	96-29-7	0.5

4. FIRST AID MEASURES

First aid measures

General Advice	If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Wash clothing before reuse. Destroy contaminated articles such as shoes.
Inhalation	Move to fresh air. If symptoms persist, call a physician. If not breathing, give artificial respiration. Call a physician immediately.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Consult a physician.
Protection Of First-Aiders	Use personal protective equipment.
Most Important Symptoms/Effects	May cause allergic skin reaction.
Notes To Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause flash fire.
Suitable Extinguishing Media	Foam, dry powder or water. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective Equipment And Precautions For Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Hazardous Combustion Products	Burning may result in carbon dioxide, carbon monoxide

and other combustion products of varying composition which may be toxic and/or irritating.

Specific Hazards Arising From The Chemical

Flammable. Flash back possible over considerable distance. Keep product and empty container away from heat and sources of ignition. Closed containers may rupture if exposed to fire or extreme heat. Thermal decomposition can lead to release of irritating gases and vapors.

Sensitivity To Mechanical Impact

No

Sensitivity To Static Discharge

Yes

Flash Point Data

Flash Point (°F)

80

Flash Point (°C)

27

Flash Point Method

PMCC

Flammability Limits In Air

Lower Explosion Limit

Not available

Upper Explosion Limit

Not available

NFPA **Health:** 1 **Flammability:** 3 **Instability:** 0 **Special:** Not Applicable

NFPA Legend

0 - Not Hazardous

1 - Slightly

2 - Moderate

3 - High

4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Remove all sources of ignition. Take precautions to prevent flashback. Ground and bond all containers and handling equipment. Take precautionary measures against static discharges. Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Use personal protective equipment.

Other Information

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

Environmental Precautions

See Section 12 for additional Ecological Information.

Methods For Clean-Up

Dam up. Soak up with inert absorbent material. Use a non-sparking or explosion proof means to transfer material to a sealed, appropriate container for disposal. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Handling

Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Do not breathe vapors or spray mist. Use only in ventilated areas. Prevent vapor build-up by providing adequate ventilation during and after use.

Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Ignition and/or flash back may occur.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children.

DANGER - Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container.

Incompatible Materials

Incompatible with strong acids and bases and strong oxidizing agents.

Technical measures/Precautions Ensure adequate ventilation. Use only where airflow will keep vapors from building up in or near the work area in adjoining rooms. Comply with all national, state, and local codes pertaining to the storage, handling, dispensing and disposal of flammable liquids.

Dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. All equipment should be non-sparking and explosion proof. Use explosion proof electrical equipment for ventilation, lighting and material handling.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

Chemical Name	ACGIH	OSHA
Limestone	N/E	15 mg/m ³ - TWA 5 mg/m ³ - TWA
Talc	2 mg/m ³ - TWA	20 mppcf - TWA
Xylene	100 ppm - TWA 150 ppm - STEL	100 ppm - TWA 435 mg/m ³ - TWA
Iron oxide	5 mg/m ³ - TWA	10 mg/m ³ - TWA 15 mg/m ³ - TWA Rouge 5 mg/m ³ - TWA Rouge
Stoddard solvent	100 ppm - TWA	500 ppm - TWA 2900 mg/m ³ - TWA
Ethyl benzene	20 ppm - TWA	100 ppm - TWA 435 mg/m ³ - TWA
Silica, crystalline	0.025 mg/m ³ - TWA	-

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits

OSHA - Occupational Safety & Health Administration Exposure Limits

N/E - Not Established

Appropriate engineering controls**Engineering Measures** Ensure adequate ventilation, especially in confined areas.**Personal Protective Equipment****Eye/Face Protection**

Safety glasses with side-shields. If splashes are likely to occur, wear: Tightly fitting safety goggles.

Skin Protection

Long sleeved clothing. Protective gloves.

Respiratory Protection

Use only with adequate ventilation. In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	liquid
Odor	solvent
Odor Threshold	No information available
Density (lbs/gal)	13.8 - 13.9
Specific Gravity	1.65 - 1.67
pH	No information available
Viscosity (cps)	No information available
Solubility	No information available
Water Solubility	No information available
Evaporation Rate	No information available
Vapor Pressure	No information available
Vapor Density	No information available
Wt. % Solids	75 - 85
Vol. % Solids	55 - 65
Wt. % Volatiles	15 - 25
Vol. % Volatiles	35 - 45
VOC Regulatory Limit (g/L)	< 340
Boiling Point (°F)	213
Boiling Point (°C)	101
Freezing Point (°F)	No information available
Freezing Point (°C)	No information available
Flash Point (°F)	80
Flash Point (°C)	27
Flash Point Method	PMCC
Flammability (solid, gas)	Not applicable
Upper Explosion Limit	No information available
Lower Explosion Limit	No information available
Autoignition Temperature (°F)	No information available
Autoignition Temperature (°C)	No information available
Decomposition Temperature (°F)	No information available
Decomposition Temperature (°C)	No information available
Partition Coefficient (n-octanol/water)	No information available

10. STABILITY AND REACTIVITY

Reactivity	No data available
Chemical Stability	Stable under normal conditions. Hazardous polymerisation does not occur.
Conditions To Avoid	Keep away from open flames, hot surfaces, static electricity and sources of ignition. Sparks. Elevated temperature.
Incompatible Materials	Incompatible with strong acids and bases and strong oxidizing agents.
Hazardous Decomposition Products	Thermal decomposition can lead to release of irritating gases and vapors.
Possibility Of Hazardous Reactions	None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information Repeated or prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Information on toxicological effects

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact	Contact with eyes may cause irritation.
Skin contact	May cause skin irritation and/or dermatitis. Prolonged skin contact may defat the skin and produce dermatitis.
Ingestion	Harmful if swallowed. Ingestion may cause irritation to mucous membranes. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.
Inhalation	Harmful by inhalation. High vapor / aerosol concentrations are irritating to the eyes, nose, throat and lungs and may cause headaches, dizziness, drowsiness, unconsciousness, and other central nervous system effects.
Sensitization:	May cause an allergic skin reaction
Neurological Effects	No information available.
Mutagenic Effects	No information available.
Reproductive Effects	No information available.
Developmental Effects	No information available.

Target Organ Effects	No information available.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure if inhaled. Contains: Crystalline Silica which has been determined to be carcinogenic to humans by IARC when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint. Causes damage to organs through prolonged or repeated exposure.
STOT - single exposure	May cause disorder and damage to the. Respiratory system.
Other adverse effects	No information available.
Aspiration Hazard	May be harmful if swallowed and enters airways. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	19011 mg/kg
ATEmix (dermal)	10819 mg/kg
ATEmix (inhalation-dust/mist)	15.1 mg/L

Acute Toxicity**Component**Xylene

LD50 Oral: 4300 mg/kg (Rat)

LD50 Dermal: > 1700 mg/kg (Rabbit)

LC50 Inhalation (Vapor): 5000 ppm (Rat, 4 hr.)

Iron oxide

LD50 Oral: > 5000 mg/kg (Rat) vendor data

Stoddard solvent

LD50 Oral: > 5,000 mg/kg (Rat)

LD50 Dermal: > 3160 mg/kg (Rabbit)

LC50 Inhalation (Vapor): > 6.1 mg/L (Rat)

Ethyl benzene

LD50 Oral: mg/kg (Rat)

LD50 Dermal: > mg/kg (Rabbit)

LC50 Inhalation (Vapor): mg/m³ (Rat, 2 hr.)Silica, crystalline

LD50 Oral: 500 mg/kg (Rat)

Methyl ethyl ketoxime

LD50 Oral: 930 mg/kg (Rat)

LD50 Dermal: 200 µL/kg (Rabbit)

LC50 Inhalation (Vapor): > 4.8 mg/L (Rat)

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:

Chemical Name	IARC	NTP	OSHA Carcinogen
Ethyl benzene	2B - Possible Human Carcinogen		Listed
Silica, crystalline	1 - Human Carcinogen	Known Human Carcinogen	Listed

• Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.

Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION**Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

Product Information**Acute Toxicity to Fish**

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation / Accumulation

No information available.

Mobility in Environmental Media

No information available.

Ozone

Not Applicable

Component**Acute Toxicity to Fish**Xylene

LC50: 13.5 mg/L (Rainbow Trout - 96 hr.)

Ethyl benzene

LC50: 12.1 mg/L (Fathead Minnow - 96 hr.)

Methyl ethyl ketoxime

LC50: 48 mg/L (Bluegill sunfish - 96 hr.)

Acute Toxicity to Aquatic InvertebratesEthyl benzene

EC50: 1.8 mg/L (Daphnia magna - 48 hr.)

Methyl ethyl ketoxime

EC50: 750 mg/L (Daphnia magna - 48 hr.)

Acute Toxicity to Aquatic Plants

Ethyl benzene

EC50: 4.6 mg/L (Green algae (Scenedesmus subspicatus), 72 hrs.)

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method	Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.
Empty Container Warning	Emptied containers may retain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition.

14. TRANSPORT INFORMATION**DOT**

Proper Shipping Name	Paint
Hazard Class	3
UN-No	UN1263
Packing Group	III
Reportable Quantity (RQ)	Ethylbenzene: RQ kg= 454.00, Xylenes mixed isomers: RQ kg= 45.40
Description	UN1263, Paint, 3, III, RQ

ICAO / IATA Contact the preparer for further information.

IMDG / IMO Contact the preparer for further information.

15. REGULATORY INFORMATION**International Inventories**

TSCA: United States Yes - All components are listed or exempt.
DSL: Canada Yes - All components are listed or exempt.

Federal Regulations**SARA 311/312 hazardous categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

<u>Chemical Name</u>	<u>CAS-No</u>	<u>Weight % (max)</u>	<u>CERCLA/SARA 313 (de minimis concentration)</u>
Xylene	1330-20-7	10	1.0

Zinc phosphate	7779-90-0	5	1.0
Ethyl benzene	100-41-4	5	0.1

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

<u>Chemical Name</u>	<u>CAS-No</u>	<u>Weight % (max)</u>	<u>Hazardous Air Pollutant (HAP)</u>
Xylene	1330-20-7	10	Listed
Ethyl benzene	100-41-4	5	Listed

State Regulations**California Proposition 65**

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

State Right-to-Know

Chemical Name	Massachusetts	New Jersey	Pennsylvania
Limestone	X	X	X
Talc	X	X	X
Xylene	X	X	X
Iron oxide	X	X	X
Stoddard solvent	X	X	X
Zinc phosphate		X	X
Ethyl benzene	X	X	X
Silica, crystalline	X	X	X

Legend

X - Listed

16. OTHER INFORMATION

HMIS - Health: 1* Flammability: 3 Reactivity: 0 PPE: -

HMIS Legend

- 0 - Minimal Hazard
- 1 - Slight Hazard
- 2 - Moderate Hazard
- 3 - Serious Hazard
- 4 - Severe Hazard
- * - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself

and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By Product Stewardship Department
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
855-724-6802

Revision Date: 16-Sep-2016
Revision Summary Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET