



**CENTURY
INDUSTRIES**

A Division of Century Container, LLC

PERFORMANCE COATINGS

PRODUCT CATALOG Vol. 21

- DRIVEWAY COATINGS & REPAIR
- ROOF CEMENTS & ADHESIVES
- ROOF & FOUNDATION COATINGS
- REFLECTIVE COATINGS
- CONCRETE REPAIR





Pro-Q[®] 8-Year Ultra Premium Driveway Filler & Sealer

A polymer modified asphalt emulsion based driveway resurfacer designed to beautify, protect and renew asphalt pavement surfaces. Fortified with sand for added strength, filling, slip resistance and durability.

USES:

- Asphalt Driveways & Parking Areas

FEATURES:

- 8-Year Protection
- 8x Polymer Modification
- High Solids Formula for Good Filling & Long Term Protection
- Fast & Easy to Apply
- Dries Black

DRIVEWAY COATING & REPAIR PRODUCTS

Size:	Item #	Pack	Weight
4.75 Gal. Pail	10-492-05	1	57.5 lbs.



Pro-Q[®] 5-Year Premium Drive Filler & Sealer

A polymer modified asphalt emulsion based driveway filler and sealer designed to beautify and protect asphalt pavement surfaces. Fortified with sand for added filling, slip resistance and durability.

USES:

- Asphalt Driveways & Parking Areas

FEATURES:

- 5-Year Protection
- 5x Polymer Modification
- Fast & Easy to Apply
- Dries Black

COVERAGE:

One 4.75 gallon pail will cover approximately 250-350 square feet per coat. Two coats are recommended for maximum durability and warranty purposes. Coverage will ultimately be dependent upon pavement porosity. Extremely porous pavement may significantly reduce product coverage.

Size:	Item #	Pack	Weight
4.75 Gal. Pail	10-270-05	1	57.5 lbs.

Pro-Q[®] 3-Year Asphalt Emulsion Drive Filler & Sealer

A polymer modified asphalt emulsion based driveway filler and sealer designed to beautify and protect asphalt pavement surfaces. Fortified with sand for added filling, slip resistance and durability.

USES:

- Asphalt Driveways & Parking Areas

FEATURES:

- 3-Year Protection
- 3x Polymer Modification
- Fortified with Sand for Slip Resistance
- Dries Black

Size:	Item #	Pack	Weight
4.75 Gal. Pail	10-260-05	1	55.4 lbs.

Century Black Beauty Driveway Sealer

A polymer modified asphalt emulsion based driveway sealer designed to protect asphalt pavement surfaces. Fortified with sand for slip resistance and durability.

USES:

- Asphalt Driveways & Parking Areas

FEATURES:

- Fortified with Sand for Slip Resistance
- Dries Black

Size:	Item #	Pack	Weight
4.75 Gal. Pail	10-250-05	1	55.4 lbs.

DRIVEWAY COATING & REPAIR PRODUCTS



Rubberize™ Heavy Duty Crack Filler

A polymer modified elastomeric asphalt emulsion crack sealant designed for sealing cracks up to 3/4" wide in asphalt pavement surfaces.

USES:

- Filling Cracks in Asphalt Pavement

FEATURES:

- Elastomeric Formula for Outstanding Flexibility & Adhesion
- Fills & Seals Cracks in Asphalt Driveways
- Seals Out Moisture
- High Solids Formula for Lasting Repair
- Dries Black

COVERAGE:

One 0.9 gallon jug will fill approximately 150 linear feet of cracks 1/2" wide by 1/4" deep.

Size:	Item #	Pack	Weight
0.9 Gal. Jug	10-440-01	6	62.3 lbs.



Century Latex Plus Driveway Patch

Heavy-bodied sand-filled trowel grade asphalt emulsion crack filler designed for filling cracks up to 1" wide in asphalt pavement surfaces. Can also be used to fill shallow ruts and depressions in pavement surfaces.

USES:

- Filling Cracks & Ruts in Asphalt Pavement

FEATURES:

- Levels Low Spots & Depressions in Asphalt Driveways
- Seals Out Moisture
- Easy to Apply
- Dries Black

COVERAGE:

Ultimate coverage will be dependent upon depth and width of crack.

Size:	Item #	Pack	Weight
0.9 Gal. Pail	10-245-01	6	77.82 lbs.



CONCRETE REPAIR PRODUCTS



Ultra Seal™ Concrete Crack Filler

A 100% acrylic elastomeric sealant designed for filling cracks up to 1/2" wide in concrete pavement surfaces.

USES:

- Filling Cracks in Concrete Surfaces

FEATURES:

- Seals Out Moisture
- Fills Cracks Up To 1/2" Wide
- High Solids Formulation for Lasting Repair

COVERAGE:

Coverage is dependent upon depth and width of cracks. Typically, one quart of Concrete Crack Filler will fill approximately 20-35 feet of cracks.

Size:	Item #	Pack	Weight
0.9 Qt. Bottle	10-785-32	12	39 lbs.



Pro-Q® All Weather Roof Cement

Professional grade all-weather roof patch and flashing cement that is rubberized for added strength and flexibility. Cures to a tough and resilient protective barrier. Its non-sag properties and exceptional adhesion makes this an ideal cement for the construction and repair of all flashings, metal joints, seams, coping, vent pipes, skylights and chimneys.

USES:

- Repair holes, cracks, splits & seams
- Seal around chimneys, flashings, metal joints, skylights, copings & more
- Repair asphalt & fiberglass shingle leaks

FEATURES:

- Rubberized for lasting performance
- All-weather formula
- Will not run or sag
- Added flexibility & elasticity
- Superior flashing, patching & leak repair

COVERAGE:

Approximately 12 square feet per gallon.

ROOF CEMENTS & ADHESIVES

Size:	Item #	Pack	Weight
4.75 Gal. Pail	10-180-05	1	50 lbs.
0.9 Gal. Pail	10-180-01	6	56 lbs.



Century Wet or Dry Plastic Roof Cement

This multi-purpose patch material features a special blend of refined asphalts and adhesion promoters designed to bond rapidly to moist, damp, wet or dry surfaces. It provides water repellency when conventional cements just won't stick.

USES:

- Splits & Seams
- Vents & Skylights
- Chimneys & Copings
- Flashings
- Metal Joints

FEATURES:

- Stops roof leaks instantly
- Long-lasting protection
- Fiber reinforced
- Easy-to-use trowel grade formula
- Commercial & residential use

COVERAGE:

Approximately 12 square feet per gallon. One 10 ounce tube will fill approximately 30 linear feet at 1/4" thick.

Size:	Item #	Pack	Weight
4.75 Gal. Pail	10-190-05	1	50 lbs.
0.9 Gal. Pail	10-190-01	6	56 lbs.
10 Oz. Tube	10-780-10	12	11 lbs.



Century Cold Process Blind Nail & Lap Adhesive

A special blend of adhesive asphalts, fibers, special resins and other ingredients that assure its rapid fusion to the base surface. Intended primarily as a blind nailing cement for use with roll roofing. It creates a tight bond and prevents buckling and curling of edges. Roof adhesive is also suitable for application to older roofs to seal cracks and pinholes. Dries black.

USES:

- Adhesive for rolled roofing

FEATURES:

- A waterproof adhesive for use in the application of roll roofing
- Bonds layers of roll roofing
- Provides a moisture barrier

COVERAGE:

Approximately 50 square feet per gallon, 150-175 linear feet per 4 inch lap.

Size:	Item #	Pack	Weight
4.75 Gal. Pail	10-165-05	1	44 lbs.
0.9 Gal. Pail	10-165-01	6	54 lbs.





ROOF & FOUNDATION COATINGS



Century Fibered Roof & Foundation Coating

A mixture of liquid asphalt and fibers which forms a tough, adhesive bond with most roof surfaces. Highly resistant to water and other types of weather damage. Seals small cracks, joints, seams and nail holes. Dries black.

USES:

- Metal Roofs
- Roof Felts
- Concrete Foundations
- Built Up Roofs
- Concrete Roofs
- Wood Roofs and More

FEATURES:

- Protects Built-Up Composition, Metal, Gravel & Concrete Roofs & Foundations
- Use for Coating Entire Surface Area, Above or Below Grade

COVERAGE:

Metal Roof: 60-70 square feet per gallon. Felt or Composition: 50-60 square feet per gallon. Concrete: 25-50 square feet per gallon. Old, Oxidized Roofing: 25-50 square feet per gallon.

Size:	Item #	Pack	Weight
4.75 Gal. Pail	10-100-05	1	44 lbs.
0.9 Gal. Pail	10-100-01	6	52 lbs.



Century All Purpose Non-Fibered Roof & Foundation Coating

A sealer-preservative for all types of surfaces, this product is an excellent saturant for composition roofing which has become excessively dry. It rustproofs metal, preserves wood, waterproofs stone or brick and rejuvenates composition surfaces. Also used to coat concrete foundations, above or below grade as well as fences and barns. Dries black.

USES:

- Concrete Foundations
- Wood Fences & Barns
- Most Roof Surfaces

FEATURES:

- Penetrates, Preserves, & Protects Roofs, Foundations, Wood Fences, Barns, & More
- Coats Entire Surface Area, Above or Below Grade

COVERAGE:

Metal Surfaces: 90-100 square feet per gallon. Concrete: 75-100 square feet per gallon. Wood or Composition: 65-90 square feet per gallon. Old, Oxidized Roofing: 50-80 square feet per gallon.

Size:	Item #	Pack	Weight
4.75 Gal. Pail	10-107-05	1	42 lbs.
0.9 Gal. Pail	10-107-01	6	57 lbs.



Pro-Q® Latex Plus Roof & Foundation Sealer

An elastomeric polymer modified asphalt emulsion designed for coating most roof surfaces and concrete foundations. Protects concrete foundations and most roof surfaces from moisture and water intrusion. Dries black.

USES:

- Most Roof Surfaces
- Waterproofing
- Exterior Basement Walls
- Poured Concrete Walls
- Polystyrene/Styrofoam Insulation Board
- Wood, Foam & More

FEATURES:

- Seals Out Water & Moisture
- Easy to Apply
- Advanced Elastomeric Formula Bridges Hairline Cracks in Concrete
- Soap & Water Cleanup
- Zero VOC Water-Based Formula

COVERAGE:

Approximately 150 square feet per 4.75 gallon pail at 60 MIL thickness. Approximately 31 square feet per 0.9 gallon pail at 60 MIL thickness.

Size:	Item #	Pack	Weight
4.75 Gal. Pail	10-120-05	1	42 lbs.
0.9 Gal. Pail	10-120-01	6	52 lbs.

REFLECTIVE COATING



UltraSeal™ MaxAlum Fibered Aluminum Roof Coating

This premium energy saving formula stays brighter longer. It will seal, protect, and reflect solar heat using a proven blend of selected waterproofing pigments. Forms an excellent adhesive bond with most substrates. Areas immediately under roof will remain approximately 15-20 degrees cooler in summer. In winter, heat is reflected back into the building, saving energy costs. Dries bright silver.

USES:

- Metal & Concrete Roofs
- Weathered Asphalt
- Metal Buildings/Grain Bins
- Built-Up Roofs & Mobile Homes
- Modified Bitumen, SBS & APP

FEATURES:

- Bright Aluminum Color
- Saves Energy Costs
- Superior Reflectivity
- Our Best Aluminum Roof Coating

COVERAGE:

Metal Surface: 70-100 square feet per gallon. Composition Surface: 40-60 square feet per gallon.

Size:	Item #	Pack	Weight
4.75 Gal. Pail	10-230-05	1	49 lbs.

Pro-Q® 5-Year Premium Fibered Aluminum Roof Coating

A blend of pure waterproofing asphalt and high grade aluminum pigments plus the addition of fibers. Reflects up to 80% of the sun's rays, helping prevent excessive drying and cracking of substrate, thus reducing leaks. Areas immediately under roof will remain approximately 15-20 degrees cooler in summer. In winter, inside heat is reflected back into the building, thus saving energy costs. Dries silver.

USES:

- Metal Roofs
- Weathered Asphalt
- Mobile Homes
- Built-Up Roofs

FEATURES:

- 5-Year Protection
- Bright Aluminum Color
- Saves Energy Costs

Size:	Item #	Pack	Weight
4.75 Gal. Pail	10-215-05	1	49 lbs.
0.9 Gal. Pail	10-215-01	6	58 lbs.

Century 3-Year Aluminum Roof & Mobile Home Coating

A blend of select asphalts, aluminum pigments and fibers designed to reflect the sun's rays. Temperature directly under roof surface stays cooler in the summer and warmer in the winter. Dries silver.

USES:

- Mobile Homes/RV's
- Commercial & Residential Buildings

FEATURES:

- 3-Year Protection
- Aluminum Color
- Reflects Sunlight & Saves Energy Costs

Size:	Item #	Pack	Weight
4.75 Gal. Pail	10-200-05	1	45 lbs.
0.9 Gal. Pail	10-200-01	6	54 lbs.

& REPAIR PRODUCTS



Pro-Q® Non-Fibered Aluminum Roof Sealer

A blend of pure waterproofing asphaltum and high grade aluminum pigments. This material will reflect up to 80% of the sun's rays, helping prevent excessive drying and cracking of substrate, thus reducing leaks. Areas immediately under roof will remain approximately 15-20 degrees cooler in summer. In winter, inside heat is reflected back into the building, thus saving energy costs. Dries silver.

USES:

- Metal Roofs
- Weathered Asphalt
- Mobile Homes
- Built-Up Roofs

FEATURES:

- Bright Aluminum Color
- Reflects Sunlight
- Lowers Energy Costs

COVERAGE: Metal Surface: 70-100 square feet per gallon. Composition Surface: 50-75 square feet per gallon

Size:	Item #	Pack	Weight
4.75 Gal. Pail	10-210-05	1	47 lbs.



Pro-Q® 7-Year White Elastomeric Roof Coating

An acrylic elastomeric roof coating designed to form a rubber-like membrane over a variety of roof surfaces. Reflects the sun's rays resulting in energy cost savings. Designed for use on metal, polyurethane foam, masonry, asphalt and wood surfaces. Dries white.

USES:

- Aged Asphalt & Aluminum Coatings
- Polyurethane Foam
- Mobile Homes, Campers/RV's
- Metal, Concrete, Wood & More

FEATURES:

- 7-Year Protection
- Dries White
- Saves Energy Costs
- Acrylic Elastomeric Polymers for Lasting Durability

COVERAGE: One 4.75 gallon pail will cover approximately 250-350 square feet. One 0.9 gallon container will cover approximately 50-70 square feet.

Size:	Item #	Pack	Weight
4.75 Gal. Pail	10-540-05	1	55 lbs.
0.9 Gal. Pail	10-540-01	6	69 lbs.



Pro-Q® White Elastomeric Roof Patch

An acrylic emulsion patch material designed for repairing cracks, seams and edges around skylights, vents, and metal joints. Dries white.

USES:

- Cracks
- Seams
- Skylights
- Vents
- Metal Joints

FEATURES:

- Dries White
- Excellent Adhesion & Flexibility
- Acrylic Formula for Lasting Performance

COVERAGE: One 0.9 gallon pail will cover approximately 12 square feet at 1/8" thick or 35 linear feet of 4" wide repair at 1/8" thick.

Size:	Item #	Pack	Weight
0.9 Gal. Pail	10-545-01	6	71 lbs.



PERFORMANCE COATINGS

Century Industries
5331 State Route 7 New Waterford, OH 44445
800-955-8443 www.centuryindustriescorporation.com