



COREtec Plus Enhanced XL

Product Specifications

- Style Number
- Construction
- Edge Profile
- Nominal Dimensions
- Actual Product Width
- Actual Product Length
- Wear Layer Thickness
- Overall Product Thickness
- Core Thickness
- Attached Underlayment
- Attached Underlayment Thickness
- Finish
- Installation Methods
- Profile
- Country of Origin
- Packaging



905 Twilight Oak

40 boxes

Colors

 905 Twilight Oak Color Variation: Substantial	 908 Fairweather Oak Color Variation: Slight	 912 Hayes Oak Color Variation: Slight	 913 Appalachian Pin Color Variation: Substantial	 914 Williamson Oak Color Variation: Moderate
 915 Waddington Oak Color Variation: Slight	 916 Venado Oak Color Variation: Moderate	 921 Tolima Pine Color Variation: Moderate	 922 Arvon Oak Color Variation: Moderate	

COREtec, manufactured by USFloors | 3580 Corporate Dr. | Dalton, GA 30721 | www.COREtecFloors.com

For reference purposes only if printed or downloaded.



COREtec Plus Enhanced XL

Performance

Static Load (ASTM F970)	Passes
Residual Indentation (ASTM F1914)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Smoke Density (ASTM E662)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Slip Resistance (ASTM D2047)	ADA compliant






Warranties

USF Lifetime
[Residential Resilient Limited Warranty - Defects, Wear, Waterproof, Petproof](#)
USF 10 Year Medium Commercial

Certifications

GreenGuard (Certification, Gold, Private Label) Certified

Coordinating Trim

					
Baby Threshold*	T-Molding*	Quarter Round	Overlap Stairnose*	Flush Stairnose	Overlap Reducer
01V09 94"	02V37 94"	01V35 94"	01V83 94"	FS7HU 94"	01V59 94"
	02V40 94"			02V10 94"	
	02V44 94"				
	02V45 94"				
	02V46 94"				
	02V47 94"				
	02V48 94"				
	02V50 94"				

*Packaged with molding track

Stair Tread


Stair Tread
03Z70 48"

