



PRODUCT DATA SHEET

Zinc-It® Instant Cold Galvanize, 13 Wt Oz
 No. 05048 | Item# 1003659 | Case# 1003658



Product Description	High Performance coating of >93% pure zinc that actively fights rust and corrosion. Provides protection of hot dip galvanize with on the job convenience.
Applications	Threads, exposed edges, fasteners, conduit, strapping, welds, fencing, railings, grates, electrical poles, breaker panel housings, rain spouts, signs, doors, trailers, waste containers, catwalks, and guard rails.
Unit Package Description	16 Ounce Aerosol
Brand	CRC
Generic Description 1	Instant Cold Galvanized Coating
Net Fill	13 Wt Oz
UPC Code	078254050485
Unit Dimensions	7.75H x 2.63W x 2.63D in
Units Per Case	12
Case Dimensions	8.25H x 8.38W x 11D in
Cases Per Pallet	75
Case Weight	15 lbs
I 2 of 5 Code	30078254050486
Appearance	Gray Viscous Liquid
Flash point (F)	-2°F
Flash point (C)	-19°C
Flammability Class - CPSC	Extremely Flammable
Spec Gravity Concentrate	0.77 to 0.85
Plastic Safe	Yes
Evaporation Rate	>1 (butyl acetate=1)
Dry Time - Fully Dry	8 Hours
Dry Time - Tack Free	20 Minutes
Recoat	Before 1 Hour or After 48 Hours
Coverage	28 to 32 Sq Ft at 3 Mil Dry
Working Temp (F)	130°F (Continuous) / 150°F (Intermittent)

Last revised: 3/27/2018
 Page 1 of 2



Customer Care: 800-556-5074
 Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



PRODUCT DATA SHEET



Working Temp (C)	54.4°C (Continuous) / 65.6°C (Intermittent)
Propellant	Hydrocarbon
Aerosol Flammability Level	III
Military Specification Number	Meets requirements of Mil-P-26915, Meets requirements of Mil-P-46105
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity (Marine Pollutant)
VOC % (Consumer Product def)	45.6
VOC g/L (Consumer Product def)	555.6
VOC lbs/gal (Consumer Prod def)	4.64
VOC Category	Aerosol Coating: Metallic
MIR Limit (EPA)	1.9
MIR Limit (CA)	1.25
MIR Value	1.2
Removal (How To)	Remove with aromatic solvents, Xylene. Toluene can be used, but is not recommended.

Last revised: 3/27/2018
Page 2 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.