



Technician Grade Dielectric Grease, 3.3 Wt Oz

No. 05113 | Item# 1003734 | Case# 1003733

Product Description

Best New Packaging in the performance category at the 2015 AAPEX/SEMA Show! Simply turn the dial on the Select-A-Bead™ actuator to select the best bead width for your project. A unique, non-curing compound used for sealing, protecting & electrical insulating. Improves electrical performance by reducing arcing & voltage drop. Also ideal for lubricating plastic & rubber. Improves electrical performance in adverse weather conditions. Patented finger-actuated delivery system for smooth, continuous coverage.

Applications

Electrical connections, circuit breakers, contacts, spark plug boots, trailer connectors, HEI distributor, battery terminals, contacts, lubrication of plastic, rubber parts & o-rings

Unit Package Description

6 Ounce Pressurized Can

Brand

CRC

Generic Description 1

Dielectric Grease

Net Fill

3.3 Wt Oz

UPC Code

078254051130

Unit Dimensions

8.75H x 2W x 2D in

Units Per Case

12

Case Dimensions

9.4H x 8W x 7.9D in

Cases Per Pallet

120

Case Weight

6 lbs

I 2 of 5 Code

30078254051131

Appearance

Opaque White Gel

Base Type

Silicone

Flash point (F)

>572°F

Flash point (C)

>300°C

Flammability Class - CPSC

None

Spec Gravity Concentrate

0.97

NLGI Grade

2



Last revised: 4/23/2019

Page 1 of 2



Chemical Solutions to Keep You Moving™

f t y i n • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



Timken OK Load Lbs.	Not Determined
Plastic Safe	Safe on Most Plastics (Test small area)
Dielectric Strength	>450 Volts/Mil
Working Temp (F)	-70 to 400°F
Working Temp (C)	-56.7 to 204.4°C
Drop Point	None
Leakage	Not Determined
Low Temp Torque	Not Determined
Oil Separation	<1%
Oxidation Stability	Not Determined
Water Washout	Not Determined
Worked Penetration	Varies with grade
Propellant	Nitrogen
Aerosol Flammability Level	I
DOT Proper Shipping Name	Aerosols, Non-Flammable, Limited Quantity
VOC % (Consumer Product def)	<1
VOC g/L (Consumer Product def)	<0.01
VOC lbs/gal (Consumer Prod def)	<0.1
VOC Category	Not Regulated
Removal (How To)	Remove with petroleum distillates and chlorinated solvents.

Last revised: 4/23/2019
Page 2 of 2



Chemical Solutions to Keep You Moving™
f t y o i n • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.