

simpleprep™ PRE-MIXED FLOOR PATCH

- **Repairs holes and cracks**
- **Fills minor dips and imperfections**
- **Ready to use — no mixing**
- **Use over concrete, plywood and vinyl**

PRICE



PRODUCT DESCRIPTION

Repairs holes and cracks in concrete and plywood floors prior to installing tile or other flooring. Smooths and fills minor dips and imperfections.

AREAS OF USE

- For interior use only
- Concrete
- Cement backerboards
- Ceramic tile
- Exterior grade plywood
- Vinyl flooring

LIMITATIONS

- Do not use as a wear surface.

SURFACE PREPARATION

General Surface Preparation:

All surfaces must be structurally sound, clean, dry and free from contaminants that would prevent a good bond. Concrete must be fully cured and not subject to hydrostatic pressure. Concrete surfaces should accept water penetration. Plywood floors should be built to industry standards. Smooth concrete, existing glazed tile, cement terrazzo or polished stone must be roughened or scarified. Sheet vinyl must be well bonded and stripped of old finish. Surfaces and materials should be maintained at a temperature above 50° F (10° C) or below 100° F (38° C) for 72 hours.

Plywood Substrates:

Plywood flooring, including those under resilient flooring must be structurally sound and meet all ANSI and deflection requirements (no flex or movement). For questions about proper subfloor installation, call Technical Services.

APPLICATION

Stir contents thoroughly. Lightly dampen the area to be patched with clean water. Use smooth edge of trowel or putty knife to apply compound. May be smoothed or featheredged. Fills greater than 1/4" (6 mm) deep require two or more applications. Remove excess with a cloth.

DRYING TIME

Wait 4 hours before tiling; longer for deeper fills.

CLEAN-UP

Quickly clean tools with warm soapy water.

CAUTION

Avoid eye contact. If eye contact occurs, flush with water for 15 minutes. Consult a physician immediately.
KEEP OUT OF REACH OF CHILDREN.
DO NOT TAKE INTERNALLY. KEEP FROM FREEZING.
CLOSE CONTAINER AFTER EACH USE.

ORDERING INFORMATION

	ITEM CODE	SIZE	COLOR	PACKAGE
USA	FPQT	1 quart (.946 L)	Gray	Pail
USA	FP1	1 gallon (3.78 L)	Gray	Pail
Canada	CFPQT	1 quart (.946 L)	Gray	Pail
Canada	CFP1	1 gallon (3.78 L)	Gray	Pail

LIMITED WARRANTY

Custom Building Products ("Custom") warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's sole liability under this warranty shall be limited to the replacement of the product. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's printed instructions. Custom makes no other warranties either express or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state.



CUSTOM®
BUILDING PRODUCTS