## **SAFETY DATA SHEET**

## **Section 1: IDENTIFICATION**

#### 1.1 PRODUCT IDENTIFIER

**Product Name:** SimpleFix® Pre-Mixed Adhesive & Grout

Product Code: Not Available

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Product Use: Adhesive

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEETS

Name/Address: Custom Building Products

Five Concourse Parkway, Suite 1900

Atlanta, GA 30328

**Telephone Number:** 1-(800)-272-8786

1.4 EMERGENCY TELEPHONE NUMBER

**Emergency Telephone** INFOTRAC 1-800-535-5053 (US and Canada)

Number: INTERNATIONAL + 1-352-323-3500

## Section 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE CHEMICAL IN ACCORDANCE WITH PARAGRAPH (d) OF 29 CFR 1910.1200 (OSHA HAZCOM2012)

Carcinogenicity Category 1A
Eye Irritation Category 2A
Specific Target Organ Toxicity—Repeated Exposure Category 1

## 2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM2012

2.2a SIGNAL WORD:

DANGER!

2.2b HAZARD STATEMENTS

May cause cancer through inhalation of dust Causes serious eye irritation Causes damage to organs through prolonged or repeated exposure

#### 2.2c HAZARD PICTOGRAMS





#### 2.2d PRECAUTIONARY STATEMENTS

i.	PREVENTION	Wash hands thoroughly after handling. Do not breathe dust/fume/vapors. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear impervious gloves/protective clothing/eye protection.
ii.	RESPONSE	If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: call a poison center/doctor. If swallowed call a poison center/doctor. Rinse mouth. Do NOT induce vomiting. If exposed or concerned: get medical advice/attention.
iii.	STORAGE	Store in a well-ventilated place. Keep container tightly closed.
iv.	DISPOSAL	Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations.

## 2.3 ADDITIONAL INFORMATION

# 2.3a HNOC – HAZARDS NOT OTHERWISE CLASSIFIED

Not Applicable

## 2.3b UNKNOWN ACUTE TOXICITY

11% of the mixture consists of ingredient(s) of unknown acute toxicity.

## **Section 3: COMPOSITION/INFORMATION ON INGREDIENTS**

## 3.1 MIXTURES

Chemical Name	CAS Number	Weight %
Crystalline Silica, Quartz	14808-60-7	40 – 70%*
Ethylene Glycol	107-21-1	0.5 – 1.5%*
Diethylene Glycol Monobutyl Ether	112-34-5	0.5 – 1.5%*

<sup>\*</sup>Means that the component will fall into one the ranges specified due to batch-to-batch variability.

## **Section 4: FIRST-AID MEASURES**

## 4.1 DESCRIPTION OF THE FIRST-AID MEASURES

ROUTES OF EXPOSURE	DESCRIPTION
Eye Contact:	In case of contact, immediately flush eyes with plenty of water for several minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.
Skin Contact:	In case of contact, immediately flush skin with plenty of water.

## SAFETY DATA SHEET

Remove contaminated clothing and shoes. Wash clothing before

reuse. Call a physician if irritation develops and persists.

**Inhalation:** If breathing is difficult, remove victim to fresh air and keep at rest in

a position comfortable for breathing. Get medical advice/attention if

you feel unwell.

**Ingestion:** If swallowed, do NOT induce vomiting unless directed to do so by

medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention.

## 4.2 MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED

ROUTES OF EXPOSURE DESCRIPTION

**Eye Contact:** Causes serious eye irritation. Symptoms may include discomfort or

pain, excess blinking and tear production, with marked redness and

swelling of the conjunctiva.

**Skin Contact:** May cause skin irritation. Symptoms may include redness, drying,

defatting and cracking of the skin.

**Inhalation:** May cause respiratory tract irritation. Causes damage to organs

through prolonged or repeated inhalation of dust. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a

serious disabling and fatal lung disease.

Ingestion: May be harmful if swallowed. Ingestion may cause discomfort

and/or distress, nausea or vomiting.

#### 4.3 INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

**Note to Physicians:** Symptoms may not appear immediately.

Specific Treatments: In case of accident or if you feel unwell, seek medical advice

immediately (show the label or SDS where possible).

#### Section 5: FIRE-FIGHTING MEASURES

#### 5.1 FLAMMABILITY

Flammability: Not Flammable/Not Combustible by WHMIS/OSHA HAZCOM2012 Criteria

## **5.2 EXTINGUISHING MEDIA**

#### 5.2a. Suitable Extinguishing Media:

Treat for surrounding material

## 5.2b. Unsuitable Extinguishing Media:

Not Available

## SAFETY DATA SHEET

#### 5.3 SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

#### 5.3a. Products of Combustion:

May include, and are not limited to: oxides of carbon

#### 5.3b. Explosion Data

i. Sensitivity to Mechanical Impact:

Not Available

ii. Sensitivity to Static Discharge:

Not Available

#### 5.4 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection(SCBA).

## Section 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

#### 6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

**Methods for Containment:** Recover all usable material. Contain and/or absorb spill with inert

material (e.g. sand, vermiculite), then place in suitable container. Do not flush to sewer or allow entrance to waterways. Use

appropriate Personal Protective Equipment (PPE).

**Methods for Cleaning-Up:** Scoop up material and place in a disposal container. Provide

ventilation.

## Section 7: HANDLING AND STORAGE

#### 7.1 PRECAUTIONS FOR SAFE HANDLING

Handling: Use in well-ventilated areas. Wear impervious gloves and eye

protection. Do not mix with other chemical products. Do not get in

eyes. Do not get on skin or clothing. Do not breathe

dust/fume/vapors. Do not take internally.

**General Hygiene Advice:** Use good industrial hygiene practices and wear recommended

personal protection. Launder contaminated clothing before reuse.

Wash hands before eating, drinking, or smoking.

## 7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage: Keep out of the reach of children. Keep container tightly closed.

Store at room temperature and keep containers closed when not in

use.



## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

# 8.1 CONTROL PARAMETER Exposure Guidelines

Occupational Exposure Limits					
Chemical Name OSHA-PEL ACGIH-TLV					
Crystalline Silica, Quartz	0.1 mg/m³	0.025 mg/m³ (Resp.)			
Ethylene Glycol	50 ppm	50 ppm			
Diethylene Glycol Monobutyl Ether	Not Available	Not Available			

#### **8.2 EXPOSURE CONTROLS**

**Engineering Controls:** Use ventilation adequate to keep exposures (airborne levels of

dust, fume, vapor, etc.) below recommended exposure limits.

#### 8.3 INDIVIDUAL PROTECTION MEASURES

#### 8.3a. Personal Protective Equipment:

**i. Eye/Face Protection:** Wear approved eye protection [properly fitted dust- or splash-proof chemical safety goggles/face (face shield)]

## ii. Skin Protection:

1. Hand Protection: Wear impervious gloves, such as nitrile.

2. Body Protection: Wear suitable protective clothing

- **iii. Respiratory Protection:** A NIOSH approved respirator or filtering face piece, such as N95, is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).
- iv. General Health and Safety Measures: Handle according to established industrial hygiene and safety practices. Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Wash contaminated clothing before reusing.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.):	Sanded Paste(White Or Alabaster)
Odor:	Characteristic
Odor Threshold:	Not Available
pH:	8.80 – 9.50
Melting point/Freezing point:	Not Available
Initial boiling point and boiling range:	Not Available
Flash point:	>212°F(>100°C)
Evaporation rate (Water=1):	Not Available

# SAFETY DATA SHEET

Flammability:	Not Flammable/Not Combustible
Upper Flammability/Explosive Limit:	Not Available
Lower Flammability/Explosive Limit:	Not Available
Vapor Pressure	Not Available
Vapor Density:	Not Available
Relative Density:	1.60 – 1.90 g/mL
Solubility in Water:	Not Available
Partition coefficient: n-octanol/water:	Not Available
Auto-ignition temperature:	Not Available
Decomposition Temperature:	Not Available
Viscosity (cps):	Not Available
VOC Content:	<65 g/L (0% CARB VOC)

## **Section 10: STABILITY AND REACTIVITY**

#### 10.1. REACTIVITY

No dangerous reaction known under conditions of normal use.

#### 10.2. CHEMICAL STABILITY

Stable under normal storage conditions. Keep dry in storage.

## 10.3. POSSIBILITY OF HAZARDOUS REACTION

No dangerous reaction known under conditions of normal use.

#### 10.4. CONDITIONS TO AVOID

Heat. Incompatible materials.

#### 10.5. INCOMPATIBLE MATERIALS

None known.

#### 10.6. HAZARDOUS DECOMPOSITION PRODUCTS

Upon decomposition, this product may yield oxides of carbon.

## Section 11: TOXICOLOGICAL INFORMATION

## 11.1. LIKELY ROUTES OF EXPOSURE:

Skin contact, skin absorption, eye contact, inhalation, and ingestion.

#### 11.2. SYMPTOMS RELATED TO PHYSICAL/CHEMICAL/TOXICOLOGICAL CHARACTERISTICS:

**Eye Contact:** Causes serious eye irritation. Symptoms may include discomfort or

pain, excess blinking and tear production, with possible redness

and swelling.

**Skin Contact:** May cause skin irritation. Symptoms may include redness, drying,

defatting and cracking of the skin.

**Inhalation:** May cause respiratory tract irritation. Causes damage to organs

through prolonged or repeated inhalation of dust. This product contains crystalline silica. Prolonged or repeated inhalation of

# **SAFETY DATA SHEET**

respirable crystalline silica from this product can cause silicosis, a serious disabling and fatal lung disease.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea

or vomiting.

Acute Toxicity(ATE <sub>mix</sub> = 9,977 mg/kg)					
Chemical Name LC50 LD50					
Crystalline Silica, Quartz Not Available		Oral: >10,000 mg/kg, rat			
Ethylene Glycol	Inhalation: >2.5 mg/L, rat	Oral: 4,700 mg/kg, rat			
Diethylene Glycol Monobutyl Ether	Not Available	Oral: 2,410 mg/kg, rat			

Carcinogenicity			
Chemical Name	Chemical Listed as Carcinogens or Potential Carcinogo (NTP,IARC,OSHA,ACGIH,CP65)		
Crystalline Silica, Quartz	N-2, I-1, O-1, ACGIH-A2, CP65		
Ethylene Glycol	ACGIH-A4		
Diethylene Glycol Monobutyl Ether	Not Listed		

## 11.3. DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT AND LONG-TERM EXPOSURE

SHORT-TERM			
Skin Corrosion/Irritation:	May cause skin irritation		
Serious Eye Damage/Irritation:	Causes serious eye irritation		
Respiratory Sensitization:	Not Classified		
Skin Sensitization:	Not Classified		
STOT-Single Exposure:	May cause respiratory irritation		
Aspiration Hazard:	Not Classified		
LONG-TERM			
Carcinogenicity:	May cause cancer through inhalation of dust		
Germ Cell Mutagenicity:	Not Classified		
Reproductive Toxicity:	Not Classified		
STOT-Repeated Exposure:	Causes damage to organs through prolonged or repeated exposure		
Synergistic/Antagonistic Effects:	Not Classified		

## **Section 12: ECOLOGICAL INFORMATION**

#### 12.1. ECOTOXICITY

May cause long-term adverse effects to the aquatic environment. Keep from entry into sewers and waterways.

Ecotoxicity				
Chemical Name	EC50/NOEC-48 Hours	LC50/NOEC-96 Hours		
Crystalline Silica, Quartz	Not Available	Not Available		
Ethylene Glycol	Not Available	18,500 mg/L, Oncorhynchus mykiss		
Diethylene Glycol Monobutyl Ether	Not Available	Not Available		

## 12.2. PERSISTENCE AND DEGRADABILITY

Not Available

## 12.3. BIOACCUMULATIVE POTENTIAL

Not Available

# **SAFETY DATA SHEET**

#### 12.4. MOBILITY IN SOIL

Not Available

#### 12.5. OTHER ADVERSE EFFECTS

Not Available

## **Section 13: DISPOSAL CONSIDERATIONS**

#### 13.1. DISPOSAL METHOD

Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations

## 13.2. OTHER DISPOSAL CONSIDERATIONS

Not Available

## **Section 14: TRANSPORT INFORMATION**

DOT (U.S.)	TDG (CANADA)	IATA	
UN NUMBER:	UN NUMBER:	UN NUMBER:	
Not Regulated	Not Regulated	Not Regulated	
UN PROPER SHIPPING NAME:	UN PROPER SHIPPING NAME:	UN PROPER SHIPPING NAME:	
Not Regulated	Not Regulated	Not Regulated	
TRANSPORT HAZARD CLASS (ES):	TRANSPORT HAZARD CLASS (ES):	TRANSPORT HAZARD CLASS (ES):	
Not Regulated	Not Regulated	Not Regulated	
PACKING GROUP (if applicable):	PACKING GROUP (if applicable):	PACKING GROUP (if applicable):	
Not Regulated	Not Regulated	Not Regulated	

SUMMARY: Product is NOT regulated under DOT/TDG and other transportation regulations.

## 14.1. ENVIRONMENTAL HAZARDS

Not Available

# 14.2. TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE Not Available

## 14.3. SPECIAL PRECAUTIONS FOR USER

Do not handle until all safety precautions have been read and understood.

## **Section 15: REGULATORY INFORMATION**

# 15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATIONS SPECIFIC FOR THE CHEMICAL

Canada: This product has been classified in accordance with the hazard criteria of the



Hazardous Products Regulations and the SDS contains all the information required by the Hazardous Products Regulations.

**US:** SDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

## **15.2. US FEDERAL INFORMATION:**

	SARA TITLE III			
CHEMICAL NAME	SECTION 302 (EHS) TPQ (LBS)	SECTION 304 EHS RQ (LBS)	CERCLA RQ (LBS)	SECTION 313 (TRI)
Crystalline Silica, Quartz	Not Listed	Not Listed	Not Listed	Not Listed
Ethylene Glycol	Not Listed	Not Listed	5,000	Listed
Diethylene Glycol Monobutyl Ether	Not Listed	Not Listed	Not Listed	Listed

## 15.3. US STATE RIGHT TO KNOW LAWS:


California Proposition 65:	warning: This product can expose you to chemicals including crystalline silica, which is known to the State of California to cause cancer, and ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="https://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> .
Other U.S. States "Right to Know" Lists:	
New Jersey:	Silica, Quartz: CAS#14808-60-7 Calcium Carbonate: CAS#1317-65-3 Ethylene Glycol: CAS#107-21-1 Diethylene Glycol Monobutyl Ether: CAS#112-34-5 Titanium Dioxide: CAS#13463-67-7
Pennsylvania:	Silica, Quartz: CAS#14808-60-7 Calcium Carbonate: CAS#1317-65-3 Ethylene Glycol: CAS#107-21-1 Diethylene Glycol Monobutyl Ether: CAS#112-34-5 Titanium Dioxide: CAS#13463-67-7
Massachusetts:	Silica, Quartz: CAS#14808-60-7 Calcium Carbonate: CAS#1317-65-3 Ethylene Glycol: CAS#107-21-1 Diethylene Glycol Monobutyl Ether: CAS#112-34-5 Titanium Dioxide: CAS#13463-67-7
Minnesota:	Silica, Quartz: CAS#14808-60-7 Calcium Carbonate: CAS#1317-65-3 Ethylene Glycol: CAS#107-21-1 Diethylene Glycol Monobutyl Ether: CAS#112-34-5 Titanium Dioxide: CAS#13463-67-7
Florida:	Not Available
Michigan:	Not Available


## 15.4. GLOBAL INVENTORIES

Chemical Name	USA TSCA	Canada DSL/NDSL
Crystalline Silica, Quartz	YES	DSL
Ethylene Glycol	YES	DSL
Diethylene Glycol Monobutyl Ether	YES	DSL




#### 15.5. NFPA AND HMIS RATINGS:





Hazard Index	
4	Severe Hazard
3	Serious Hazard
2	Moderate Hazard
1	Slight Hazard



#### 15.6. SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

CP65	California Proposition 65
OSHA (O)	Occupational Safety and Health Administration
ACGIH (G)	American Conference of Governmental Industrial Hygienists
	A1 – Confirmed human carcinogen
	A2 – Suspected human carcinogen
	A3 – Animal carcinogen
	A4 – Not classifiable as a human carcinogen
	A5 – Not suspected a human carcinogen
IARC (I)	International Agency for Research on Cancer
	<ul> <li>1 – The agent (mixture) is carcinogenic to humans</li> </ul>
	<ul> <li>2A – The agent (mixture) is probably carcinogenic to humans; there</li> </ul>
	is limited evidence of carcinogenicity in humans and sufficient



# **SAFETY DATA SHEET**

	<ul> <li>evidence of carcinogenicity in experimental animals.</li> <li>2B – The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.</li> <li>3 – The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.</li> <li>4 – The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.</li> </ul>
NTP (N)	National Toxicology Program
	1 – Known to be carcinogens
	<ul> <li>2 – Reasonably anticipated to be carcinogens</li> </ul>

## **Section 16: OTHER INFORMATION**

**Date of Preparation:** January 20, 2015

Version: 2.1

**Revision Date:** September 13, 2017

**Disclaimer:** The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products

Prepared by: Custom Building Products

Phone: (562)-968-2980

www.custombuildingproducts.com

**End of Safety Data Sheet**