



Cabot® Crystal Clear Waterproofing

#1000

DESCRIPTION

Cabot® Waterproofing provides unsurpassed waterproofing. This simple-to-use formulation penetrates and fills the pores of the substrate with premium silicone and will impart lasting repellency to any surface where it is applied.

PRODUCT FEATURES

- Silicone fortified to last 5 times longer than ordinary wax-based formulas
- Penetrates to fill surface pores and lock out water
- Easy to use, long lasting on all surfaces

FOR USE ON

- Wood
- Concrete
- Brick
- Stone
- Unglazed tile
- Masonry
- Decks
- Patios
- Fences
- Walkways
- Foundations
- Driveways

TINTING

Do not tint this product.

COVERAGE

100–250 sq. ft. per gallon (9.3–23 m²). Rates will vary depending on porosity of the surface.

DRYING TIME

Dries to touch in 1 hour. Time will vary depending on temperature and humidity. Recently applied Cabot® Waterproofing may remain slick, even when dry, until surface has been exposed to general weathering (rain and sun) for several days.

SURFACE PREPARATION

Surfaces should be clean, porous and free of any previous finishes. To test for porosity, apply a few drops of water to the substrate. The surface is ideal for application if water can be quickly absorbed. Use Cabot® Problem-Solver® Wood Cleaner in order to remove dirt, mildew, stains, algae stains and other foreign matter. Use Cabot® Problem-Solver® Wood Brightener to easily remove extractive bleeding as well as nail and metal rust stains. Cabot® Problem-Solver® Wood Stripper can be used to remove coatings from surfaces to be treated. New masonry, stucco and concrete must be cured for a minimum of 30 days. Always apply to a small test area and allow to dry.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the USEPA/Lead Information Hotline at 1-800-424-LEAD (5323) or visit www.epa.gov/lead.

APPLICATION

Shake container thoroughly before using. Apply liberally and evenly using a low-pressure sprayer, nylon or synthetic brush, roller, or by dipping. When using a sprayer, be sure to back-brush or roll immediately after spraying. To avoid streaking, start at the bottom and spray toward the top. **One coat is recommended.** Reapply seasonally or every 1–2 years depending on exposure. Use caution when standing or walking on surfaces still wet after the application of Cabot® Waterproofing, as the surface may be very slippery.

Airless Spray: Recommended tip sizes and adjustments are 1000–1500 PSI, 0.013–0.015" tip with fan width of 8–10". These recommendations are a starting point only. Due to variability in sprayers, we recommend testing your spray pattern and flow before proceeding. If spraying large surfaces, be sure to back-brush or roll immediately after spraying. When using HVLP spray equipment, see manual for proper set-up instructions.

RESTRICTIONS

For exterior use only. Do not apply when air or surface temperature is below 40 °F or may fall below 40 °F for 24 hours after application. To stain or paint over surfaces treated with Cabot® Waterproofing, allow a period of up to 12 months for the surface to sufficiently weather. Allow the surface to dry for 6 hours before contact with water. Do not thin or combine with any other products. Do not use steel wool on surfaces that are to be coated with this product. Do not apply over painted or sealed surfaces.

MAINTENANCE

UV rays (sunlight) and moisture (rain/snow/dew) are wood's natural enemies, so minimize exposure. Evaluate finish each spring and maintain as needed. Finish durability depends upon weather, wear and other local conditions, but finish typically lasts 1–2 years.



Cabot® Crystal Clear Waterproofing

#1000

TECHNICAL DATA

Pigment Type: Silicone emulsion, Trans-oxide pigments

Vehicle Type: Silicone Emulsion

Viscosity: 8–13 seconds, #4 Ford cup

Flash Point: N/A

V.O.C. Content: < 100 g/L

Solids Weight: 3%

Solids Volume: 3%

Pigment Weight: 1%

Density: 8.3 lbs./gal.

Film Thickness: Minimal

REGULATORY COMPLIANCE

Current as of: 12/16/2014

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes

PACKAGING

Available in gallon and 5 gallon.

BASE AND FILL LEVELS

	(oz./gal.)
Crystal Clear (1000)	128

CLEANUP AND DISPOSAL

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulations.

WARRANTY

If this product does not perform as stated on the label after you apply it according to label directions, Cabot will either replace this product or refund its purchase price, at its option. Cabot disclaims all other implied or expressed warranties. Cabot will not provide or pay for labor for removal or application of the product. This warranty excludes all incidental or consequential damages. This warranty gives you specific legal rights, and you may have other rights which vary from state to state.

CAUTIONS

CAUTION! KEEP OUT OF THE REACH OF CHILDREN. May cause eye and skin irritation. **Use only with adequate ventilation.** Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **DO NOT TAKE INTERNALLY. First Aid: Eye Contact:** Immediately flush with plenty of water for at least 15 minutes. If irritation persists, get medical attention.* **If Inhaled:** If affected by inhalation of vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.* **If Swallowed:** Drink 2 glasses of water. Get medical attention immediately.*

* Call poison control center, hospital emergency room or physician immediately.

UCL 1.1

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

8725 W. Higgins Rd., Chicago, IL 60631
800-US-STAIN
cabotstain.com
Revised: 12/16/14
Version: 1000C