

CAM-ALLOY®



Campbell®

Campbell®

Another Campbell advantage –
a complete selection of Grade 100 products

In 1992, Campbell pioneered the development of Grade 100 chain and fittings. Today, we continue to be the leader in the products that give you working load limits, manufacturing proof tests, and design strengths that are 25% higher than the Grade 80 competition.

NEW



CAM-ALLOY
SELF LOCKING HOOKS

Size (in.)	Eye Style Cat. No.	Clevis Style Cat. No.	WLL (lbs.)
9/32"	5648495	5748495	4,300
3/8"	5648695	5748695	8,800
1/2"	5648895	5748895	15,000
5/8"	5649095	5749095	22,600

CAM-ALLOY
CHAIN GRADE 100

Size (in.)	Cat. No.	WLL (lbs.)
7/32" *	0400312	2,100
9/32"	0405212	4,300
5/16" *	0400512	4,500
3/8"	0405412	8,800
1/2"	0405512	15,000
5/8"	0405612	22,600
3/4"	0405712	35,300
7/8"	0405812	42,700
1" *	0401612	47,700
1-1/4" *	0402012	72,300

CAM-ALLOY OBLONG
MASTER LINKS

Size (in.)	Cat. No.	WLL (lbs.)
3/8" *	5685615	4,200
1/2"	5683215	8,600
3/4"	5683315	17,600
1-1/8"	5683415	30,000
1-1/4"	5683515	45,200
1-5/8"	5683615	70,600
1-7/8"	5683715	105,900
2" *	5687015	102,600
2-1/4" *	5687215	144,600

CAM-ALLOY / QUIK-ALLOY
COUPLING LINKS

Size (in.)	Cat. No.	WLL (lbs.)
7/32" *	5770315	2,100
9/32"	5779125	4,300
3/8"	5779135	8,800
1/2"	5779145	15,000
5/8"	5779155	22,600
3/4"	5779165	35,300
7/8"	5779175	42,700
1" *	5771615	47,700
1-1/4" *	5772015	72,300

CAM-ALLOY/QUIK-ALLOY
SLING HOOKS

Size (in.)	EYE STYLE		CLEVIS STYLE		WLL (lbs.)
	Cat. No. (Regular)	Cat. No. (Latched)	Cat. No. (Regular)	Cat. No. (Latched)	
9/32"	5644415	5644495	5744415	5744495	4,300
3/8"	5644615	5644695	5744615	5744695	8,800
1/2"	5644815	5644895	5744815	5744895	15,000
5/8"	5645015		5745015	5745095	22,600
3/4"	5645215		5745215	5745295	35,300
7/8"	5645415				42,700
1" *	5641615				47,700

CAM-ALLOY
FOUNDRY HOOKS

Size (in.)	Cat. No.	WLL (lbs.)
9/32"	5664415	4,300
3/8"	5664615	8,800
1/2"	5664815	15,000
5/8"	5665015	22,600
3/4"	5665215	35,300
7/8"	5665415	42,700
1" *	5661615	47,700
1-1/4" *	5662015	72,300

CAM-ALLOY/QUIK-ALLOY
GRAB HOOKS

Size (in.)	Eye Style Cat. No.	Clevis Style Cat. No.	WLL (lbs.)
9/32"	5624415	5724415	4,300
3/8"	5624615	5724615	8,800
1/2"	5624815	5724815	15,000
5/8"	5625015	5725015	22,600
3/4"	5625215	5725215	35,300
7/8"	5625415		42,700
1" *	5621615		47,700

* Grade 80

Superior shackles,
selection and service.

High-quality shackles, plus full-line expertise and outstanding
after-the-sale attention. That's the Campbell® advantage.

Apex Tool Group, LLC
14600 York Road, Suite A
Sparks, Maryland 21152
www.apextoolgroup.com

ATG-1022 /???????/5M / PRINTED 9/12 / ITEM NO. T550847
©2012 Apex Tool Group, LLC

CAMPBELL® and CAM-ALLOY® are registered trademarks of Apex Brands, Inc.,
a Division of Apex Tool Group, LLC Specifications subject to change without notice.



Made in the USA

- Forged steel for maximum strength
- Statistically tested for hardness, tensile strength, impact resistance, ductility and fatigue
- 6 to 1 design factor
- Manufactured in our Cortland, New York facility
- ISO 9001 compliant
- Additional product certification upon request
- A leading supplier in the worldwide industrial and marine markets
- Continuing tech support and training

The Campbell Difference

Campbell offers the full range of products and support services that guarantees industrial and marine users quality, value and peace of mind.

Bows, pins, and bolts galvanized to ASTM A-153

Meets Federal Specification RR-C-271D, Type IV

All Campbell carbon and alloy shackles are made in U.S.A.

Drop-forged for superior strength and performance

6 to 1 design factor

Pins and bolts made of alloy steel; through hardened by a quench and tempering process



Date Code, "WLL" (Working Load Limit), "Campbell" or "CC", "USA" and size are permanently forged on shackle bow



When you buy Campbell shackles, you get our expertise in a broad line of material handling products, including chain, fittings, blocks and clamps.



Bolt Type
Anchor Shackles

Size (in.)	Carbon Steel Galvanized		Alloy Steel Galvanized	
	Cat.No.	WLL (Ton)	Cat.No.	WLL(Ton)
1/4"	5390435	1/2		
3/8"	5390635	1		
1/2"	5390835	2	5390895	3-1/4
5/8"	5391035	3-1/4		
3/4"	5391235	4-3/4	5391295	7
7/8"	5391435	6-1/2		
1"	5391635	8-1/2	5391695	12-1/2
1-1/8"	5391835	9-1/2		
1-1/4"	5392035	12	5392095	18
1-3/8"	5392235	13-1/2		
1-1/2"	5392435	17	5392495	30
1-3/4"	5392835	25		
2"	5393235	35		
2-1/2"	5394035	55		

Screw Pin
Anchor Shackles

Size (in.)	Carbon Steel Painted Blue		Carbon Steel Galvanized	Alloy Steel Galvanized	
	Cat.No.	WLL (Ton)	Cat.No.	WLL(Ton)	Cat.No. WLL(Ton)
3/16"			5410335	1/3	
1/4"	5410405	1/2	5410435	1/2	
5/16"	5410505	3/4	5410535	3/4	
3/8"	5410605	1	5410635	1	5410695 2
7/16"	5410705	1-1/2	5410735	1-1/2	
1/2"	5410805	2	5410835	2	5410895 3-1/3
5/8"	5411005	3-1/4	5411035	3-1/4	
3/4"	5411205	4-3/4	5411235	4-3/4	5411295 7
7/8"	5411405	6-1/2	5411435	6-1/2	
1"	5411605	8-1/2	5411635	8-1/2	5411695 12-1/2
1-1/8"	5411805	9-1/2	5411835	9-1/2	
1-1/4"	5412005	12	5412035	12	5412095 18
1-3/8"	5412205	13-1/2	5412235	13-1/2	
1-1/2"	5412405	17	5412435	17	
1-3/4"	5412805	25	5412835	25	
2"	5413205	35	5413235	35	
2-1/2"			5414035	55	