

PLASTIMASK TAPE


U.V. RESISTANT
HIGH HOLDING POWER

EXAMPLE OF APPLICATION



DESCRIPTION

This tape is made of a red polyethylene film and coated with a natural rubber adhesive. This tape is designed for masking and protecting surfaces during stucco application. Recommended as well as general protective tape, repair tape and identification tape. Removes clean with up to 30 days exposure to sunlight.

MAIN FEATURES

- Polyethylene film conforms very well to all type of surfaces.
- The strong adhesive will hold on rough surfaces.
- Moisture resistant.
- Will remove cleanly after 30 days on outdoor application.

APPLICATIONS

- Protective masking for non-painted surfaces such as wood, glass, steel, vinyl and aluminum.
- Indoor and outdoor application.
- Splicing and holding polyethylene sheeting.
- Patching and repairing a variety of surfaces.

TECHNICAL DATA

Colour	Red
Backing	Polyethylene film
Adhesive	Natural rubber
Thickness	7 mil
Adhesion to steel	50 oz/in
Tensile strength	23 lb/in
Elongation	99%
Temperature Resistance	80°C (176°F) for 30 minutes
Application Temperature	5°C (41°F) to 50°C (122°F)
VOC (Volatile Organic Compound) content	0%

STOCK SIZE

48 mm x 55 m — 24 rolls/case

Please note:

The technical characteristics quoted are averages only and may vary within industry tolerances.

The final user must assure product suitability for the application and assumes all risks and liabilities.