



cantech.com

205-**

CONTRACTORS' SHEATHING TAPE



DESCRIPTION

This tape is made of a UV resistant polypropylene film and coated with high shear, high tack solvent based acrylic adhesive.

** This tape is meant for permanent application only.
It will leave adhesive residue if removed.*

MAIN FEATURES

- High tack adhesive provides aggressive contact.
- Strong and durable holding power.
- Water and moisture resistant.
- Excellent resistance to UV and weathering.
- Prevents air infiltration.
- CCMC Evaluation Report #11955-R.

APPLICATIONS

- Sealing of joints and seams of insulation materials.
- Tape has to be pressed firmly on surface.
- Should be applied on clean, dry surfaces.

TECHNICAL DATA

Colour	Red (02), White (10)
Backing	UV Resistant Polypropylene Film
Adhesive	Solvent Based Acrylic
Thickness	3 mil
Adhesion to steel	40 oz/in
Tensile strength	30 lb/in
Elongation	120%
Application Temperature	-18°C (0°F) to 50°C (122°F)
Temperature Resistance	-40°C (-40°F) to 100°C (212°F)
VOC (Volatile Organic Compound) content	Estimated 0,1%
Water Vapor Transmission (ASTM E96)	0.068 perm (gr/ft ² /hr/in-Hg)
Water Penetration Rate (ASTM D3816)	0.009 g/100 in ² /24 hr
Air Permeance Rate (ASTM E2178)	0.0010 L/s m ² [0.0002 cfm/ft ²]

STOCK SIZE

60 mm x 66 m — 20 rolls/case

Please note:

The technical characteristics quoted are averages only and may vary within industry tolerances.

The final user must assure product suitability for the application and assumes all risks and liabilities.

