



GTX Diesel 15W-40

Passenger Car/Light Truck Diesel Engine Oil

Description

Castrol® GTX Diesel15W-40 is a premium quality diesel engine oil formulated to provide exceptional lubrication for passenger car and light truck diesel engines where API CJ-4/SN is required.

Advantages

- Provides exceptional protection from piston deposits, oil thickening and valve train wear while minimizing engine sludge formation
- Engineered to provide exceptional performance in engines operating under severe service conditions, including towing and hauling under high temperatures
- Special viscosity improvers, anti-wear, anti-oxidant and detergent additives protect and maintain cleanliness in hot running, diesel and gasoline engines

Typical Characteristics

Name	Method	Units	Typical Result
Viscosity@			
40 °C, cSt	ASTM D-445	cSt	119.5
100 °C, cSt	ASTM D-445	cSt	15.5
Viscosity Index	ASTM D-2270		139
Pour Point, °C max	ASTM D-97	°C	-36
TBN	ASTM D-2896	mg/g KOH	8.5
Sulfated Ash Content	ASTM D-874	%wt.	0.95
Density @15°C, relative	ASTM D-1298	g/ml	0.886
Pounds per Gallon			7.378
Flash Point, PMCC, min	ASTM D-92	°C	200

Product Performance Claims

API CJ-4/SN

Additional Information

Part Numbers and UPCs: Size	Case Part No.	Bottle/Unit UPC	Case UPC
6/1 Qt	06141	79191-00846-1	79191-06141-1
3/1 Gal	03849	79191-00847-8	79191-03847-5
5 Gal. Pail	0845	79191-00845-4	
6 Gal. Manual Epack	60082	79191-20082-7	79191-60082-5
55 Gal. Drum	0847	79191-01847-7	
Bulk	0840		

Warranty and Protection Requirements

- Applicable for on and off road heavy duty 4-stroke trucks, gasoline and diesel light trucks and passenger cars where API CJ-4, CI-4, CH-4, CG-4, CF-4, CF, SN are recommended

Meets Ford WSS-M2C171-D

GTX Diesel 15W-40

29 Nov 2013

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470

Telephone: 1,800.462.0835

www.castrol.com/us Email: contactus@bp.com