

50ft 12/3 STW Pro Cap Covered Power Distribution Cord 600V



Our heavy-duty Pro Cap Extension Cords feature molded and lighted, Pro Cap™ multi-outlet connectors and our ring sealed male plug.

FEATURES

- Manufactured to 12/3 AWG (American Wire Gauge) specifications.
- Each of the 3 conductors contain 65 strands of soft drawn annealed 30 gauge 100% copper wire.
- Type "STW" 600V thermo vinyl cold weather jacket guarantees the cord not to crack and remain flexible in temperatures below freezing.
- Converts a single outlet extension cord into five (5) outlets at 10ft. intervals on a 50ft. cord.
- Clear neon lighted connectors indicates that there is power in the circuit.
- Bright neon lamps are rated for 25,000 hours of usage.
- Cap covers keep moisture, dirt and grime out of the outlets when not in use.
- Pro Cap™ outlets when used with a Pro Cap™ male plug will form a water resistant, dust resistant, airtight connection.
- Pro Cap[™] extension cords (plugs & connectors) will not pull apart from each other. This is due to an airtight suction induced seal at each connection that's created as the cords ends are plugged together.
- Bright neon lamps are rated for 25,000 hours of usage.
- · Jacket Color: White, Black or Yellow
- Length: 50ft

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Part number **D12421050**

Length **50'**

Description

Pro Cap Multi-Outlet Cord

Product line

Pro Cap Multi-Outlet

Color

Yellow

Gauge/Conductors

12/3

Wire type

STW

Certifications

n/a

Electrical ratings

15A, 125V, 1875W

Product packaging

Cuff Wrapper

Unit dimensions D x W x H (inches)

13.0 x 13.0 x 4.0

Unit weight (lbs)

12.7

Master carton type

Plain corrugated

Master carton dimensions D x W x H

12.4 x 14.5 x 9.0

Master carton weight (lbs)

26.7

Master carton case quantity

_

Master carton cube (cu. ft.)

1.0

UPC

661899 111569