

# CHAMPION PDS

PRODUCT DATA SHEET

## DIESEL FLO FUEL CONDITIONER & ANTI-GEL

CHAMPION Diesel Flo is a premium diesel fuel anti-gel and de-icer designed to prevent operability issues in diesel fueling systems at sub-zero temperatures. Disperses and removes water from diesel fuel and prevents icing of fuel filters. Cold-flow improvers prevent aggregation of diesel wax crystals, allowing for lower pouring points, cold-filter plugging points (CFPPs), and gel temperatures in low-sulfur and ultra-low sulfur diesel fuels and biodiesel blends.

- Most concentrated formula EVER reduces solvent load and decreases cost-to-treat
- Performs in low sulfur and ultra low sulfur diesel and biodiesel blends
- Reduces cold-filter plugging points by as much as 20°C (36°F) in untreated fuels
- Disperses and removes water from fuel
- Reduces the pouring point and gel temperature of fuel
- Helps prevent fuel filter icing and cold-filter plugging
- One quart treats up to 250 US Gallons of diesel fuel

Always shake well before using. Product can continue to provide additional benefits up to approximately twice the labeled treat rate. Further over-treating does not provide significant additional benefit.



## PART# 4183

### Available in:

4183H	-	1 Quart
4183D	-	5 Gallon
4183AN	-	55 Gallon

### TYPICAL PROPERTIES:

PRODUCT CODE:	4183
APPEARANCE	CLEAR
FLASH POINT °C (°F)	12.0 (53.6)
DENSITY	0.8 mg/cu cm @15.6 °C
VISCOSITY	1 mm/s2 @ 40°C / 105°F
DECOMPOSITION TEMP	200°C

FOR HEALTH / SAFETY INFORMATION - REFER TO THE SDS at [WWW.CHAMPIONBRANDS.COM](http://WWW.CHAMPIONBRANDS.COM)

CHAMPION BRANDS, LLC // CLINTON, MO // 800-821-5693 // SINCE 1956

REV 01/20

