

CHAMPION PDS

PRODUCT DATA SHEET

GLOBALTRANS SYNTHETIC MV ATF FLUID

CHAMPION GLOBALTRANS Synthetic MV ATF Fluid is proven in field tests to be so tough to breakdown and so consistent in performance in so many different automatic transmissions. Champion Globaltrans full synthetic multi-vehicle automatic transmission fluid delivers superior performance in low-temperature flow, wear protection, frictional stability and resistance to thermal breakdown and is made with:

100% synthetic base fluid chosen for superior resistance to oxidation and viscosity change. A highly shear stable cold flow viscosity control additive for superior resistance to viscosity change over thousands of miles. Synergistic wear and seal protection chemistry preferred by O.E.M.s and found in premium factory fill fluids. Optimized friction control additives that not only prevent slip and shudder, for smooth shifting. More durable than many other competing brands. Compatible with common transmission seal materials and other automatic transmission fluids.



Follow OEM recommendations regarding extended drain intervals.

WARNING: THIS PRODUCT IS NOT RECOMMENDED IN TRANSMISSIONS SPECIFYING USE OF FORD MERCON® CVT OR TYPE F TRANSMISSION FLUID.

Do NOT use in Continuously Variable Transmissions (CVTs) or Dual-Clutch Transmissions. For use in a wide variety of transmissions for trouble free performance.

See Page 2 for Specifications

PART# 4357

Available in:

4357H	-	1 Quart
4357N	-	1 Gallon
4357D	-	5 Gallon
4357AN	-	55 Gallon

TYPICAL PROPERTIES:

PRODUCT CODE:	4357
COLOR	RED
GRAVITY API @60°F	34.3
VISCOSITY @ 40°C, cSt	35.0
VISCOSITY @ 100°C, cSt	7.2
cP @ -40°C	10200
SUS @ 104°F	158
SUS @ 210°F	50
VISCOSITY INDEX	> 175
POUR POINT °F	< -40
FLASH POINT °F	> 440

FOR HEALTH / SAFETY INFORMATION - REFER TO THE SDS at WWW.CHAMPIONBRANDS.COM

CHAMPION BRANDS, LLC // CLINTON, MO // 800-821-5693 // SINCE 1956

REV 01/20



CHAMPION PDS

PRODUCT DATA SHEET

GLOBALTRANS SYNTHETIC MV ATF FLUID

For use in a wide variety of transmissions for trouble free performance, Champion® Globaltrans is suitable for use* in transmissions specifying;

Acura ATF-Z1
Allison C-3 & C-4, TES-295** & TES-389**
ATF RED 1, RED 1K
Audi/VW G 052 025-A2, Audi/VW G 053 025-A2
Audi/VW G 055 005-A/A1/A2 (ZF Lifeguardfluid 6)
Audi/VW G 055 025 A2 (JWS 3309)
Audi/VW 052 055
BMW JWS 3309 (T-IV), BMW LA2634
BMW ZF 5HP18FL, 5HP24, 5HP30, BMW 7045E
BMW 83 22 9 407 765, BMW 83 222 152 426
BMW ZF Lifeguardfluid 8, Bosch TE-ML 09
Chrysler ATF+, +2, +3 (MS 7176E), ATF +4
Chrysler/Dodge/Jeep 68043742AA
Daihatsu AMMIX ATF D-II, Daihatsu AMMIX ATF D-III SP
FIAT T-IV type, JWS 3309
Ford WSS M2C 922A1, 924A (XT-8-QAW) JWS 3309
Fuso ATF-II, Fuso ATF-SPIII, Fuso ATF-A4
GM DEXRON®-II, GM DEXRON®-IID, GM DEXRON®-IIE
GM/GMCOpel/Saturn AW-1, GM/GMCOpel/Saturn 88863400
GM 21005966, GM 22717466, GM 88900925, GM 9986195
Hino Blue ribbon ATF
Hyundai/Kia SP-IV, Hyundai/Kia SP-IV M, Hyundai/Kia SP-IV-RR
Hyundai/Kia NWS 9638, Hyundai/Kia 040000C90SG
ISUZU BESCO ATF-II, ISUZU BESCO ATF-III
Jaguar ATF 3403 M115, ATF 3403-M115,
Jaguar JLM 20292, Jaguar Fluid 8432
JEEP ATF+3, ATF +4
Land Rover LRO23288
KIA ATF SP-II, SP-III, SP-IV, SP-IVM, Red 1
Mazda ATF D-II, Mazda ATF M-III, Mazda ATF M-V
MAZDA ATF 3317
Mitsubishi Diaqueen SK, Mitsubishi Diaqueen SP-II
Mitsubishi Diaqueen AW, Mitsubishi Diaqueen J2
Mitsubishi Diaqueen ATF PA
Nissan Matic Fluid C, Nissan Matic Fluid D
Opel/GM 19 40 700, Opel/GM 19 40 767
Opel/GM 88900925, Opel/GM 9986195
Porsche 000 043 205 09, Porsche 999 917 547 00 (A2)
Porsche ATF 3403-M115, Porsche T-IV (JWS 3309)
Saab T-IV (JWS 3309), Saab 93 165 147, Saab 93 160 393
Scion (all vehicles)
Ssang yong DSIH 5M-66
Subaru Dexron®-II, Subaru ATF, ATF HP
Suzuki ATF 2384K, Suzuki JWS 3309, Suzuki ATF 3314
Texaco 7045-E, Texaco 8072B, Texaco N402
Toyota ATF T-IV, Toyota ATF WS, Toyota WS*
Voith Svc Bltn #013 and #118
Volvo 97335, Volvo CE 97340
VW G 052 025-A2, VW G 053 025-A2
VW G-053 162 A1 (ZF Lifeguardfluid 5)
VW G 060 162 (ZF Lifeguardfluid 8)
VW G 055 540-A2, VW TL 521 62, VW G US 000 162
ZF TE-ML 05L, ZF TE-ML 09, ZF TE-ML 11A, 11B

Aisin Warner JWS 3309 (T-IV) & JWS 3324 (WS), AW-1
American Motors ATF +3 (MS7176-E), ATF +4 (MS9602)
Audi 5 HP LT71141 (ZF 5 HP 18FL/19FL/24A)
Audi/VW G 052 162-A1/A2 (ZF Lifeguardfluid 5)
Audi/VW G 060 162 (ZF Lifeguardfluid 8)
Audi/VW G 052 990, Audi/VW G 055 540-A2
Bentley PY112995PA
BMW LT71141 (ZF 5 HP 18FL/19FL/24A)
BMW ETL-8072B
BMW 83 222 289 720, BMW ZF Lifeguardfluid 6
CAT TO-2
Chrysler/Dodge MOPAR AS 68 RC (T-IV), JWS 3309
Daewoo LT 71141
Esso LT 71141
Ford MERCON®, Ford XT-2-QDX (M), Ford XT-2-QSM (Syn), Ford FNR5,
Ford ESP-M2C166H, XL-12, Ford MERCON® LV, MERCON® V
GM9986195 (Aisin AW, JWS 3309), GM TASA
GM DEXRON®-IIIG, GM DEXRON®-IIIH, GM DEXRON® VI
GM/GMCOpel/Saturn 88863401, GM 1940700, GM 1940767,
GM 93160393
Honda ATF-Z1, Honda Type 3.0 and 3.1, Honda DW1 (Except CVTs)
Hyundai/Kia SP-III, Hyundai/Kia Dex-II/ SP-II, Hyundai/Kia JWS 3314
Idemitsu K17 3100 PLO85
ISUZU BESCO ATF-SP, ISUZU SCS Fluid, ISUZU 08200-9001
Jaguar ATF LT71141, ZF 5HP24, Jaguar ATF 3403 JLM20238,
JASO M315-2013 1A, JASO M315-2013 1A-LV, JASO M315-2013 2A
Land Rover TYK500050, Land Rover LRO022460
Lexus JWS 3309
Maserati 231603
Mazda ATF FZ, Mazda ATF F-1, Mazda ATF S-1, Mazda ATF N-1
MINI COOPER T-IV
Mitsubishi Diaqueen SP-III, Mitsubishi Diaqueen SP-IV
Mitsubishi Diaqueen J3, Mitsubishi Diaqueen ATF-MA1
NAG 1 (Chrysler, Jeep, Cherokee)
Nissan Matic Fluid J, Nissan Matic Fluid K, Nissan Matic Fluid S
Opel/GM 21005966 Transaxle, Opel/GM 22 17466
Peugot ZF 4HP20, Peugeot/Citreon Z 000169756
Porsche 000 043 205 28, Porsche Z 000169756
Renault Matic D2, Renault DPO/AL4, Renault Samsung SATF-D
Saturn T-IV (JWS 3309)
Shell M-1375.4, Shell L12108
Subaru ATF, Subaru K0140Y0700, Subaru ATF 5AT
Suzuki ATF AW-1, Suzuki AT OIL 5D06, Suzuki ATF 2326
Suzuki ATF 3317
Toyota ATF D-II, Toyota ATF D-III, Toyota ATF T-III
Vickers M2950-S, I-286-S
Volvo PN 1161521, Volvo PN 1161540/1161640, Volvo 97325
VW 5 HP (ZF 5 HP 30), VW 5HP (18FL, 30), VW 5HP (19FL, 24A)
VW G 052 162-A1/A2 (ZF Lifeguardfluid 5)
VW G 055 005-A/A1/A2 (ZF Lifeguardfluid 6)
VW G 055 025 A2 (JWS 3309), VW G 052 055, VW G 052 990
ZF 3, 4, & 6 speed transmissions, ZF 8 speed transmissions
ZF TE-ML 21L

* Champion supports the use of product to replace these specifications based on field results; product does not fall in viscosity range for these specifications.

** Champion supports the use of this fluid in applications requiring TES-295 and TES-398 based on technical judgement, field experience and available data. This product is not approved or endorsed by Allison Transmission, Inc.

FOR HEALTH / SAFETY INFORMATION - REFER TO THE SDS at WWW.CHAMPIONBRANDS.COM

CHAMPION BRANDS, LLC // CLINTON, MO // 800-821-5693 // SINCE 1956

REV 01/20

