

# **Product Submittal Sheet**

Tech Support: 888-437-3244 Engineering Services: 877-832-3206 Sales: 800-543-7140 clarkdietrich.com

# Quicksilver™ Corner Bead (CBS)

## **Hot-dipped Metal Corner Bead**

Quicksilver<sup>™</sup> corner bead is a hot-dipped,highly durable galvanized bead that offers superior corrosion protection. This bead is ideal for humid, moisture-prone conditions and high-traffic areas subject to more than normal abuse.

Recognized as a superior corrosion-resistant drywall finishing corner bead, Quicksilver™ corner bead provides a high-quality finish and solid protection at drywall corners. This traditional drywall finishing product is nailed, stapled, screwed or clinched into place. Flanges are deeply knurled and perforated for excellent joint compound adhesion.

## **Product Data & Ordering Information**

Material: 0.0125" min. thickness, G30 hot-dipped galvanized steel

Dimensions: 1-1/4" leg x 1-1/4" leg

Width	Length	Wt./Ctn.	Pcs./Ctn.
1-1/4" x 1-1/4"	6'-9"	56 lbs	75
1-1/4" x 1-1/4"	6'-10"	57 lbs	75
1-1/4" x 1-1/4"	7'	56 lbs	72
1-1/4" x 1-1/4"	8'	56 lbs	63
1-1/4" x 1-1/4"	9'	56 lbs	56
1-1/4" x 1-1/4"	10'	55 lbs	50
1-1/4" x 1-1/4"	12'	56 lbs	42

#### **ASTM & Code Standards**

- ASTM C1047
- SDS & Product Certification Information is available at www.clarkdietrich.com/SupportDocs


### Storage

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather.

## 09.22.00 (Support for Plaster & Gypsum Board)



- Strong metal reinforcement for drywall corners
- Exposed nose of the bead resists impact and forms a screed for finishing



## Sustainability Credits:

For more details and LEED letters contact Technical Services at 888-437-3244 or visit www.clarkdietrich.com/LEED

LEED v4 MR Credit -- Building Product Disclosure and Optimization: EPD (1 point) - Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) - Innovation Credit (up to 2 points).

LEED 2009 Credit MR 2 & MR 4 -- ClarkDietrich's steel products are 100% recyclable and have a minimum recycled content of 34.2% (19.8% post-consumer and 14.4% pre-consumer). If seeking a higher number to meet Credit MR 5, please contact us at (info@clarkdietrich.com / 888-437-3244)

Metal-CBS © 10/2017 ClarkDietrich Building Systems

Project Information	Contractor Information	Architect Information
Name:	Name:	Name:
Address:	Contact:	Contact:
	Phone:	Phone:
	Fax:	Fax: