



DRINKING WATER

# CW-M2

## Refrigerator Replacement Filter

### ADVANCED FILTRATION TECHNOLOGY

This Culligan® refrigerator water filter contains a compressed carbon block which provides tremendous capacity to remove and/or reduce impurities and sediment that may be present in your drinking water. The carbon block has millions of active sites on it's surface and within the structure which can absorb impurities like a sponge, and can adsorb and hold other types of impurities on it's surface like a magnet. Additionally, this filter can catalytically breakdown other impurities very similar to the way a catalytic converter works in your automobile. These processes ensure that you are getting the cleanest and best tasting water possible.



### THIS FILTER FITS IN PLACE OF:

#### Maytag\*:

UKF8001, UKF8001AXX, 67003523, 67003526, 67003527, 67003528, 12589203, 12589206, 12589208, 12589210, 13040216, 13040216N, UKF9001

#### Whirlpool†:

FILTER 4, 4396395, UKF8001, UKF8001AXX-750, 67003523-750, UKF8001AXX-200, UKF9001AXX-100

#### Sears/Kenmore Refrigerator‡:

46-9005, 9005, 9005P, 46-9006, 469006, 9006, 9006P, 46-9992, 469992, 9992, 9992P, 469005750, 469005-750, 46-9005-750, 469006750, 469006-750, 46-9006-750, 4690065000, 46-9006-200

#### Amana\*:

WF50, OWF50, WF51, OWF51, WF50-NI300, OWF50-NI300, WF50-KNI300, WF50-NI500, OWF50-WI500, WF50-WI500, WF50-KWI500

### SPECIFICATIONS:

Flow Rate:	.5 gpm (1.89 lpm)
Operating Temperature:	33°-100°F (0.6°-38°C)
Min Operating Pressure:	30 psi (207 kPa)
Max Operating Pressure:	100 psi (689 kPa)
Life:	6 months or 300 gallons (1,136 liters)

### FILTER FEATURES:

- Better tasting water
- Improved Purity
- Effective up to 6 months or 300 gallons
- Easy DIY installation



This CW-M2 is Tested and Certified by NSF International against NSF/ANSI Standard 42 and 53, for the reduction of chlorine taste and odor, Tetrachlorethylene, Endrin, Carbon Tetrachloride, Trichlorobenzene, p-Dichlorobenzene. Refer to performance data sheet for complete list of claims.



This CW-M2 is Certified by IAPMO R&T against NSF/ANSI 42, 53, 372, 401 & CSA B483.1 for the reduction of Lead, Cyst, VOC's, Pharmaceuticals, BPA, PFOA/PFOS, Chlorine taste and odor. Refer to Performance Data Sheet for complete list of claims.

\*MAYTAG IS A REGISTERED TRADEMARK OF THE MAYTAG CORP., DELAWARE.  
†WHIRLPOOL IS A REGISTERED TRADEMARK OF WHIRLPOOL, U.S.A.  
‡KENMORE IS A REGISTERED TRADEMARK OF KCO LP, LLC.  
\*AMANA IS A REGISTERED TRADEMARK OF AMANA CORPORATION.



42188 Rio Nedo, Temecula, California 92590  
951-541-9517 • 951-296-1050 Fax  
www.tstwater.com • info@tstwater.com

