MATERIAL SAFETY DATA SHEET

DAMTITE LATEX READY MIX MASONRY WATERPROOFER 03550 - Gallon, 03555 - 5 Gallon

DAMTITE WATERPROOFING, INC

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTIFICATION

Brand Name DAMTITE LATEX READY MIX MASONRY WATERPROOFER

Formula LATEX BASE

Product Use WATERPROOFING MASONRY PAINT

MANUFACTURER

EMERGENCY TELEPHONE NUMBER

Damtite Waterproofing, Inc. 733 East Main Street Monongahela, PA 15063 Telephone (724)258-7175 CHEMTREC 1-800-424-9300

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component (Chemical & Common Name)	CAS Number	Other Exposure Limits	ACGIH OSHA TLV PEL
Styrene Acrylic Latex	25035-69-2	None	Non-Hazardous
Water	7732-18-5	None	Non-Hazardous
Calcium Carbonate	1317-65-3	None	Non-Hazardous
Aluminum Silicate	22708-90-3	None	Non-Hazardous
Titanium Dioxide	13463-67-7	None	Non-Hazardous
Hydrated Magnesium-Aluminum-			
Iron Silicate	21462-5-1	None	Non-Hazardous
Additives		None	Non-Hazardous

Percent Volatiles by volume.....58.325 Percent Organic solvent by volume.....2.461

3. PHYSICAL / CHEMICAL CHARACTERISTICS

Appearance
Odor Mild Paint Odor
Viscosity in Centipoise2,900
Vapor Pressure (mm Hg)
Vapor Density (Air =1) Lighter than Air
Boiling Point
Specific Gravity (H ₂ O =1)

4. FIRE AND EXPLOSION HAZARD DATA Flash Point: N/A Upper Explosive Limit: N/A Lower Explosive Limit: N/A EXTINGUISHING MEDIA: N/A SPECIAL FIRE FIGHTING PROCEDURES: N/A UNUSUAL FIRE AND EXPLOSION HAZARDS: N/A 5. PHYSICAL HAZARDS (REACTIVITY DATA) STABILITY (CHOOSE ONE) UNSTABLE

STABILITY	(CHOOSE ONE)	STABLE	X
CONDITION	IS TO AVOID: None		
INCOMPATI	IBILITY (MATERIALS TO AVO	DID): None	
	JS DECOMPOSITION PRODU Carbon Dioxide	JCTS: Thermal o	decomposition or burning may produce Carbon
HAZARDOU	JS POLYMERIZATION (CHOO	OSE ONE)	MAY OCCUR `_ X WILL NOT OCCUR

6. HEALTH HAZARDS

ACUTE: None

CHRONIC: None

SIGNS & SYMPTOMS OF EXPOSURE: N/A

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N/A

CHEMICAL LISTED AS CARCINOGEN OR POTENTIAL CARCINOGEN: N/A

EMERGENCY AND FIRST AID PROCEDURES:

- 1. INHALATION: Remove person to area of fresh air and get medical attention
- 2. EYES: Flush eyes for 15 minutes while lifting eyelids. Get medical attention.

EMERGENCY AND FIRST AID PROCEDURES (Continued):

- 3. SKIN: Remove contaminated clothing, wash with soap and water, apply a quality cream
- 4. INGESTION: DO NOT INDUCE VOMITING! Get medical attention.

7. SPECIAL PRECAUTION AND SPILL / LEAK PROCEDURES

SPECIAL PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: **DO NOT FREEZE!!!** Store above 40 F.

OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN!!!

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Flush heavily with water.

WASTE DISPOSAL METHODS (Consult federal, state and local regulations): Comply with Federal, State and Local Regulations.

8. SPECIAL PROTECTION INFORMATION / CONTROL MEASURES

RESPIRATORY PROTECTION (SPECIFY TYPE): None required

VENTILATION:

Local Exhaust: N/A Mechanical(General): Yes

Special: N/A OTHER: N/A

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None

WORK/HYGIENIC PRACTICES: Wash hands before eating, smoking, or using restroom. Wash clothing before wearing again.

PREPARATION INFORMATION: DATE PREPARED:October 22, 2003 REPLACES:June 1, 1999

Damtite Latex Masonry Waterproofer msdss3lx