



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 03/07/03

DAP® Latex Wood Filler by PLASTIC WOOD®

- Looks and Acts Like Real Wood
- Fills Nail Holes, Gouges & Cracks
- Stainable/Paintable
- Won't Crack or Shrink
- Easy Water Clean-Up
- Interior/Exterior Use

Packaging: 3.25 fl oz (96 mL) squeeze tubes; 4 fl oz (118 mL), 8 fl oz (236 mL), 16 fl oz (473 mL) tubs

Colors: Natural, White, Golden Oak, Red Oak, Walnut

UPC Numbers: 08140, 08142, 08144, 08146, 08148, 08111, 08114, 08116, 08118, 08135, 00527

Company Identification:

Manufacturer: DAP Inc., 2400 Boston Street, Baltimore, Maryland 21224
Usage Information: DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.
Order Information: 800-327-3339
Fax Number: 410-534-2650
Also, visit the DAP website at www.dap.com.

Product Description:

DAP Latex Wood Filler by PLASTIC WOOD® is a high-performance filler that hardens to create a surface and body that looks and acts like real wood. For use on furniture, molding and other wood surfaces. Can be sanded, cut, stained or painted. Hold nails and screws. Easy water clean-up. Interior/exterior use.

Suggested Uses:

Ideal for repairing cracks, gouges, chips, holes and other surface defects on wood surfaces such as:

- Furniture
- Molding
- Paneling
- Windows
- Doors
- Plywood

Surface Preparation & Application

- Surface must be clean, dry and free of dirt, oil and loose material. De-gloss surface if necessary for best adhesion.
- Surface, wood filler and air temperature should be above 40°F.
- If staining, test wood filler with desired stain on scrap wood before filling to ensure desired stain color.
- Squeeze Tube: Knead tube before using. Before removing cap, squeeze tube to pop out nozzle. Remove cap.
- Apply wood filler into area to be filled. Press firmly into place using a putty knife or tool.
- Avoid overspreading filler on surrounding surfaces. Overfill slightly to allow for sanding and settling. Most repairs require just one fill. Larger and deeper holes may require more than one application.

- For larger and deeper holes, apply thin layers to build up thick sections. Build fill-up slightly higher than surface to allow for sanding and settling. Allow each layer to dry before applying next layer.
- Allow to dry thoroughly before sanding: approximately 2 to 6 hours for shallow fills up to 1/8" and 36 hours for deeper fills 1/4" and over. Sand with medium sandpaper.
- May be painted with latex-based paint immediately after sanding, or after 12 hours if using an oil-based paint.
- Exterior applications must be coated with latex or oil-based paint or solid color stain.
- If wood is to be stained, stain before filling with wood filler. Select a wood filler color that most closely matches desired stain finish color. Then use stain to develop desired final finish.
- Reseal container tightly with lid/cap.
- Keep from freezing.

Physical & Chemical Characteristics:

Vehicle:	Polymer Latex Emulsion
Filler:	Inert Pigment
Volatile:	Water
Solids:	80% by weight
Odor:	Mild
Consistency:	Stiff Paste
Application Temperature Range:	Above 40°F
Drying Time:	Depending on temperature and humidity: 2 to 6 hours in shallow fills up to 1/8"; up to 36 hours in deep fills 1/4" and over.
Shelf Life:	1 Year
MSDS No.:	79200

Clean-Up:

Wipe off excess filler from surface and tools with a damp cloth before material dries. Dried wood filler must be sanded or scraped away. Reseal tightly with lid/cap after each use.

Safety:

See product label and Material Safety Data Sheet for safety information. You can request an MSD sheet by calling visiting our website at www.dap.com or calling **888-DAP-TIPS**.

Ltd. Warranty: DAP will not accept liability for more than product replacement.