



TECHNICAL DATA SHEET

8/10/2017

Alex Flex® Flexible Spackling



Product Description: **DAP® ALEX FLEX®** Flexible Spackling is a premium spackling for eliminating reoccurring cracks in drywall. Its ready-to-use smooth, white formula spreads easily for fast, professional repairs. ALEX FLEX® Spackling sands effortlessly and can be painted. It does not flash or gloss low sheen/flat paint. It can be used for interior or exterior applications.



Won't Shrink or Crack



Sandable



Paintable

Featured & Benefits:

- Flexible – Eliminate Reoccurring Cracks
- Sandable
- Paintable
- Won't Sink or Shrink
- Interior/Exterior use

Suggested Uses:

Ideal for filling holes, cracks, dents and defects on:

- Drywall
- Plaster
- Wood

Available In:

SKU #	Description	Size	Package Type	Case Pack	Color
7079818742	Alex Flex Flexible Spackling	16 Fl. Oz. (473 mL)	Tub	12 PK	White
7079818743	Alex Flex Flexible Spackling	32 Fl. Oz (946 mL)	Tub	8 PK	White



TECHNICAL DATA SHEET

Surface Preparation & Application Instructions:

- Surface must be clean, dry and free of foreign material.
- Stir thoroughly before use.
- Apply with a clean putty knife.
- For a smoother finish, dip putty knife in water and lightly smooth spackling.
- One application is usually sufficient for small repairs. For repairs deeper than 1/8", apply two or more layers allowing spackling to dry between applications.
- May be sanded or painted in 1 to 5 hours depending on temperature, humidity and depth of fill. Wet sanding is recommended to avoid generation of dust.
- Clean tools immediately with water.

For Best Results:

- Do not apply when temperatures are below 50°F.
- Do not apply outside if rain is expected within 24 hours.
- Do not use on floors or as a caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- **DO NOT USE AS A SKIM COAT.**
- For exterior applications, always topcoat with a quality paint.
- If a textured finish is desired, add clean sand to spackling compound prior to application.
- Do not use for tuck pointing applications on brick.
- For larger areas to be patched on bare concrete, use a latex fortified Portland cement-based dry mix.

Typical Physical & Chemical Characteristics:

Consistency	Thick Paste
Vehicle	Latex Polymer
Volatile	Water
Filler	Inert Filler
Odor	Mild
Weight/Gallon	13.5 pounds
Solids	74%
Application Temperature	50°F minimum
Service Temperature	0°F to 150°F
Shelf Life	1 year
Freezing	Freeze/thaw stable 5 cycles at 0°F
Dry Time	1 to 5 hours depending on temperature, humidity and depth of fill
SDS Number	00017078001



TECHNICAL DATA SHEET

Cleanup & Storage Recommendations:

- Wash tools immediately after use with water.
- Dried material must be removed by scraping or sanding.
- Be sure container lid/cap is closed and tightly sealed.
- Store in a cool, dry place.

Safety Information:

Contains: Crystalline silica. Sanding of this product may generate dust. Inhalation of dust may cause adverse pulmonary and respiratory effects. May cause eye and skin irritation. Do not breathe dust. Use only with adequate ventilation. Ensure fresh air entry. Wet sanding is recommended to reduce dust exposure. When sanding, wear a NIOSH-approved dust mask. Harmful if swallowed. Do not ingest. Avoid contact with eyes, skin and clothing. Wear gloves and safety glasses. Close container after use. Wash thoroughly after handling.

FIRST AID: SKIN: Wash thoroughly. EYE: Immediately flood with large quantities of water. INHALATION: Remove to fresh air. INGESTION: DO NOT INDUCE VOMITING. Get medical attention if complications arise from any exposure. **For emergencies, call your poison control center at 1-800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com.**

KEEP OUT OF REACH OF CHILDREN.

Warranty Information:

- If product fails to perform as directed, within one year from the date of purchase, call 1-888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund.
- DAP will not be responsible for incidental or consequential damages.

Disclaimer:

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Purchasers should test the products to determine acceptable quality and suitability for their own intended use.

Company Information:

Manufacturer: DAP Products Inc., Baltimore, MD 21224.

Usage Information: Call 888-DAP-TIPS or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339

Fax Number: 410-558-1068

Also visit the DAP website at dap.com.