



2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 1/25/2016

DAP[®] KWIK SEAL PLUS[®] Siliconized Adhesive Sealant with MICROBAN[®] Antimicrobial Product Protection

- Microban[®] Antimicrobial Product Protection fights the growth of stain & odor-causing bacteria, mold & mildew on the sealant
- 100% waterproof
- Crack proof
- Paintable
- Easy water clean-up & low odor
- Interior

Packaging: 5.5 fluid ounces (162 mL) and 10.1 fluid ounces (300 mL)
Color: White, Biscuit
UPC Numbers: 70798 18510, 70798 18519, 70798 18526, 70798 18539, 70798 07045, 70798 07047

Company Identification:

Manufacturer: DAP Products Inc., 2400 Boston St., Baltimore, Maryland 21224
Usage Information: Call 1-888-DAP-TIPS or visit dap.com & click on “Ask the Expert”
Order Information: 800-327-3339
Fax Number: 410-558-1068
Also, visit the DAP website at www.dap.com

Product Description:

DAP[®] KWIK SEAL PLUS[®] KITCHEN & BATH SILICONIZED ADHESIVE SEALANT contains Microban[®] Antimicrobial Product Protection to fight the growth of stain and odor-causing bacteria, mold and mildew on the sealant. The advanced Microban[®] Protection neutralizes bacterial and fungal growth where it lives and breeds. This means the sealant is easier to keep clean and stays cleaner longer. This specially formulated siliconized adhesive sealant provides excellent adhesion and flexibility for a 100% waterproof and crackproof seal around tubs, sinks, showers, countertops and fixtures. KWIK SEAL PLUS[®] is easy to apply and tool, paintable, low in odor and cleans up easily with water. Interior use.

Suggested Uses:

Ideal for caulking & sealing:

- Tubs
- Sinks
- Backsplashes
- Showers
- Countertops
- Toilets
- Fixtures
- Loose Tile Repair
- Cracks and Joints

Adheres To:

- *Ceramic/Porcelain*
- *Glass*
- *Most Plastics*
- *Granite, Cultured Marble & Natural Stone*
- *Wood*
- *Metal*
- *Drywall*
- *Fiberglass*
- *Painted Surfaces*

Performance Characteristics:

- Microban® Antimicrobial Product Protection fights the growth of stain & odor-causing bacteria, mold & mildew on the sealant
- Some cleaning products may affect the performance of this product
- 100% waterproof
- Crack proof
- Paintable
- Easy water clean-up & low odor

Surface Preparation & Application:

1. Surface must be clean, dry and free of all old sealant, dirt, dust, debris and grease. Rubbing alcohol is recommended for removing soap film and soil.
2. Remove cap (from tube). Cut nozzle at a 45° angle to desired bead size.
3. If using the cartridge, load into caulk gun.
4. Fill gap with sealant, pushing sealant ahead of nozzle.
5. For a neat finish, smooth bead of caulk immediately with a finishing tool.
6. Allow sealant to dry at least 2 hours (longer in cool or humid conditions) before painting with latex or oil-based paints.
7. Wait 24 hours before exposing to water.
8. Clean up excess uncured sealant with damp sponge before it skins over. Scrape or cut away excess cured sealant. Clean hands and tools with warm, soapy water.
9. Reseal tube/cartridge for future use.

For Best Results:

- Apply in temperatures above 40°F.
- Not for continuous underwater use, high temperature surfaces or surface defects.
- Joint width should not exceed 3/8". If joint depth exceeds 3/8", use foam backer rod.
- Allow sealant to dry at least 2 hours (longer in cool or humid conditions) before painting with latex or oil-based paints.
- Wait 24 hours before exposing to water.
- Store product away from extreme heat or cold.

Typical Physical & Chemical Characteristics:

Vehicle:	Latex polymer
Solids:	71% by weight
Filler:	Calcium carbonate
Density:	10.6 lbs/gallon
Specific Gravity:	1.27
Tooling Time:	10 minutes
Tack Free Time:	15 minutes
Paintable:	Yes
Odor:	Very mild
Consistency:	Smooth and creamy
Volatile:	Water
Flash Point:	None
Temperature Service Range:	-20° F to 150°F
Temperature Application Range:	40°F to 100°F
Freeze Thaw Stability:	Passes 5 Cycles

Applications: Interior
Shelf Life: 12 months
Coverage: 5.5 fluid ounces: 30 linear feet at a 3/16" diameter bead or two average size bathtubs
10.1 fluid ounces: 55 linear feet or four average size bathtubs
SDS No.: 00010025001

Clean Up & Storage:

Clean up excess uncured caulk with a damp cloth/sponge before it skins over (approximately 15 minutes). Excess cured caulk must be cut or scraped away. Clean hands and tools with warm, soapy water. Store in a cool, dry place away from extreme heat or cold.

Safety:

Caution! Contains white mineral oil. Use in well-ventilated area. Do not get in eye or on skin. Use gloves and safety glasses. **Keep out of reach of children. Do not take internally. Warning:** This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. In an emergency, call your poison control center at 1(800)222-1222. See product label or Safety Data Sheet (SDS) for additional safety information. You can obtain an SDS sheet by visiting dap.com or by calling 1-888-DAP-TIPS.

Crack Proof Guarantee:

DAP warrants that this product will not mildew, crack, peel or separate when used as directed within one year of purchase. If product fails, return container and sales receipt to DAP Products Inc., TCS, 2400 Boston St., Baltimore, MD 21224 for replacement product or sales price refund. DAP will not be liable for incidental or consequential damages.

MICROBAN is a registered trademark of Microban Products Company.