



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224

Phone: 410-675-2100 or 800-543-3840

Revised: 4/26/2018

DAP® PLASTIC WOOD® All-Purpose Latex Wood Filler

- Easy-to-use, latex-based formula
- Water clean-up & low odor
- Looks and acts like real wood
- Can be sanded, planed, cut, drilled, screwed & nailed
- Shrink, crack & crumble resistant
- Thick, knife-grade formula can be molded & sculpted – ideal for corners and vertical surfaces
- Easy handling – spreads smoothly and evenly
- Stainable & paintable
- Strong nail & screw anchoring
- Interior/Exterior use

Packaging: Net Weight 3oz (85g), 5.5oz. (156g), 6oz (170g), 8oz. (226g), 16oz. (453g), 32oz (907g)

Colors: Natural, Golden Oak, Red Oak, Walnut, White

UPC Numbers: 70798 00580, 70798 00581, 70798 00582, 70798 00583, 70798 00584, 70798 00585, 70798 08135, 70798 00529, 70798 00525

Company Identification:

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call 1-888-DAP-TIPS or visit dap.com and click on “Ask the Expert”

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com

Product Description:

DAP® PLASTIC WOOD® All-Purpose Wood Filler is a high quality, latex-based wood filler formulated to create a surface and body that looks and acts like real wood. It can be used to repair cracks, gouges, holes and other surface defects on furniture, woodwork, molding, cabinets, paneling, plywood, windows, doors and painted surfaces. This easy-to-use filler is low in odor and cleans up with water. The thick, knife-grade formula can be molded and sculpted making it ideal for corners, vertical and unsupported surfaces. It offers easy handling by spreading smoothly and evenly. When dry, DAP® PLASTIC WOOD® All Purpose Wood Filler can be sanded, cut, planed, drilled, nailed or screwed, stained and painted. It is shrink, crack and crumble resistant and provides strong nail and screw anchoring. Interior /exterior use.

Suggested Uses:

- For filling nail holes, gouges, cracks, scratches & imperfections on furniture, woodwork, molding, cabinets, paneling, plywood, windows, doors and painted surfaces.

Surface Preparation & Application

1. Surface must be clean, dry and free of dirt, oil and loose material. De-gloss surface if necessary for best adhesion.
2. Surface, wood filler and air temperature should be above 40°F.
3. If staining, test wood filler with desired stain on scrap wood before filling to ensure desired stain color. Stain before filling with wood filler, then use stain to develop desired final finish.
4. Stir product with putty knife before application. For squeeze tubes, knead the tube prior to cutting and extruding material.
5. Apply wood filler into area to be filled. Press firmly into place using a putty knife or tool.
6. Avoid overspreading filler on surrounding surfaces. Overfill slightly to allow for sanding and settling. Most repairs require just one fill. Larger and deeper holes may require more than one application.
7. For larger and deeper holes, apply thin layers to build up thick sections. Allow wood filler to dry before applying next layer.
8. Allow to dry thoroughly before sanding: approximately 3 to 6 hours for shallow fills up to 1/8" and 36 hours for deeper fills 1/4" and over. Sand with medium sandpaper.
9. May be painted with latex-based paint immediately after sanding, or after 12 hours if using an oil-based paint.
10. Exterior applications must be coated with latex or oil-based paint or solid color stain.
11. Reseal container tightly with lid.
12. Keep from freezing.

Typical Physical & Chemical Characteristics:

Vehicle:	Latex Polymer
Filler:	Inert Pigment
Volatile:	Water
Solids:	78.9% by weight
Odor:	Mild
Consistency:	Stiff Paste
Application Temperature Range:	Above 40°F
Drying Time:	Depending on temperature and humidity: 3 to 6 hours in shallow fills up to 1/8"; up to 36 hours in deep fills 1/4" and over.
Shelf Life:	12 Months
SDS No.:	00079200001

Clean-Up & Storage:

Wipe off excess filler from surface and tools with a damp cloth before material dries. Dried wood filler must be sanded or scraped away. Reseal tightly with lid after each use. Store in a cool, dry place away from extreme heat or cold

Safety:

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by calling 1-888-DAP-TIPS or visiting our website at dap.com.

Warranty Information:

If product fails to perform when used as directed within one year of date of purchase, call 1-888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP will not be responsible for incidental or consequential damages.