



TECHNICAL DATA SHEET

8/11/2017



DryDex® Spackling

Product Description: **DAP® DryDex® Spackling** provides a unique dry time color indicator that verifies when the patched surface is dry and ready to be sanded and painted, thus providing a smoother finished surface in a shortened amount of time. **DAP® DryDex® Spackling** may be used to fill holes and cracks in surfaces such as drywall, plaster, wood, brick and stone. Its ready-to-use formula spreads easily for fast, professional repairs that will not crack, crumble or flake. DryDex® dries hard, sands easily and can be painted.



When Ready to Sand & Paint



No Priming Required



Won't Shrink or Crack

Featured & Benefits:

- America's #1 Seller
- Dry Time Indicator – Goes on Pink Dries White
- Won't Sink or Shrink
- Eliminate Errors
- Interior/Exterior use

Suggested Uses:

Ideal for filling holes, cracks, dents and defects on:

- Drywall
- Plaster
- Wood
- Stone
- Brick

Available In:

SKU #	Description	Size	Package Type	Case Pack	Color
7079812323	DryDex Spackling	5.5 Fl. Oz. (162 mL)	Tube	6 PK	Pink to White
7079812343	DryDex Spackling	5.5 Fl. Oz. (162 mL)	Tube	6 PK	Pink to White
7079812337	DryDex Spackling	5.5 Fl. Oz. (162 mL)	Tube	12 PK	Pink to White
7079812387	DryDex Spackling	5.5 Fl. Oz. (162 mL)	Tube	15 PK	Pink to White
7079812328	DryDex Spackling	8 Fl. Oz (236 mL)	Tub	12 PK	Pink to White
7079812326	DryDex Spackling	8 Fl. Oz (236 mL)	Tub	24 PK	Pink to White
7079812348	DryDex Spackling	16 Fl. Oz (473 mL)	Tub	18 PK	Pink to White
7079812344	DryDex Spackling	32 Fl. Oz. (946 mL)	Tub	4 PK	Pink to White
7079812330	DryDex Spackling	32 Fl. Oz. (946 mL)	Tub	6 PK	Pink to White
7079812327	DryDex Spackling	32 Fl. Oz. (946 mL)	Tub	8 PK	Pink to White
7079812347	DryDex Spackling	128 Fl. Oz. (3.78 L)	Tub	2 PK	Pink to White



TECHNICAL DATA SHEET

Surface Preparation & Application Instructions:

- Surface must be clean, dry and free of foreign material.
- Stir thoroughly before use.
(When using the 5.5 oz squeeze tube, knead tube prior to use. Remove cap and cut nozzle to desired opening size.)
- Apply with a clean putty knife.
- One application is usually sufficient for small repairs.
For repairs deeper than 1/8", apply two or more layers allowing spackling to dry between applications.
- For a smoother finish, dip putty knife in water and lightly smooth spackling.
- Spackling will change color to white when surface can accept a second application or is ready to be painted or sanded in 1 to 5 hours.
Wet sanding is recommended to avoid generation of dust.
- Clean tools immediately with water.

NOTE: To retain the effectiveness of the dry time indicator, keep the container tightly closed after use.

For Best Results:

- Do not apply when temperatures are below 50°F.
- Do not apply outside if rain is expected within 24 hours.
- Do not use on floors or as a caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- **DO NOT USE AS A SKIM COAT.**
- For exterior applications, always topcoat with a good quality exterior grade paint.
- If a textured finish is desired, add clean sand to spackling compound prior to application.
- Do not use for tuck pointing applications on brick
- For larger areas to be patched on bare concrete, use a latex fortified Portland cement-based dry mix.

Typical Physical & Chemical Characteristics:

Consistency	Paste
Vehicle	Latex Polymer
Volatile	Water
Filler	Inert Filler
Odor	Mild
Weight/Gallon	15.7 pounds
Solids	77% by weight
Application Temperature	50°F or higher
Service Temperature	0°F to 150°F
Shelf Life	1 year
Freezing	Freeze/thaw stable 5 cycles at 0°F
Dry Time	1 to 5 hours depending on temperature, humidity and depth of fill
SDS Number	00010420001, 00010421001, 00010422605



TECHNICAL DATA SHEET

Cleanup & Storage Recommendations:

- Wash tools immediately after use with water.
- Dried material must be removed by scraping or sanding.
- Be sure container lid/cap is closed and tightly sealed.
- Store in a cool, dry place.

Safety Information:

Contains: Crystalline silica. Sanding of this product may generate dust. Inhalation of dust may cause adverse pulmonary and respiratory effects. May cause eye and skin irritation. Do not breathe dust. Use only with adequate ventilation. Ensure fresh air entry. Wet sanding is recommended to reduce dust exposure. When sanding, wear a NIOSH-approved dust mask. Follow dust mask manufacturer's directions for use. Keep exposure below OSHA permissible exposure limits. Harmful if swallowed. Do not ingest. Avoid contact with eyes, skin and clothing. Wear gloves and safety glasses. Close container after use. Wash thoroughly after handling.

FIRST AID: SKIN: Wash thoroughly. EYE: Immediately flood with large quantities of water. INHALATION: Remove to fresh air. INGESTION: DO NOT INDUCE VOMITING. Get medical attention if complications arise from any exposure. **For emergencies**, call your poison control center at 1-800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your **supplier or visit dap.com**.

KEEP OUT OF REACH OF CHILDREN.

Warranty Information:

- If product fails to perform as directed, within one year from the date of purchase, call 1-888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund.
- DAP will not be responsible for incidental or consequential damages.

Disclaimer:

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Purchasers should test the products to determine acceptable quality and suitability for their own intended use.

Company Information:

Manufacturer: DAP Products Inc., Baltimore, MD 21224.

Usage Information: Call 888-DAP-TIPS or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339

Fax Number: 410-558-1068

Also visit the DAP website at dap.com.