



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 7/22/05

DAP®/Bondex® Patching Plaster

- Ready to use formula
- For everyday household repairs to plaster and drywall
- Dries hard with minimal shrinkage
- Interior use

Packaging: 1 pint tub, 1 quart tub, 1 gallon tub, 946 ml tub
Color: White
UPC Numbers: 52082, 52084, 52290, 52086

Company Identification:

Manufacturer: DAP Inc., 2400 Boston Street, Baltimore, Maryland 21224
Usage Information: DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.
Order Information: 800-327-3339
Fax Number: 410-534-2650
Also, visit the DAP website at www.dap.com.

Product Description:

DAP®/Bondex® Patching Plaster is a ready mixed, easy-to-use general purpose patching material used to fill holes and cracks and treat surfaces prior to painting. The product has a smooth working consistency, dries quickly, is non-shrinking and sands easily. Recommended for interior use only.

Suggested Uses:

Ideal for everyday household repairs to plaster and drywall.

Surface Preparation & Application:

- Make sure surface to be repaired is clean and free of dust and particles. Use sandpaper to dull glossy surfaces before repairing.
- Stir thoroughly before use. Apply with a clean putty knife.
- For a smoother finish, dip putty knife in water and lightly smooth plaster.
- Widen cracks in plaster with a putty knife or utility knife to at least 1/4 inch in width and brush away loose particles.
- Patching Plaster can be sanded or painted 1 to 5 hours after application depending on temperature, humidity and depth of fill. Wet sanding is recommended to avoid generation of dust.
- For repairs deeper than 1/4 inch: Apply two or more layers allowing to dry between applications. Apply first coat to within a quarter-inch of surface and let set four to six hours. Complete patch on the second coat and smooth. Allow this coat to dry at least 24 hours before painting. Drying times may vary depending on room temperature.
- Clean tools immediately with water.

Physical & Chemical Characteristics:

Consistency:	Heavy bodied paste
Vehicle:	Latex Emulsion
Volatile:	Water
Filler:	Various Inerts
Odor:	Mild
Weight/Gallon:	14.3-14.5 lbs
Solids:	66-68%
Application Temperature:	50°F Minimum
Service Temperature:	-20°F to 120°F
Shelf Life:	1 Year
Freezing:	Protect from freezing
Drying Time:	1 to 5 hours depending on temperature, relative humidity and depth of fill
Painting:	1 to 5 hours depending on temperature, relative humidity and depth of fill
MSDS:	000 79006 001

Clean Up:

Wash tools immediately after use with water. Be sure container lid is closed and tightly sealed. Store in a cool, dry place.

Safety:

See product label and Material Safety Data Sheet (MSDS) for safety information. You can request an MSDS by visiting our website at www.dap.com or by calling 888-DAP-TIPS.

Warranty Information:

If you are not satisfied with this product's performance when used as directed, return used container and sales receipt to DAP Inc., Technical Customer Service, 2400 Boston Street, Suite 200, Baltimore, MD 21224 for product replacement or sales price refund. DAP will not be liable for incidental or consequential damages.