



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 10/26/10

DAP® Wallboard Joint Compound - Ready to Use

- For smooth finishing of gypsum panel joints
- Professional grade
- Sands easily
- Interior use

Packaging: 3 lb. tub, 12 lb. tub
Color: White
UPC Numbers: 7079810100, 7079810102

Company Identification:

Manufacturer: DAP Products Inc., 2400 Boston St., Ste. 200, Baltimore, Maryland 21224
Usage Information: Call 1-888-DAP-TIPS or visit dap.com & click on "Ask the Expert"
Order Information: 800-327-3339
Fax Number: 410-534-2650

Product Description:

DAP® Wallboard Joint Compound is a ready to use joint compound for smooth, high quality finishing of gypsum panel joints. It is preferred by professionals for embedding reinforcing tape, finishing gypsum panel joints, nailheads and metal corner beads. DAP® Wallboard Joint Compound has minimal shrinkage and is crack resistant. It is ideal for textured finishes.

Suggested Uses:

For smooth, high quality finishing of:

- Gypsum panel joints
- Nailheads
- Metal corner beads

Surface Preparation & Application:

1. Prepare surface by recessing nails into panels 1/32".
2. Fill the space between panels with DAP® Wallboard Joint Compound.
3. Center wallboard joint tape over joint and press into fresh compound with a 5" application knife.
4. Remove excess and cover embedded tape with a thin layer of compound. Apply compound to all nailheads and spread smooth with long strokes parallel to joint.
5. After compound dries, wet sand application with a damp sponge.
6. Apply a second coat of joint compound with a 10" knife along joints and over nailheads, smoothing out 2" beyond first coat. Wet sand with a damp sponge again after the compound has dried.
7. Apply a third coat, smoothing out 2" beyond second coat. Let dry and wet sand application again.

8. To finish inside corners, apply joint compound to both sides of corner, fold tape along center crease, and press into position. Embed tape with a 5" knife and apply a thin coat of compound over tape. After compound has dried, wet sand with a damp sponge and apply a second coat of compound over one side only. Let dry and then cover the other side.
9. To finish outside corners, fasten metal corner bead and apply first coat of compound smoothing onto panel surface 4" to 6". Allow compound to dry and wet sand application. Apply 2 more coats in same manner.
10. For a textured finish, apply ample amount of DAP® Wallboard Joint Compound with a paintbrush or roller. Texture surface immediately using paint rollers, a sponge, stiff bristled brush or even crumpled paper, depending on the desired effect. Allow the compound to dry thoroughly before decorating.

For Best Results:

- *Allow approximately 24 hours between applications before decorating*
- *Allow compound to dry before sanding.*
- *Wiping while wet may leave unwanted smears. Wet sand uneven areas with a damp sponge after joint compound has dried. Wet sanding is recommended to prevent generating airborne dust.*

Physical & Chemical Characteristics:

Vehicle:	Latex Emulsion
Drying Time:	Approximately 8 to 24 hours. <i>Dry time varies with temperature, humidity, and depth of fill.</i>
Temperature Service Range:	-20° F to 120° F
Minimum Application Temperature:	50°F
Coverage:	3 lbs. finishes approximately 8-10 linear feet. <i>For texturing, 3 lbs.covers approximately 10-12 square feet.</i> 12 lbs. finishes approx. 30-40 linear feet. <i>For texturing, 12 lbs.covers approximately 40-50 square feet.</i>
Odor:	Mild
Consistency:	Creamy, workable knife consistency
Volatile:	Water
Filler:	Calcium Carbonate
Solids:	68 ± 0.6%
Weight per gallon:	14.3 ± 0.15 lbs.
Freeze/Thaw Stability:	Protect from freezing
Shelf Life:	6 Months
MSDS No.:	00070288001

Clean Up:

Wash tools immediately after use with soapy water. Be sure container is closed and tightly sealed. Store in a cool, dry place.

Safety:

See product label and Material Safety Data Sheet (MSDS) for safety information. You can request an MSDS by visiting our website at dap.com or by calling 1-888-DAP-TIPS.

Satisfaction Guaranteed:

If product fails to perform when used as directed, return the sales receipt and used container to DAP Products Inc., Technical Customer Service, 2400 Boston St., Suite 200, Baltimore, MD 21224 for replacement product or sales price refund. DAP will not be liable for incidental or consequential damages.

An  Company