



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 4/21/2017

DAP® SEAL 'N PEEL® All Season Removable Weatherstrip Sealant

- Provides temporary, removable seal
- Forms a tight, temporary seal
- Seals out drafts to save energy
- Peels away easily when no longer needed
- Interior/exterior use

Packaging: 10.1 fl. oz. (300 mL) cartridge
Color: Clear
UPC Number: 70798 18324 7

Company Identification:

Manufactured for: DAP Products Inc., 2400 Boston St., Ste. 200, Baltimore, Maryland 21224
Usage Information: Call 1-888-DAP-TIPS or visit dap.com & click on "Ask the Expert"
Order Information: 800-327-3339
Fax Number: 410-534-2650
Also, visit the DAP website at www.dap.com.

Product Description:

DAP® SEAL 'N PEEL® Removable Weatherstrip Sealant is formulated for use as a seasonal weatherstripping product. It provides a watertight, weatherproof and fast drying seal against air and moisture, keeping homes warmer in winter, cooler in summer, while also reducing energy bills. Use it to seal drafty windows, seasonally used doors, around air conditioners, vents or fans. Then easily peel it away when no longer needed. Interior and exterior use.

Suggested Uses:

Ideal for sealing:

- *Window and door frames*
- *Patio doors*
- *Vents*
- *Air conditioners*
- *Fans*
- *Louvers*

Adheres to:

- *Glass*
- *Wood*
- *Ceramic/Porcelain*
- *Metal*
- *Aluminum*
- *Vinyl*

Surface Preparation & Application:

1. Remove any loose or foreign material.
2. Clean & dry surface. The surfaces must be free of creosote, oil, grease, wax, silicone, silicone-based product, asphalt or bitumen-based product, and any material soluble in solvents.
3. Trim nozzle to desired bead size. Cut the nozzle at a right angle (90°) slightly narrower than the width of the gap.
4. Puncture inner foil seal.
5. Load cartridge into caulking gun.
6. Fill gaps with sealant. Large gaps may require several layers.
7. **Do not shape or tool the bead.**
8. Peel away excess sealant when dry. Product left in place for more than one year may be more difficult to remove, Product may peel or damage wallpaper, uncured or degraded coatings.

DO NOT SEAL FIRE EXITS. CONSULT LOCAL FIRE OR CODE OFFICIAL WITH QUESTIONS ABOUT FIRE EXITS.

THIS PRODUCT HAS A VERY STRONG ODOR. ENSURE PROPER VENTILATION IS USED WHEN PRODUCT IS APPLIED AND CURING.

FOR BEST RESULTS:

- Apply in temperatures above 40°F.
- Store below 80°F in a cool, dry place away from extreme heat or cold.
- Not for continuous underwater use.
- Do not use on freshly painted surfaces. Product may peel or damage wallpaper, uncured or degraded coatings.
- Do not use on insulating panels or plastic materials which can be damaged by solvents.
- New metal and solvent resistant oily surfaces must be washed with acetone and dried.
- For unusual substrates, perform a test for adhesion prior to use.
- For gaps wider than ¼”, backer rod should be used.
- The sealant should come into contact with each of the surfaces on a width of at least 1/8”.
- **If applied indoors, the area must be ventilated during application and drying time.**

Typical Physical & Chemical Characteristics:

Tooling Time:	Do not tool or shape bead
Tack Free Time:	10 Minutes
Service Expectancy:	Temporary - 12 months maximum
Paintability:	N/A
Odor:	Strong Solvent
Consistency:	Smooth, gunnable paste
Polymer:	Synthetic rubber
Volatile:	Aliphatic and aromatic solvents
Flash Point:	39°F
Filler:	N/A
Density:	Approximately 7 lbs./gallon
Solids:	Approximately 50% by weight
VOC, less water and less exempts:	400 g/L (47%)
Temperature Service Range:	-20°F to 122°F
Temperature Application Range:	40°F to 100°F
Freeze/Thaw Stability:	Freeze thaw stable
Shelf Life:	12 months from date of manufacture when stored in unopened

Coverage: container below 80°F
55 linear ft. at a 3/16" diameter bead size or 4 average size windows
SDS No.: 00077136001

Clean-Up & Storage:

While product is still wet, use a solvent-moistened cloth. After the product has dried, excess material may be easily peeled away. Do not use solvent to clean hands. Reseal opened cartridge for future use. Store below 80°F in a cool, dry place away from extreme heat or cold.

Safety:

See product label and Safety Data Sheet (SDS) for health and safety information. For an SDS, visit www.dap.com.

WARRANTY: DAP will provide replacement product or refund sales price if product fails to perform when used as directed, during the shelf life period. Call 1-888-DAP-TIPS, with your sales receipt and product container available, to arrange for warranty fulfillment. DAP is not liable for incidental or consequential damages.