



**DYNAGRIP®**  
THE GRIP THAT OUTPERFORMS™

# Technical Data Bulletin

## ALL PURPOSE

### Construction Adhesive

DAP® DYNAGRIP® ALL PURPOSE construction adhesive is a premium grade adhesive ideal for paneling, interior remodeling, and other interior projects. DYNAGRIP® ALL PURPOSE adhesive delivers a strong permanent bond and excellent adhesion on common building materials. Offering an easy water clean up and excellent instant grab, this adhesive delivers the perfect combination of convenience and performance for interior projects.



**MULTI-MATERIAL**



**INSTANT GRAB**



**STRONG PERMANENT BOND**

#### Recommended For:

- Tub Surround Installation
- Foam Insulation Panels
- Drywall & Decorative Paneling Installations
- Molding & Decorative Trim
- Cove Base & Base Board Installation

#### Adheres To:

- ABS
- Concrete
- Cove Base
- Ceramic Tiles
- Drywall
- Dimensional Lumber
- Foamboard
- FRP
- Masonry
- OSB
- Polystyrene
- Plywood

#### Not Recommended For:

- Bonding two non-porous materials
- Constant water exposure
- Exterior use
- Flooring applications
- Mirror installation
- Subfloor or deck installation

DAP Products, Inc.  
2400 Boston Street, Suite 200  
Baltimore, MD 21224  
Phone: 410-675-2100  
REV: 11/01/2016

| SKU #      | SIZE   |
|------------|--------|
| 7079827500 | 5oz    |
| 7079827501 | 10.3oz |
| 7079827502 | 28oz   |



**CAUTION!**  
Read back panel carefully for cautions.  
**¡PRECAUCIÓN!** Lea cuidadosamente el panel posterior sobre otras precauciones.  
10.3 FL. OZ. (305 mL)

**CAUTION!**  
Read back panel carefully for cautions.  
**¡PRECAUCIÓN!** Lea cuidadosamente el panel posterior sobre otras precauciones.  
28 FL. OZ. (828 mL)



**DYNAGRIP**<sup>®</sup>  
THE GRIP THAT OUTPERFORMS™

## ALL PURPOSE

### Product Features

- Easy Water Clean Up
- Low Odor
- Easy To Gun
- VOC Compliant

### Directions

**FOR BEST RESULTS:** Apply in temperatures above 40°F. Keep adhesive above 40°F for easier gunning. For square surfaces apply around perimeter and "X" shaped bead. For long surfaces use "S" shaped bead. Press firmly into place. One surface must be porous. Store away from extreme heat or cold.

**INSTRUCTIONS:** 1. Surfaces must be clean, structurally sound and free of debris. 2. Precut & fit materials before applying adhesive. 3. Trim nozzle to desired bead size ¼" bead recommended for most applications. 4. Puncture inner foil seal. 5. Load into applicator gun. 6. Apply a continuous bead to surface. 7. Within 20 minutes, position & press substrates firmly into place. 8. Certain applications may require mechanical fasteners. 9. Allow to dry for 24 hours.

**CLEAN UP:** Uncured adhesive: wash away with warm water and soap. Cured adhesive: must be cut or scraped away.

**USAGE INFORMATION:** For usage information or warranty information, please contact DAP Technical Customer Service at 888-DAP-TIPS or visit [dap.com](http://dap.com) & click on "Ask the Expert".

Contains: Urea.

May be harmful if swallowed or in contact with skin. May cause eye, skin, nose, throat and respiratory tract irritation. Avoid breathing vapors. Use only with adequate ventilation. Ensure fresh air entry. Avoid contact with eyes, skin and clothing. Wear rubber gloves and eye protection with side shields.

**WARNING:** This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

**FIRST AID:** SKIN CONTACT: Wash skin thoroughly with soap and water. EYE CONTACT: Immediately flood with large quantities of water. INHALATION: Remove to fresh air. INGESTION: **DO NOT INDUCE VOMITING.** Get medical attention immediately if complications arise from exposure. **FOR EMERGENCIES,** call poison control center at 1-800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit [dap.com](http://dap.com).

**KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.**

### TYPICAL PHYSICAL PROPERTIES

- Type: Acrylic Latex
- Application Temperature: 40°F to 100°F
- Service Temperature: 0°F to 140°F
- Bead Color: Off-White
- Solids: 72%
- Shelf Life: 18 months
- Skin Time: 20 minutes
- Cure Time: 7 days
- Coverage:
  - 10.3oz: ¼" bead yields 32 linear ft., 3/8" bead yields 14 linear ft.
  - 28oz: ¼" bead yields 86 linear ft., 3/8" bead yields 38 linear ft.
- Specifications:
  - ASTM C557 Meets or Exceeds.
- Calif. ARB VOC <0.5% Wt/Wt
- VOC Content: VOC less Water, less Exempt Solvent: <15 g/L