



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® ALEX FAST DRY® Acrylic Latex Caulk Plus Silicone

PRODUCT DESCRIPTION

DAP® ALEX FAST DRY® Acrylic Latex Caulk Plus Silicone is specifically formulated to meet the demanding needs of Pro Painters & deliver outstanding paint finish results. It can be brush painted in 20 minutes after application or spray painted immediately, so the job gets finished faster. This durable, flexible caulk won't crack or discolour paint & doesn't pick up dirt. It has outstanding adhesion to a wide variety of surfaces, provides a waterproof seal & cured caulk is mould & mildew resistant. Smooth & easy application. Can be used indoors or out and exceeds ASTM Specification C834.



PACKAGING	COLOR	UPC
12 x 300 ml (Contractor Pack)	WHITE	7079874851
300 ml	WHITE	7079878425
162 ml	WHITE	7079874856

KEY FEATURES & BENEFITS

- Paintable in 20 Minutes
- Spray Paint Immediately
- Pro Painter Formula
- Crack Resistant
- Reduced Dirt Pick-Up
- Won't Shine Through Paint
- Waterproof Seal
- Easy Water Clean-Up
- Interior/Exterior

PERFORMANCE CHARACTERISTICS

- Exceeds ASTM Spec. C834
- Paintable in 20 minutes with brush or roller, or spray painted immediately
- Resists cracking and chalking



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

SUGGESTED USES

Ideal for caulking and sealing:

- Window & door frames
- Baseboards & molding
- Corner joints
- Siding & trim
- Vents, ducts, pipes

Adheres To:

- Wood
- Brick
- Metal
- Drywall & plaster
- Painted surfaces
- Glass
- Concrete, masonry & stone
- Most common building materials

FOR BEST RESULTS

- Apply in temperature above 4°C (40°F)
- Do not apply when rain or freezing temperatures are forecasted before full cure can occur.
- Do not use below waterline or for marine or automotive applications.
- Do not use for filling butt joints, surface defects, for tuck-pointing or expansion joints.
- Joint size should not exceed 3/8" wide x 3/8" deep. If joint depth exceeds 3/8", use backer rod material.
- Store away from extreme heat or cold.

KEY FEATURES & BENEFITS

Surface Preparation & Application:

1. Surface must be clean, dry and free of old caulk, dirt, dust, debris and grease.
2. If using cartridge: trim the nozzle at 45° angle to desired bead size and load cartridge into caulking gun. If using squeezing tube, remove cap and trim nozzle at 45° angle to desired bead size.
3. Fill the gap with caulk, pushing caulk ahead of nozzle.
4. If necessary, smooth or tool the bead with a caulk finishing tool.
5. Clean up excess uncured caulk with a damp sponge before it skins over. Cured caulk must be cut or scraped away.
6. Allow 20 minutes for skin to form prior to painting with brush or roller. Can be spray painted immediately. Allow additional dry time in high humidity or cool temperatures.
7. Allow 24 hours or longer for caulk to dry before exposure to water.
8. Reseal cartridge or tube for storage and reuse.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Vehicle:	Acrylic Copolymer
Tooling Time:	5 minutes
Tack-Free Time:	15 minutes
Paintable:	Yes
Service Temperature Range:	-28°C to 82°C (-20°F to 180°F)
Application Temperature Range:	4°C to 37°C (40°F to 100°F)
Dynamic Joint Movement:	± 12.5%
Odour:	Very mild
Consistency:	Smooth and creamy
Volatile:	Water
Filler:	Calcium Carbonate
Flash Point:	None
Specific Gravity:	1.65
Solids:	82.0% by weight
Weight per Gallon:	13.80 lbs./gal.
Freeze Thaw Stability:	Passes 5 Cycles at 0°F
Shelf Life:	12 months
Coverage:	300 ml. cartridge: 55 linear ft. at a 3/16" bead size (three average size doors or four average size windows) 162 ml. squeeze tube: 30 linear ft. at a 3/16" bead size

CLEAN UP & STORAGE

Clean up excess uncured caulk with a damp sponge before it skins over. Wash hands with warm water and soap. Excess dried caulk must be cut or scraped away.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.ca or by calling 1-888-DAP-TIPS.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

WARRANTY

Limited Warranty:

DAP Products Inc. warrants that this product, when applied in accordance with our label, technical bulletins and applicable industry standards, will be free from defects in materials and workmanship for 12 months from the date of purchase. If a product defect is encountered, call 1-888-DAP-TIPS for warranty fulfillment. You must have your sales receipt and product container available when you call.

DAP's **sole liability** is either to supply new product or refund the purchase price. This limited warranty excludes all other express or implied warranties, including the warranties of **Merchantability or Fitness for a Particular Use or Purpose**. DAP will in no event be liable for any **Incidental or Consequential Damages**. Some states do not allow limitations on how long implied warranties last nor exclusions or limitations of incidental or consequential damages so the above limitations or exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from State to State.

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **1-888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com