



Safety Data Sheet

24 Hour Emergency Phone Numbers
Medical/Poison Control:
In U.S.: Call 1-800-222-1222

Outside U.S.: Call your local poison control center

Transportation/National Response Center:

1-800-535-5053

1-352-323-3500

NOTE: The National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this SDS are further described in Section 16.

1. Identification

This Safety Data Sheet is available in American Spanish upon request.
Los Datos de Seguridad pueden obtenerse en Espanol si lo requiere.

Product Name:	Plastic Wood-X All Purpose Wood Filler with DryDex Dry Time Indicator	Revision Date:	9/20/2018
Product UPC Number:	070798005402, 070798005426, 070798005419, 070798005433, 070798005952	Supersedes Date:	10/25/2017
Product Use/Class:	Wood Putty	SDS No:	00079206001
Manufacturer:	DAP Products Inc. 2400 Boston Street Suite 200 Baltimore, MD 21224-4723 888-327-8477 (non - emergency matters)	Preparer:	Regulatory and Environmental Affairs
	SDS Coordinator: MSDS@dap.com		
	Emergency Telephone: Transportation: 1-800-535 -5053 1-352-323-3500 Poison Control: 1-800-222-1222		

2. Hazards Identification

GHS Classification

Acute Tox. 4 Inhalation, Carc. 2, Eye Irrit. 2B, STOT RE 1, STOT SE 3 RTI

Symbol(s) of Product**Signal Word**

Danger

Possible Hazards

7% of the mixture consists of ingredients of unknown acute toxicity

GHS HAZARD STATEMENTS

Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
Carcinogenicity, category 1A	H350	May cause cancer.
STOT, single exposure, category 1	H370	Causes damage to organs . Classified Category 1 Substances that produced significant toxicity in humans and evidence to produce significant toxicity with single exposure. Cell death, adverse change in biochemistry, haematology or urinalysis parameters, Central or peripheral nervous system and effects senses. multifocal or diffuse necrosis, fibrosis or granuloma formation in organs.
STOT, repeated exposure, category 1	H372	Causes damage to organs through prolonged or repeated exposure.
Eye Irritation, category 2B	H320	Causes eye irritation

GHS LABEL PRECAUTIONARY STATEMENTS

P201	Obtain special instructions before use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P307+P311	IF exposed: Call a POISON CENTER or doctor/physician.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

GHS SDS PRECAUTIONARY STATEMENTS

P270	Do no eat, drink or smoke when using this product.
------	--

3. Composition/Information on Ingredients

Chemical Name	CAS-No.	Wt. %	GHS Symbols	GHS Statements
Limestone	1317-65-3	45-70	No Information	No Information
Fly ash	68131-74-8	5-10	GHS06	H331
Quartz	14808-60-7	0.1-1.0	GHS07	H302
Titanium dioxide	13463-67-7	0.1-1.0	No Information	No Information
Phenolphthalein	77-09-8	0.1-1.0	GHS08	H341-350

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures

FIRST AID - INHALATION: Material is not likely to present an inhalation hazard at ambient conditions. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

FIRST AID - SKIN CONTACT: In case of contact, wash skin immediately with soap and water.

FIRST AID - EYE CONTACT: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

FIRST AID - INGESTION: If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: No Information

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

6. Accidental Release Measures

ENVIRONMENTAL MEASURES: No Information

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

7. Handling and Storage

HANDLING: KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY. Use only with adequate ventilation. Ensure fresh air entry during application and drying. Avoid prolonged or repeated contact with skin. Avoid contact with eyes. Do not breathe dust. While dry sanding, use of a NIOSH-approved dust mask is recommended. Wash thoroughly after handling.

STORAGE: Do not store at temperatures above 120 degrees F. Store away from caustics and oxidizers. Keep containers tightly closed.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
Limestone	N.E.	N.E.	15 mg/m3 TWA total dust, 5 mg/m3 TWA respirable fraction	N.E.
Fly ash	N.E.	N.E.	N.E.	N.E.
Quartz	0.025 mg/m3 TWA respirable particulate matter	N.E.	50 µg/m3 TWA	N.E.
Titanium dioxide	10 mg/m3 TWA	N.E.	15 mg/m3 TWA total dust	N.E.
Phenolphthalein	N.E.	N.E.	N.E.	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation
Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: When concentrations exceed the exposure limits specified, use of a NIOSH-approved dust, mist and fume respirator is recommended. Where the protection factor of the respirator may be exceeded, use of a full facepiece, supplied air, or Self Contained Breathing Apparatus (SCBA) may be necessary. No personal respiratory protective equipment normally required. National Institute for Occupational Safety and Health (NIOSH) has recommended that the permissible exposure limit be changed to 50 micrograms respirable free silica per cubic meter of air (0.05 mg/m3) as determined by a full shift sample up to 10-hour work shift.



SKIN PROTECTION: Wear gloves with repeated or prolonged use. Wear protective gloves.



EYE PROTECTION: Safety glasses with side-shields.



OTHER PROTECTIVE EQUIPMENT: No special protective equipment required.



HYGIENIC PRACTICES: Remove and wash contaminated clothing before re-use. Although this product is not considered an eye irritant, inhalation hazard, or a skin contact hazard under normal conditions, it is advisable that personnel minimize skin contact, inhalation of vapors and eye contact.

9. Physical and Chemical Properties

Appearance:	Pink	Physical State:	Paste
Odor:	Slight	Odor Threshold:	Not Established
Density, g/cm³:	1.68 - 1.68	pH:	Between 7.0 and 12.0
Freeze Point, °C:	Not Established	Viscosity (mPa.s):	Not Established
Solubility in Water:	No Information	Partition Coeff., n-octanol/water:	Not Established
Decomposition Temperature, °C:	Not Established	Explosive Limits, %:	100 - 100
Boiling Range, °C:	100 - 100	Auto-Ignition Temperature, °C	Not Established
Minimum Flash Point, °C:	100	Vapor Pressure, mmHg:	Not Established
Evaporation Rate:	Slower Than n-Butyl Acetate	Flash Method:	Seta Closed Cup
Vapor Density:	Heavier Than Air	Flammability, NFPA:	Non-Flammable
Combustibility:	Does not support combustion		

(See "Other information" Section for abbreviation legend)

(If product is an aerosol, the flash point stated above is that of the propellant.)

10. Stability and Reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Do not breathe dust. Avoid dust formation in confined areas. Excessive heat and freezing.

INCOMPATIBILITY: Incompatible with strong bases and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e., CO_x, NO_x.

11. Toxicological Information

EFFECT OF OVEREXPOSURE - INHALATION: Under normal use conditions, this product is not expected to cause adverse health effects. Inhalation of vapors in high concentration may cause mild irritation of respiratory system (nose, mouth, mucous membranes). Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes). Prolonged, repeated, or high exposures may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Under normal use conditions, this product is not expected to cause adverse health effects. Prolonged or repeated contact with skin may cause mild irritation. May cause skin irritation in susceptible persons.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Under normal use conditions, this product is not expected to cause adverse health effects. Direct eye contact may cause irritation. May cause eye irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Under normal use conditions, this product is not expected to cause adverse health effects. Single dose oral toxicity is very low. Amounts ingested incidental to industrial handling are not likely to cause injury; however, ingestion of large amounts may cause injury.

CARCINOGENICITY: No Information

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: Contains Crystalline Silica which has been determined to be carcinogenic to humans (1) by IARC when in respirable form. Risk of cancer depends upon duration and level of inhalation exposure to dust from sanding the dried paint or spray mist. The International Agency for Research on Cancer (IARC) has determined that crystalline silica in the form of quartz or cristobalite that is inhaled from occupational sources is carcinogenic to humans (Group 1- carcinogenic to humans). Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (published in June 1997) in conjunction with the use of these materials. The National Toxicology Program (NTP) classifies respirable crystalline silica as "known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (Group A2). Breathing dust containing respirable crystalline silica may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may have the following serious chronic health effects: Excessive inhalation of respirable dust can cause pneumoconiosis, a respiratory disease, which can result in delayed, progressive, disabling and sometimes fatal lung injury. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function. Smoking exacerbates this disease.

Individuals with pneumoconiosis are predisposed to develop tuberculosis. There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by fibrosis of the lungs, skin and other internal organs) and kidney disease. This product contains fly ash based hollow microspheres. Avoid dry sanding which may generate levels of crystalline silica in excess of 0.1%. Prolonged or repeated inhalation of dust may cause lung damage. Under normal use conditions, this product is not expected to cause adverse health effects.

PRIMARY ROUTE(S) OF ENTRY: Inhalation, Skin Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
1317-65-3	Limestone	6450 mg/kg Rat	>2000 mg/kg	>20 mg/L
68131-74-8	Fly ash	>2000 mg/kg Rat	N.I.	> 5.38 mg/L Rat
14808-60-7	Quartz	500 mg/kg Rat	>2000 mg/kg	>20 mg/L
13463-67-7	Titanium dioxide	>10000 mg/kg Rat	>5000 mg/kg Rabbit	>20 mg/L
77-09-8	Phenolphthalein	N.I.	N.I.	N.I.

N.I. = No Information

12. Ecological Information

ECOLOGICAL INFORMATION: Ecological injuries are not known or expected under normal use.

13. Disposal Information

DISPOSAL INFORMATION: This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulation, 40 CFR Section 261. Dispose as hazardous waste according to all local, state, federal and provincial regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT UN/NA Number:	N.A.
DOT Proper Shipping Name:	Not Regulated
DOT Technical Name:	N.A.
DOT Hazard Class:	N.A.
Hazard SubClass:	N.A.
Packing Group:	N.A.

15. Regulatory Information

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
Phenolphthalein	77-09-8

TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

16. Other Information

Revision Date: 9/20/2018 **Supersedes Date:** 10/25/2017

Reason for revision: Product Composition Changed
 Substance and/or Product Properties Changed in Section(s):
 02 - Hazards Identification
 05 - Flammability Information
 09 - Physical & Chemical Information
 14 - Transportation Information
 15 - Regulatory Information
 Revision Statement(s) Changed

Datasheet produced by: Regulatory Department

HMIS Ratings:

Health:	Flammability:	Reactivity:	Personal Protection:
1	1	0	X

VOC Less Water Less Exempt Solvent, g/L: 3.3

VOC Material, g/L: 2

VOC as Defined by California Consumer Product Regulation, Wt/Wt%: 0.4

VOC Actual, Wt/Wt%: 0.1

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H302	Harmful if swallowed.
H331	Toxic if inhaled.
H341	Suspected of causing genetic defects.
H350	May cause cancer.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS06



GHS07



GHS08



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.

