

2" & 3 " Light Duty Casters

These are small yet efficient casters that move cleanly and stay out of the way. Great for light duty equipment that needs to be in motion frequently but doesn't require a lot of upkeep.

Zinc plated for corrosion resistance, rivited axle, and a double ball bearing swivel. Most models are available with brake.

Load Capacity 66 - 110 lbs

Applications:

- Office equipment
- Light medical stands & carts
- Chairs and stools
- Store fixtures

NSF Certified Component. The casters listed below are NSF listed

(Casters with polyurethane wheels excluded)

Add -FS to the end of the part number for NSF designation.

Product Images:

[Click to enlarge](#)

[Click to enlarge](#)

[Click to enlarge](#)

[Click to enlarge](#)

[Click to enlarge](#)

[Click to enlarge](#)

[Click to enlarge](#)

[Click to enlarge](#)

*Please select the quantity for each item you wish to order and click the 'Add To Quote' button below.

Model+	Type	Wheel Diameter (inches)	Tread Width (inches)	Wheel Type	Mounting Type	Mounting Size	Load Capacity (lbs)	Add Qty.
C-L20P2RS Swivel Radius: 1-13/16" Overall Height: 2-5/8" Bolt Size: 3/16" Hole Spacing: 13/16" x 1-9/16"	Swivel	2	13/16	Rubber	Plate	1-1/4" x 2-1/16"	77	<input type="text" value="0"/>
C-L20P2RSB Swivel Radius: 1-13/16" Overall Height: 2-5/8" Bolt Size: 3/16" Hole Spacing: 13/16" x 1-9/16"	Swivel with Brake	2	13/16	Rubber	Plate	1-1/4" x 2-1/16"	77	<input type="text" value="0"/>
C-L20S1MS Stem Size: 5/16" x 1-1/2" Swivel Radius: 1-13/16" Overall Height: 2-5/8"	Swivel	2	13/16	Non Marking Gray Rubber	Stem & Socket	5/16" x 1-1/2"	66	<input type="text" value="0"/>
C-L20S1MSB Stem Size: 5/16" x 1-1/2" Swivel Radius: 1-13/16" Overall Height: 2-5/8"	Swivel with Brake	2	13/16	Non Marking Gray Rubber	Stem & Socket	5/16" x 1-1/2"	66	<input type="text" value="0"/>
C-L20S1PS Stem Size: 5/16" x 1-1/2" Swivel Radius: 1-13/16" Overall Height: 2-5/8"	Swivel	2	13/16	Non-Marking Polyurethane	Stem & Socket	5/16" x 1-1/2"	100	<input type="text" value="0"/>
C-L20S1PSB Stem Size: 5/16" x 1-1/2" Swivel Radius: 1-13/16" Overall Height: 2-5/8"	Swivel with Brake	2	13/16	Non-Marking Polyurethane	Stem & Socket	5/16" x 1-1/2"	100	<input type="text" value="0"/>
C-L20S1RS Stem Size: 5/16" x 1-1/2" Swivel Radius: 1-13/16" Overall Height: 2-5/8"	Swivel	2	13/16	Rubber	Stem & Socket	5/16" x 1-1/2"	77	<input type="text" value="0"/>
C-L20S1RSB Stem Size: 5/16" x 1-1/2" Swivel Radius: 1-13/16" Overall Height: 2-5/8"	Swivel with Brake	2	13/16	Rubber	Stem & Socket	5/16" x 1-1/2"	77	<input type="text" value="0"/>
C-L20T1MS Stem Size: 5/16" - 18 x 1" Swivel Radius: 1-13/16" Overall Height: 2-5/8"	Swivel	2	13/16	Non Marking Gray Rubber	Threaded Stem	5/16" - 18 x 1"	66	<input type="text" value="0"/>
C-L20T1MSB Stem Size: 5/16" - 18 x 1" Swivel Radius: 1-13/16" Overall Height: 2-5/8"	Swivel with Brake	2	13/16	Non Marking Gray Rubber	Threaded Stem	5/16" - 18 x 1"	66	<input type="text" value="0"/>



DH Casters International - 2260 S. Haven Avenue, Suite C - Ontario, California 91761
Phone: 909.930.6400 - Fax: 909.930.6448 - Email: info@dhcasters.com

DH Casters International