

# DRYLOK® Pourable Crack Filler

## MANUFACTURER

### UNITED GILSONITE LABORATORIES

MAILING: P.O. Box 70, Scranton, Pennsylvania, 18501

SHIPPING: 1396 Jefferson Avenue, Dunmore, Pennsylvania, 18509

TOLL FREE: 1-800-UGL-LABS (845-5227)

PHONE: 1-570-344-1202 • FAX: 1-570-969-7634

www.UGL.com



## PRODUCT DESCRIPTION

DRYLOK® Pourable Masonry Crack Filler is formulated to fill and seal cracks on interior and exterior concrete and masonry surfaces. Reduces radon gas penetration. Dries to the color of concrete.

- Seals and fills cracks in concrete and masonry
- Blends with natural color and texture of surface
- Easy flow formula self-levels
- Reduces radon gas penetration
- Precise nozzle tip - no special tool needed

## BASIC USES

Ideal for interior and exterior concrete and masonry sidewalks, walkways, steps, patios, garage floors, etc.

## TECHNICAL DATA

### COMPOSITION:

Proprietary

### % WEIGHT SOLIDS:

85%

### COLORS:

Gray

### SET TIME:

12 Hours

**Note:** Maximum cure and dry time will be prolonged when slightly humid or when damp, cool conditions prevail.

### CLEAN UP:

Soap and water

Dispose of contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.

### COVERAGE (SQ. FT./US QT.):

One quart (946mL) will fill approximately a 1/4" x 1/2" (6 x 12mm) crack 38 ft (11m) long

**Note:** Actual coverage will vary depending upon application method, surface texture, and porosity.

### RECOMMENDED FILM THICKNESS/COAT:

N/A

### SHELF LIFE:

2 Years unopened container

### FREEZE/THAW:

Do not freeze

### CONTAINER SIZES:

One quart (US) container

### VOC

Does not exceed 40 g/L

### TINTING

N/A

## SURFACE PREPARATION

Apply when air and surface temperatures are a minimum of 50°F (10°C). Crack must be free from frost, dust, dirt, oil, and particles. Wire brushing and hosing facilitates cleaning. Remove excess moisture before filling the crack. Do not apply if rain is expected within 24 hours. SHAKE WELL BEFORE USING. Use only when cracks are 1/2" (12mm) wide or less.

## WARNING

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control

lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## APPLICATION

Remove the red cap. Cut the tip of the spout to a size slightly smaller than the width of the crack. Squeeze DRYLOK® Pourable Masonry Crack Filler tightly into the crack, over-filling slightly to allow for shrinkage. Smooth patched area with a putty knife. Replace the cap after use.

## VENTILATION

Use only with adequate ventilation.

## CAUTION

Cancer hazard: Contains Crystalline Silica, which can cause cancer. Risk of cancer depends on duration and level of exposure to dust generated from sanding surfaces, grinding, or spray mists.

**Use only with adequate ventilation.** Do not breathe dust. Avoid exposure to dust by wearing an appropriate (NIOSH approved) particulate respirator during sanding. Follow respirator manufacturer's directions for respirator use. Close container after each use. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

**KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY. KEEP FROM FREEZING.**

## FIRST AID

In case of eye contact, flush immediately



**SET TIME:**  
12 Hours



**CLEAN-UP:**  
Soap and Water



**COVERAGE:**  
Varies on Application



**SPREAD RATE:**  
1 Qt./1/4"x1/2"  
Crack 38 Ft. Long

OVER

with plenty of water for at least 15 minutes. If swallowed, do not induce vomiting. Call poison control center, hospital emergency room, or physician immediately. For additional health and safety information please refer to the "Safety Data Sheet".

If spilled, contain spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulators.

 **WARNING:** Cancer – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

DRYLOK® is a registered trademarks of United Gilsonite Laboratories (UGL®).



**Pourable Masonry Crack Filler – Gray**  
1 QT. 6/Case .....30512

**DISCLAIMER:** This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.