

# DURAPRO<sup>®</sup>

AF0034

ZERO<sup>\*</sup>  
UF

## Pre-finish Wood Parquet Adhesive



DURA PRO AF 0034 is a high solids latex based adhesive used for direct glue-down of pre-finished 12"x12" finger strips mosaic parquet made of maple, oak or birch on T&G floor grade plywood or cured concrete either on above or below grade.





## AF0034

## Pre-finish Wood Parquet Adhesive

### PRODUCT DESCRIPTION

DURA PRO AF 0034 is a high solids latex based adhesive used for direct glue-down of pre-finished 12"x12" finger strips parquet made of maple, oak or birch on T&G floor grade plywood or cured concrete either on above or below grade.

### PRODUCT FEATURES

- Rapid set
- Excellent adhesion
- Non – Flammable
- VOC compliant

### PREPARATION

Subfloors must be structurally sound, linear, porous, clean, dry and free of contaminants. Adhesive and wood flooring (unwrapped) must be at room temperature (20°C) 24 hours before, during, and after installation. Best bonds are obtained when moisture content of wood ranges between 8% and 12%; concrete floors must be fully cured and free from moisture and hydrostatic pressure.

### APPLICATION

Stir before using. Spread adhesive with a 5 mm (3/16") V notch trowel held at 45° angle. Apply adhesive evenly on surface which can be covered in about 10 minutes. Leave 6 mm (1/4") minimum space uncovered along the walls and permanent structures for normal wood expansion. Install the parquet then press it down into the glue by using a rubber mallet or walking on it in both directions step by step. Check for adhesive transfer to the back of the parquet. Let dry 24 hours before allowing heavy foot traffic or moving furniture.

### COVERAGE

Approximately 2 m<sup>2</sup>/L (80 sq.ft./gallon)

### ATTENTION

Refer to wood flooring manufacturer's recommendation for layout, expansion space requirements, and detailed installation instructions. Room temperature must be kept at 20°C and at relative humidity between 35%-55% one week before the installation and thereafter. For indoor use only. For basement floors or areas below grade, a subfloor should be built over a vapour barrier.

### PHYSICAL PROPERTIES

Viscosity	25 - 26 McPs (6/20 rpm/25°C)
Solids	70% - 72%
Colour	Creamy white
Odour	Very Mild
Specific Gravity	1.35 ± 0.02
pH	6.5 - 7.5
Water Resistance	Excellent (when dried)
Open Time	10 – 15 minutes
VOC	1.2 g / L

### RESTRICTIONS

AF 0034 is not recommended for engineered wood flooring, wood planks, and exotic woods. Not to be used on particleboard.

### CLEAN UP

Clean hands, tools and excess adhesive with warm soapy water before the product dries. If glue has hardened, mineral spirits may be used with caution for cleaning. On bonded materials, scrape off and sand dried excess.

### STORAGE

Shelf life is 18 months at room temperature in original unopened container. Product is freeze/thaw stable if frozen not lower than -10°C.

### PRECAUTIONS

This product is not classified dangerous according to the Consumer Chemicals and Containers Regulations (CCCR). Note to professional user: refer to Safety Data Sheet (SDS) for more information.

### ENVIRONMENT

VOC compliant for low emissions adhesives and sealants standards in place at the date of production. \*This product contains no added urea-formaldehyde. The use of this product may contribute in obtaining LEED credits.

### ORDERING INFORMATION

UPC	Size	Units per case	Units per row	Units per pallet
058751340104	950 ml	6	72	432
058751343785	3.78 L	2	20	100
058751340159	15.0 L	1	12	36



## AF0034

## Pre-finish Wood Parquet Adhesive

---

### WARRANTY

Surface conditions, product application, storage and transport are beyond the manufacturer's control; liability, if any, is limited to replacement of product ONLY.

### DISCLAIMER

Our personnel is available to help purchasers obtain best results from our products, and recommendations are based on tests and information believed to be reliable. However, since we have no control over the conditions under which our products are transported to, stored, handled, or used by purchasers, all recommendations and sales are made on condition that we will not be held liable for any damages resulting from their use. No representative of ours has any authority to waive or change this provision.

### DATE

April 2017



PRODUCT CERTIFIED FOR REDUCED  
ENVIRONMENTAL IMPACT. VIEW SPECIFIC  
ATTRIBUTES EVALUATED.  
PRODUIT CERTIFIÉ À IMPACT  
ENVIRONNEMENTAL RÉDUIT.  
VEUILLEZ CONSULTER LES  
ATTRIBUTS SPÉCIFIQUES  
ÉVALUÉS. UL.COM/EL  
UL2762