

Coating

Product Description

Dupli-Color High Performance Wheel Coating has an advanced, track-tested acrylic enamel formula. The coating restores original wheel appearance and protects against brake dust, chemicals, cleaning solvents, heat, and chipping. It features a highly durable finish with superior adhesion to steel, aluminum, and plastic wheels and wheel coverings.

Product Characteristics

Colors: High Performance White, High Performance Silver, High Performance Graphite, High Performance Satin Black, & High Performance Bronze.

Clear: High Performance Clear & Matte.

Finish: Matte, Metallic, & High Gloss.

Properties

Product Weight: 6.47 lb/gal

Flash Point: Propellant < 0° F

Preferred Application

Dupli-Color High Performance Wheel Coating provides optimum performance when this application method is followed.

Prep	PW100 CM541	Prep Wipe Grease & Wax Remover
Coat	HWPxxx	Wheel Coating
Clear	HWP103	High Performance Coating

Refer to the application box for more specific instructions!

Application

Remove wheel or hubcap from vehicle surface. Prepare surface by removing loose paint, dirt, rust, grease, wax, etc. For best results, use a Dupli-Color Prep Wipe (PW100) or Grease & Wax Remover to clean surface. Sand surface with 320-grit sand paper, wet or dry. Wash with mild soap and water. Rinse well and dry with a clean cloth.

Mask-off the surrounding areas to protect from overspray. Use at temperatures between 60°-92° F, and when humidity is less than 60%.

Shake can vigorously for one full minute after mixing ball moves freely. After each minute of use, shake the can for an additional 10 seconds. To spray, hold can parallel 8-10 inches from the surface to be painted and use in an even, sweeping motion. To avoid runs and sags, apply in 2 light coats, followed by one medium wet coat. Apply all coats within 1 hour, allowing 10 minutes between each coat. For additional coats after 1 hour, wait 7 days for paint to cure. Dries to the touch in one hour. Can be handled in 3 hours. Covers approximately 12-14 square feet.

For added gloss & durability, coat with Dupli-Color High Performance Wheel Clear Coat (WP103) within 1 hour of last color coat.

Packaging

Fill Weight: 11 oz

Per Case: 6 cans

Case Weight: 6.17 lbs

Cases/Pallet: 156

Units/Pallet: 936 cans

Uses

Wheels & Wheel Coverings.

Surfaces:

Steel, Aluminum, & Plastic.