

## WATER WELL PUMPS - 4" Submersible Pumps



# EFSUB10-123

## 4" Submersible Pump, 3-Wire

### 1 HP - 12 GPM

#### APPLICATIONS

- Provides Smooth Water Passages for Maximum Efficiency

#### FEATURES

- 1-1/4" FNPT Discharge Cast Iron Discharge Connection, includes Built-in Check Valve,
- Stainless Steel Pump Shaft is Precision Ground for Exact Bearing Fit and Straightness
- Precision Molded Impellers and Diffusers
- Stainless Steel Pump Housing for Maximum Protection Against Corrosion
- Stainless Steel Splined Shaft
- Self-healing REsin System
- Hermetically-sealed Windings
- Filter Check Valve
- Kingsbury-type Thrust Bearing
- Pressure Equalizing Diaphragm
- Removable Water-bloc Lead Connector
- NEMA Mounting Dimensions

#### SPECIFICATIONS

UPC	WARRANTY	WEIGHT	DIMENSIONS (L x W x H)	PALLET QUANTITY
856594003763	1 Year	27.6 Lbs.	29.3" x 3.5"	108



#### PERFORMANCE CHART

MODEL	HP	GPM	VOLT	GALLONS PER MINUTE PUMPED AT DIFFERENT DEPTHS TO WATER											
				20	40	60	80	100	150	175	200	250	300	350	
EFSUB10-123	1	10	230	-	-	-	-	-	-	-	11.1	10.5	9.7	-	-

PERFORMANCE SHOWN IN GPM AT 40 PSI DISCHARGE PRESSURE

### ECO-FLO PRODUCTS INCORPORATED

1899 Cottage Street, Ashland, Ohio 44805 • Customer Service: 1-877 326-3561 • Fax: 1-877 326-1994 • [www.ecofloproducts.com](http://www.ecofloproducts.com)