



- > Energy Saving 22 Watt Integrated LED
- > Uses 78% Less Energy than Equivalent 100 Watt Incandescent Bulb
- > Cool White 4000k CCT
- > Lasts 45 years or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty

16" Low Profile Flushmount

1600 lms | 120-277VAC | Model 54437241 | Part FM-16-22-840-MV-N-B



SPECIFICATIONS

Model	54437241
Part	FM-16-22-840-MV-N-B
Description	16" Round Low Profile - Non-Dimmable
Input Voltage (VAC)	120-277
Wattage	22
Average Rated Life ¹	50,000 hours
Typical Lumens ²	1600
CCT ³	4000k
Location Rating	UL Damp
CRI ⁴	80
Beam Angle	120
Operating Temperature	Min -4°F (-20° C), Max 95°F (35° C)
Power Factor	>0.9
R9	16
DUV	0.00124
CBCP	383
Operating Frequency (Hz)	50/60

1 Hours lifetime with 70% lumen maintenance

2 Thermally stable typical lumens (±10%)

3 Thermally stable CCT (±10%)

4 Color rendering index/Ra


TO ORDER:

www.ETiSSL.com

Call: 1.855.ETi.SSLI


1.855.384.7754



**lighting facts**[®]
A Program of the U.S. DOE

Light Output (Lumens)	1600
Watts	22
Lumens per Watt (Efficacy)	72.73

Color Accuracy	80
Color Rendering Index (CRI)	

Light Color	4000 (Bright White)		
Correlated Color Temperature (CCT)			
			
Warm White	Bright White	Daylight	
2700K	3000K	4500K	6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the Label Reference Guide.

Registration Number: YN84-6MXRTH (1/21/2017)
Model Number: 54437241/###(##=41-50)
Type: Luminaire - Decorative





16" Low Profile Flushmount

1600 lms | 120-277VAC | Model 54437241 | Part FM-16-22-840-MV-N-B

SHIPPING INFORMATION

Model	54437241
Part	FM-16-22-840-MV-N-B
UPC	849489001265
Product Dimensions (L x W x H in.)	15.4 x 15.4 x 2.95
Product Dimensions (L x W x H cm.)	39.2 x 39.2 x 7.5
Product Weight (lbs.)	1.84
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	4
Master Carton Bar Code	50849489001260
Master Carton Dimensions (L x W x H in.)	16.89 x 13.86x 17.09
Master Carton Dimensions (L x W x H cm.)	42.9 x 35.2 x 43.4
Master Carton Weight (lbs)	11.9
Pallet Quantity	72

AVAILABLE ACCESSORIES

Model	Description
995443720101	Diffuser Lens

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.etissl.com/fcc15b

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754

ETi Solid State Lighting, Inc.
720 Corporate Woods Parkway
Vernon Hills, IL 60061
Phone: 855.384.7754
Fax: 847.383.6256