

- > Energy Saving 22 Watt Integrated LED
- > Uses 78% Less Energy than Equivalent 100 Watt **Incandescent Bulb**
- > Cool White 4000k CCT
- > Lasts 45 years or 50,000 **Hours Continuous Use**
- > Maintenance Free No **Bulb Replacements**
- > 5 Year Limited Warranty

15" Round Brush Nickel Flushmount

1550 lms | 120VAC | Model 54620142 | Part FM-15-22-840-SV-D-C



SPECIFICATIONS

54620142 Model

FM-15-22-840-SV-D-C Part

15" Round Brush Nickel Flushmount Description

120 Input Voltage (VAC) 22 Wattage Triac Dimmability

50,000 hours Average Rated Life¹

1550 Typical Lumens² CCT³ 4000k **UL Damp Location Rating**

CRI⁴ 82 120 **Beam Angle**

Min -4°F (-20° C), **Operating Temperature**

Max 95°F (35°C)

>0.9 **Power Factor** 4 R9 0.0051 DUV

Operating Frequency (Hz)

- 1 Hours lifetime with 70% lumen maintenance
- 2 Thermally stable typical lumens (±10%)
- 3 Thermally stable CCT (±10%)
- 4 Color rendering index/Ra



1.855.384.7754













15" Round Brush Nickel Flushmount

1550 lms | 120VAC | Model 54620142 | Part FM-15-22-840-SV-D-C

SHIPPING INFORMATION

Model 54620142

Part FM-15-22-840-SV-D-C

UPC 836607009371

Product Dimensions (L x W x H in.) 15.35 x 15.35 x 3.54

Product Dimensions (L x W x H cm.) 39.0x 39.0 x 9.0

Product Weight (lbs.)

2.2

Inner Carton Quantity

N/A

Inner Carton Bar Code

N/A

Inner Carton Dimensions (L x W x H in.)

N/A

Inner Carton Dimensions (L x W x H cm.)

N/A

Inner Carton Weight (lbs)

N/A

Master Carton Quantity 3

Master Carton Bar Code50836607009376Master Carton Dimensions (L x W x H in.)17.64 x 14.17x 18.35

Master Carton Dimensions (L x W x H cm.) $44.8 \times 36.0 \times 46.6$

Master Carton Weight (lbs) 11.66
Pallet Quantity 54

COMPATIBILITY

Dimmers:

 Lutron
 Leviton
 Cooper

 DVCL-153PR-WH
 IPL06
 DLC03P-LA

 SCL-153RR-WH
 6672
 9573

 SCL-153P
 9530SG-K

TGCL-153PH-WH LG-600H-WH TG-603PGH-WH

AVAILABLE ACCESSORIES

Model Description
95462014102 Diffuser Lens

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.etissl.com/fcc15b

TO ORDER: www.ETiSSL.com Call: 1.855.ETi.SSLI 1.855.384.7754 ETi Solid State Lighting, Inc. 720 Corporate Woods Parkway Vernon Hills, IL 60061 Phone: 855.384.7754 Fax: 847.383.6256