



7" Spin Light™ with Motion Sensor

830 lm | 120VAC | Model 54606342 | Part SL-7-11-840-SV-N-OS

- > Energy Saving 11.5 Watt Integrated LED
- > Uses 81% Less Energy than Equivalent 60 Watt Incandescent Bulb
- > Cool White 4000K CCT
- > Lasts 45.6 years or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty
- > Suitable for use in closets, as defined in NEC® Section 410.16
- > US Patent # 9500352, 9541270, D776326
- > CND Patent # 169113



SPECIFICATIONS

Model	54606342
Part	SL-7-11-840-SV-N-OS
Description	7" Spin Light™ with Motion Sensor
Input Voltage (VAC)	120
Wattage	11.5
Dimmability	Non-Dimmable
Average Rated Life ¹	50,000 hours
Typical Lumens ²	830
CCT ³	4000K
Location Rating	UL Damp
CRI ⁴	80
Beam Angle Operating	120
Temperature	Min -4°F (-20° C), Max 95°F (35° C)
Power Factor	>0.9
R9	17
DUV	-0.002280
Operating Frequency (Hz)	60

1 Hours lifetime with 70% lumen maintenance
 2 Thermally stable typical lumens (±10%)
 3 Thermally stable CCT (±10%)
 4 Color rendering index/Ra

ETI

LED lighting facts
A Program of the U.S. DOE

Light Output (Lumens)	830
Watts	11.5
Lumens per Watt (Efficacy)	72.17
Color Accuracy	
Color Rendering Index (CRI)	80
Light Color	
Correlated Color Temperature (CCT)	4000 (Bright White)
Warm White	Bright White
2700K	3000K
4500K	6500K
All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.	
Visit www.lightingfacts.com for the Label Reference Guide.	
Registration Number: YN84-OL4ASD (6/23/2017) Model Number: 546063XX(XX=41-50) Type: Luminaire - Other	

TO ORDER:
www.ETiSSL.com
 Call: 1.855.ETi.SSLI
 1.855.384.7754





7" Spin Light™ with Motion Sensor

830 lm | 120VAC | Model 54606342 | Part SL-7-11-840-SV-N-OS



SHIPPING INFORMATION

Model	54606342
Part	SL-7-11-840-SV-N-OS
UPC	849489006499
Product Dimensions (L x W x H in.)	7.01 x 7.01 x 3.58
Product Dimensions (L x W x H cm.)	17.8 x 17.8 x 9.10
Product Weight (lbs.)	0.77
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	5
Master Carton Bar Code	50849489006494
Master Carton Dimensions (L x W x H in.)	20.51 x 7.91 x 8.27
Master Carton Dimensions (L x W x H cm.)	52.1 x 20.1 x 21..0
Master Carton Weight (lbs)	6.5
Pallet Quantity	300

COMPATIBILITY

Sensors: Built in PIR Sensor

AVAILABLE ACCESSORIES

Model	Description
954606342	Diffuser Lens

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.etiled.us/fcc15b

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754

ETi Solid State Lighting, Inc.
720 Corporate Woods Parkway
Vernon Hills, IL 60061
Phone: 855.384.7754
Fax: 847.383.6256