



# 15" Color preference® Flushmount

1450lms | 120VAC | Model 54451311 | Part FM-15-22-802-SV-D-K

- > Energy Saving 22 Watt Integrated LED
- > Uses 78% Less Energy than Equivalent 100 Watt Incandescent Bulb
- > Soft White 3000k CCT  
Cool White 4000k CCT  
Daylight 5000k CCT
- > Lasts 45 years or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty



## SPECIFICATIONS

Model	54451311
Part	FM-15-22-802-SV-D-K
Description	15" Color preference® Flushmount
Input Voltage (VAC)	120
Wattage	22
Dimmability	Triac
Average Rated Life <sup>1</sup>	50,000 hours
Typical Lumens <sup>2</sup>	1450
CCT <sup>3</sup>	3000k/4000k/5000k
Location Rating	UL Damp
CRI <sup>4</sup>	80
Beam Angle	120
Operating Temperature	Min -4°F (-20° C), Max 95°F (35° C)
Power Factor	>0.9
R9	15
DUV	-0.0010
CBCP	317
Operating Frequency (Hz)	60

1 Hours lifetime with 70% lumen maintenance  
 2 Thermally stable typical lumens (±10%)  
 3 Thermally stable CCT (±10%)  
 4 Color rendering index/Ra

**LED lighting facts**  
A Program of the U.S. DOE

Light Output (Lumens)	1450
Watts	22
Lumens per Watt (Efficacy)	65.91
Color Accuracy Color Rendering Index (CRI)	80
Light Color Correlated Color Temperature (CCT)	3000 (Bright White)

Color temperature scale: 2700K (Warm White) | 3000K (Bright White) | 4500K | 6500K (Daylight)

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit [www.lightingfacts.com](http://www.lightingfacts.com) for the Label Reference Guide.

Registration Number: YN84-G7E2UK (6/23/2017)  
 Model Number: 54451311(##=11-30)  
 Type: Luminaire - Other

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
 Call: 1.855.ETi.SSLI  
 1.855.384.7754





# 15" Color preference® Flushmount

1450lms | 120VAC | Model 54451311 | Part FM-15-22-802-SV-D-K



## SHIPPING INFORMATION

<b>Model</b>	54451311
<b>Part</b>	FM-15-22-802-SV-D-K
<b>UPC</b>	849489001487
<b>Product Dimensions (L x W x H in.)</b>	14.96 x 14.96 x 3.50
<b>Product Dimensions (L x W x H cm.)</b>	38.0 x 38.0 x 8.90
<b>Product Weight (lbs.)</b>	2.2
<b>Inner Carton Quantity</b>	N/A
<b>Inner Carton Bar Code</b>	N/A
<b>Inner Carton Dimensions (L x W x H in.)</b>	N/A
<b>Inner Carton Dimensions (L x W x H cm.)</b>	N/A
<b>Inner Carton Weight (lbs)</b>	N/A
<b>Master Carton Quantity</b>	4
<b>Master Carton Bar Code</b>	50849489001482
<b>Master Carton Dimensions (L x W x H in.)</b>	17.24 x 16.14 x 17.40
<b>Master Carton Dimensions (L x W x H cm.)</b>	43.8 x 41.0 x 44.2
<b>Master Carton Weight (lbs)</b>	14.26
<b>Pallet Quantity</b>	48

## COMPATIBILITY

### Dimmers:

Lutron	Leviton	Cooper
DVCL-153PR-WH	IPL06	DLC03P-LA
SCL-153RR-WH	6672	9573
SCL-153P		9530SG-K
TGCL-153PH-WH		
LG-600H-WH		
TG-603PGH-WH		

## AVAILABLE ACCESSORIES

<b>Model</b>	<b>Description</b>
95445131101	Diffuser Lens

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see [www.etiled.us/fcc15b](http://www.etiled.us/fcc15b)

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
Call: 1.855.ETi.SSLI  
1.855.384.7754

**ETi Solid State Lighting, Inc.**  
720 Corporate Woods Parkway  
Vernon Hills, IL 60061  
Phone: 855.384.7754  
Fax: 847.383.6256