



# 11" Color preference® Flushmount

910lms | 120VAC | Model 54450511 | Part FM-11-14-802-SV-D-J

- > Energy Saving 14 Watt Integrated LED
- > Uses 81% Less Energy than Equivalent 75 Watt Incandescent Bulb
- > Soft White 3000k CCT  
Cool White 4000k CCT  
Daylight 5000k CCT
- > Lasts 45 years or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty



## SPECIFICATIONS

Model	54450511
Part	FM-11-14-802-SV-D-J
Description	11" Color preference® Flushmount
Input Voltage (VAC)	120
Wattage	14
Dimmability	Triac
Average Rated Life <sup>1</sup>	50,000 hours
Typical Lumens <sup>2</sup>	910
CCT <sup>3</sup>	3000k/4000k/5000k
Location Rating	UL Damp
CRI <sup>4</sup>	80
Beam Angle	120
Operating Temperature	Min -4°F (-20° C), Max 95°F (35° C)
Power Factor	>0.9
R9	23
DUV	-0.0018
CBCP	174
Operating Frequency (Hz)	60

1 Hours lifetime with 70% lumen maintenance  
 2 Thermally stable typical lumens (±10%)  
 3 Thermally stable CCT (±10%)  
 4 Color rendering index/Ra

**LED lighting facts®**  
A Program of the U.S. DOE

Light Output (Lumens)	910
Watts	14
Lumens per Watt (Efficacy)	65
Color Accuracy Color Rendering Index (CRI)	80
Light Color Correlated Color Temperature (CCT)	3000 (Bright White)

Warm White 2700K | Bright White 3000K | Daylight 4500K | 6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit [www.lightingfacts.com](http://www.lightingfacts.com) for the Label Reference Guide.

Registration Number: YN84-PNSJMU (6/23/2017)

Model Number: 54450511(##=11-30)

Type: Luminaire - Other

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
 Call: 1.855.ETi.SSLI  
 1.855.384.7754





# 11" Color preference® Flushmount

910lms | 120VAC | Model 54450511 | Part FM-11-14-802-SV-D-J



## SHIPPING INFORMATION

Model	54450511
Part	FM-11-14-802-SV-D-J
UPC	849489001494
Product Dimensions (L x W x H in.)	10.75 x 10.75 x 3.78
Product Dimensions (L x W x H cm.)	27.3 x 27.3 x 9.60
Product Weight (lbs.)	1.21
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	6
Master Carton Bar Code	50849489001499
Master Carton Dimensions (L x W x H in.)	25.35 x 13.23 x 13.46
Master Carton Dimensions (L x W x H cm.)	64.4 x 33.6 x 34.2
Master Carton Weight (lbs)	12.79
Pallet Quantity	108

## COMPATIBILITY

### Dimmers:

Lutron	Leviton	Cooper
DVCL-153PR-WH	IPL06	DLC03P-LA
SCL-153RR-WH	6672	9573
SCL-153P		9530SG-K
TGCL-153PH-WH		
LG-600H-WH		
TG-603PGH-WH		

## AVAILABLE ACCESSORIES

Model	Description
95445051101	Diffuser Lens

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see [www.etiled.us/fcc15b](http://www.etiled.us/fcc15b)

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
Call: 1.855.ETi.SSLI  
1.855.384.7754

**ETi Solid State Lighting, Inc.**  
720 Corporate Woods Parkway  
Vernon Hills, IL 60061  
Phone: 855.384.7754  
Fax: 847.383.6256