



# 24" Beam Adjustable Under Cabinet

700lms | 120VAC | Model 53504111 | Part UC-24-13-930-SV-D

- > Easy installation including MAGNA MOUNT™ and screw mount.
- > Adjustable light angel and dimmable.
- > Amber White 2200k to Soft White 3000k CCT
- > Lasts 45 years\* or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty



## SPECIFICATIONS

Model	53504111
Part	UC-24-13-930-SV-D
Description	24" Beam Adjustable Under Cabinet Light-Dimmable
Input Voltage (VAC)	120
Wattage	12.5
Dimmability	Triac
Average Rated Life <sup>1</sup>	50,000 hours
Typical Lumens <sup>2</sup>	700
CCT <sup>3</sup>	2200-3000k
Location Rating	UL Damp
CRI <sup>4</sup>	90
Beam Angle	90
Operating Temperature	Min -4°F (-20° C), Max 113°F (45° C)
Power Factor	>0.8
R9	61
DUV	.0020
Operating Frequency (Hz)	60

- 1 Hours lifetime with 70% lumen maintenance
- 2 Thermally stable typical lumens (±10%)
- 3 Thermally stable CCT (±10%)
- 4 Color rendering index/Ra

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
Call: 1.855.ETi.SSLI  
1.855.384.7754

**Lighting facts**  
A Program of the U.S. DOE

Light Output (Lumens)	700
Watts	12.5
Lumens per Watt (Efficacy)	56
Color Accuracy Color Rendering Index (CRI)	93
Light Color Correlated Color Temperature (CCT)	3000 (Bright White)

Warm White | Bright White | Daylight  
2700K | 3000K | 4500K | 6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit [www.lightingfacts.com](http://www.lightingfacts.com) for the Label Reference Guide.

Registration Number: YN84-SO524J (8/22/2017)  
Model Number: 535041###(##=11-30)  
Type: Luminaire - Display Case





# 24" Beam Adjustable Under Cabinet

700lms | 120VAC | Model 53504111 | Part UC-24-13-930-SV-D



## SHIPPING INFORMATION

Model	53504111
Part	UC-24-13-930-SV-D
UPC	849489009117
Product Dimensions (L x W x H in.)	24 x 2.4 x 1.1
Product Dimensions (L x W x H cm.)	609 x 61 x 28
Product Weight (lbs.)	1.69
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	5
Master Carton Bar Code	50849489009112
Master Carton Dimensions (L x W x H in.)	30.87 x 9.37 x 3.66
Master Carton Dimensions (L x W x H cm.)	784 x 238 x 93
Master Carton Weight (lbs)	10.92
Pallet Quantity	400

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see [www.eted.us/fcc15b](http://www.eted.us/fcc15b)

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
Call: 1.855.ETi.SSLI  
1.855.384.7754

**ETi Solid State Lighting, Inc.**  
720 Corporate Woods Parkway  
Vernon Hills, IL 60061  
Phone: 855.384.7754  
Fax: 847.383.6256