

- > 120/277V Dual voltage operation
- > Test switch and charge indicator
- > Maximum 24 hours for full recharge time
- > Lasts 45 years\* or 50,000 Hours Continuous Use
- > Minimum 90 minutes emergency operation
- > 2 Year Limited Warranty

# **Emergency Light/Exit Sign Combo**

263lms | 120/277VAC | Model 55502101 | Part EM-ELC-R



### **SPECIFICATIONS**

 Model
 55502101

 Part
 EM-ELC-R

Description Emergency Light/Exit Sign Combo

Input Voltage (VAC) 120/277
Wattage 2.4
Dimmability NA

Average Rated Life<sup>1</sup> 50,000 hours

Typical Lumens<sup>2</sup> 263
CCT<sup>3</sup> 6500k
Location Rating UL Damp

CRI<sup>4</sup> NA
Beam Angle NA

Operating Temperature Min 32°F (0°C),

Max 104°F (40° C)

Power Factor NA
R9 NA
DUV NA
CBCP NA
Operating Frequency (Hz) 50/60

- 1 Hours lifetime with 70% lumen maintenance
- 2 Thermally stable typical lumens (±10%)
- 3 Thermally stable CCT (±10%)
- 4 Color rendering index/Ra



www.ETiSSL.com Call: 1.855.ETi.SSLI 1.855.384.7754











# **Emergency Light/Exit Sign Combo**

263lms | 120/277VAC | Model 55502101 | Part EM-ELC-R

#### SHIPPING INFORMATION

 Model
 55502101

 Part
 EM-ELC-R

 UPC
 849489009650

 Product Dimensions (L x W x H in.)
 19.84 x 7.95 x 4.37

 Product Dimensions (L x W x H cm.)
 50.4 x 20.2 x 11.1

Product Weight (lbs.)

Inner Carton Quantity

Inner Carton Bar Code

Inner Carton Dimensions (L x W x H in.)

Inner Carton Dimensions (L x W x H cm.)

Inner Carton Weight (lbs)

Master Carton Quantity

3.77

N/A

N/A

N/A

6

Master Carton Bar Code50849489009655Master Carton Dimensions (L x W x H in.)19.69 x 17.32 x 15.16Master Carton Dimensions (L x W x H cm.)50.0 x 44.0 x 38.5

Master Carton Weight (lbs) 27.78
Pallet Quantity 72

#### **COMPATIBILITY**

Dimmers: NA Sensors: NA

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.ETiSSL.com/fcc15b

TO ORDER: www.ETiSSL.com Call: 1.855.ETi.SSLI 1.855.384.7754 ETi Solid State Lighting, Inc. 720 Corporate Woods Parkway Vernon Hills, IL 60061 Phone: 855.384.7754 Fax: 847.383.6256