



5 7/16" AC Power Recessed Downlight

670lm | 120VAC | Ordering 53193101 | Part DL-6-11-827-SV-D

- > Energy Saving 9 Watt Integrated LED
- > Uses 84% Less Energy than Equivalent 65 Watt Incandescent Bulb
- > Warm White 2700K CCT
- > Lasts 45 years* or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty
- > IC Rated for Direct Contact with Insulation



SPECIFICATIONS

Ordering	53193101
Part	DL-6-11-827-SV-D
Description	5 7/16" AC Power Recessed Retrofit Downlight Kit
Input Voltage (VAC)	120
Wattage	9
Dimmability	Triac
Average Rated Life ¹	50,000 hours
Typical Lumens ²	670
CCT ³	2700K
Location Rating	UL Wet
CRI ⁴	80
Beam Angle	100
Operating Temperature	Min -4°F (-20° C), Max 113°F (45° C)
Power Factor	>0.9
R9	12
DUV	-0.00084
CBCP	311
Operating Frequency (Hz)	60

1 Hours lifetime with 70% lumen maintenance
 2 Thermally stable typical lumens (±10%)
 3 Thermally stable CCT (±10%)
 4 Color rendering index/Ra


ETI

LED lighting facts
A Program of the U.S. DOE

Light Output (Lumens)	670
Watts	10.5
Lumens per Watt (Efficacy)	63.81

Color Accuracy	80
Color Rendering Index (CRI)	

Light Color	2700 (Warm White)
Correlated Color Temperature (CCT)	



Warm White Bright White Daylight
 2700K 3000K 4500K 6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the Label Reference Guide.

Registration Number: YN84-T16PMB (8/11/2017)
 Model Number: 531931#(##=00-10)
 Type: Luminaire - Downlight

TO ORDER:
www.ETiSSL.com
 Call: 1.855.ETi.SSLI
 1.855.384.7754





5 5/8" AC Power Recessed Downlight

670 lm | 120VAC | Ordering 53193101 | Part DL-6-11-827-SV-D

SHIPPING INFORMATION

Ordering	53193101
Part	DL-6-11-827-SV-D
UPC	849489006406
Product Dimensions (W x H in.)	7 1/2 x 2 1/8
Product Dimensions (W x H cm.)	19 x 5 1/2
Product Weight (lbs.)	0.77
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	4
Master Carton Bar Code	50849489006401
Master Carton Dimensions (L x W x H in.)	10 x 9 x 10
Master Carton Dimensions (L x W x H cm.)	242 x 217 x 262
Master Carton Weight (lbs)	1.84
Pallet Quantity	252

COMPATIBILITY

Dimmers:

Lutron: CT-603PGH-WH, GL-600H-DK, MSCL-OP153M, MACL-153MH-WH, SCL-153PR-WH, TGCL-153PR-WH, TGCL-153PH-WH, TG-603PGH-WH, AYCL-153P-WH
Leviton: CD-C22-06672-12A, CD-R62-06674-12A, CD-R50-IPL06-12A, SB-011-IPL06-22A, 8100-I

Legrand: ADWR703HW4, ADPD453LM2

Cooper: DLC03PA-PTA, 9573A-PTA

Cans:

Commercial Electric: H1, H2, H3, H4, H5, H6, H7, H8, H15, H16, H17, H18, H21

Juno: IC20, IC21, IC22, IC20R, IC2R, IC22R

Halo: H5T, H5RT, H5ICAT, H5RICAT, H5ICT, H5RICT, H7RICT, H7ICAT, H7RICAT, H7ICT,

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.etiled.us/fcc15b

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754

ETi Solid State Lighting, Inc.
720 Corporate Woods Parkway
Vernon Hills, IL 60061
Phone: 855.384.7754
Fax: 847.383.6256